

bitcoin.conf Configuration File

The configuration file is used by `bitcoind`, `bitcoin-qt` and `bitcoin-cli`.

All command-line options (except for `-?`, `-help`, `-version` and `-conf`) may be specified in a configuration file, and all configuration file options (except for `includeconf`) may also be specified on the command line. Command-line options override values set in the configuration file and configuration file options override values set in the GUI.

Changes to the configuration file while `bitcoind` or `bitcoin-qt` is running only take effect after restarting.

Configuration File Format

The configuration file is a plain text file and consists of `option=value` entries, one per line. Leading and trailing whitespaces are removed.

In contrast to the command-line usage: - an option must be specified without leading `-`; - a value of the given option is mandatory; e.g., `testnet=1` (for chain selection options), `noconnect=1` (for negated options).

Blank lines

Blank lines are allowed and ignored by the parser.

Comments

A comment starts with a number sign (`#`) and extends to the end of the line. All comments are ignored by the parser.

Comments may appear in two ways: - on their own on an otherwise empty line (*preferable*); - after an `option=value` entry.

Network specific options

Network specific options can be: - placed into sections with headers `[main]` (not `[mainnet]`), `[test]` (not `[testnet]`), `[signet]` or `[regtest]`; - prefixed with a chain name; e.g., `regtest.maxmempool=100`.

Network specific options take precedence over non-network specific options. If multiple values for the same option are found with the same precedence, the first one is generally chosen.

This means that given the following configuration, `regtest.rpcport` is set to 3000:

```
regtest=1
rpcport=2000
regtest.rpcport=3000
```

```
[regtest]
rpcport=4000
```

Configuration File Path

The configuration file is not automatically created; you can create it using your favorite text editor. By default, the configuration file name is **bitcoin.conf** and it is located in the Bitcoin data directory, but both the Bitcoin data directory and the configuration file path may be changed using the **-datadir** and **-conf** command-line options.

The **includeconf=<file>** option in the **bitcoin.conf** file can be used to include additional configuration files.

Default configuration file locations

Operating System	Data Directory	Example Path
Windows	%APPDATA%\Bitcoin\	C:\Users\username\AppData\Roaming\Bitcoin\bitc
Linux	\$HOME/.bitcoin/	/home/username/.bitcoin/bitcoin.conf
macOS	\$HOME/Library/Application Support/Bitcoin/	Users/username/Library/Application Support/Bitcoin/bitcoin.conf

You can find an example **bitcoin.conf** file in **share/examples/bitcoin.conf**.