

Configuring CA Certificates

If you're using a private (typically a corporate) package registry that requires a certificate from a CA (certificate authority), you may need to set up the certificate in your `npm`, `yarn`, and `node` config.

Common errors from misconfigured certificates

If you're seeing errors like `unable to get local issuer certificate` in the console output while trying to install a Gatsby plugin, a misconfigured certificate might be the problem. This occurs particularly with plugins or themes that need to be built as native Node.js modules (e.g. `gatsby-plugin-sharp`). It may happen when installing packages from a private registry (via `npm install` or `yarn install`) without an appropriately setup certificate in config.

cafile config option

Both `npm` and `yarn`, support a `cafile` config option. You'll have to add `cafile` as the key, and set the path to your certificate as the value.

Using npm to set cafile

```
npm config set cafile "path-to-my-cert.pem"
```

To check the value of the certificate path at the `cafile` key, use the following command to list all keys in your `npm` config:

```
npm config ls -l
```

Using yarn to set cafile

```
yarn config set cafile "path-to-my-cert.pem"
```

You can now check values in your `yarn` config with the following command:

```
yarn config list
```

Using Node.js

Alternatively, you can also configure this for Node.js on your machine. Export the path to your certificate with the `NODE_EXTRA_CA_CERTS` variable:

```
export NODE_EXTRA_CA_CERTS=["path-to-my-cert.pem"]
```