

This is a simple example that shows the usage of CommonJS.

The three files `example.js`, `increment.js` and `math.js` form a dependency chain. They use `require(dependency)` to declare dependencies.

You can see the output file that webpack creates by bundling them together in one file. Keep in mind that webpack add comments to make reading this file easier. These comments are removed when minimizing the file.

You can also see the info messages that webpack prints to console (for both normal and minimized build).

## example.js

```
const inc = require('./increment').increment;
const a = 1;
inc(a); // 2
```

## increment.js

```
const add = require('./math').add;
exports.increment = function(val) {
  return add(val, 1);
};
```

## math.js

```
exports.add = function() {
  var sum = 0, i = 0, args = arguments, l = args.length;
  while (i < l) {
    sum += args[i++];
  }
  return sum;
};
```

## dist/output.js

```
/***/ ((() => { // webpackBootstrap
/***/      var __webpack_modules__ = ([
/* 0 */,
/* 1 */
/*!*****!\
  !*** ./increment.js ***!
  \*****\
/*! default exports */
```

```

    /*! export increment [provided] [no usage info] [missing usage info prevents
renaming] */
    /*! other exports [not provided] [no usage info] */
    /*! runtime requirements: __webpack_require__, __webpack_exports__ */
    /***/ ((__unused_webpack_module, exports, __webpack_require__) => {

const add = __webpack_require__(/*! ./math */ 2).add;
exports.increment = function(val) {
    return add(val, 1);
};

/***/ }),
/* 2 */
/*!*****!*\
    !*** ./math.js ***!
    \*****/
/*! default exports */
/*! export add [provided] [no usage info] [missing usage info prevents renaming] */
/*! other exports [not provided] [no usage info] */
/*! runtime requirements: __webpack_exports__ */
/***/ ((__unused_webpack_module, exports) => {

exports.add = function() {
    var sum = 0, i = 0, args = arguments, l = args.length;
    while (i < l) {
        sum += args[i++];
    }
    return sum;
};

/***/ })
/*****/
    ]);

```

► /\* webpack runtime code \*/

```

var __webpack_exports__ = {};
// This entry need to be wrapped in an IIFE because it need to be isolated against
other modules in the chunk.
(() => {
    /*!*****!*\
    !*** ./example.js ***!
    \*****/
    /*! unknown exports (runtime-defined) */
    /*! runtime requirements: __webpack_require__ */
    const inc = __webpack_require__(/*! ./increment */ 1).increment;
    const a = 1;
    inc(a); // 2

})();

```

```
/***/ } ) ()  
;
```

## Info

### Unoptimized

```
asset output.js 2.51 KiB [emitted] (name: main)  
chunk (runtime: main) output.js (main) 326 bytes [entry] [rendered]  
  > ./example.js main  
  dependent modules 254 bytes [dependent] 2 modules  
    ./example.js 72 bytes [built] [code generated]  
      [used exports unknown]  
    entry ./example.js main  
webpack 5.51.1 compiled successfully
```

### Production mode

```
asset output.js 310 bytes [emitted] [minimized] (name: main)  
chunk (runtime: main) output.js (main) 326 bytes [entry] [rendered]  
  > ./example.js main  
  dependent modules 254 bytes [dependent] 2 modules  
    ./example.js 72 bytes [built] [code generated]  
      [no exports used]  
    entry ./example.js main  
webpack 5.51.1 compiled successfully
```