# format-stale-output

Format the output of actions/stale into something you can pass to pullreminders/slack-action as blocks.

### Inputs

```
staled-issues-prs
Comes from actions/stale.
closed-issues-prs
```

Comes from actions/stale.

## **Outputs**

#### blocks

Something you can directly pass to pullreminders/slackaction like:

```
- name: Slack Report Closed Issues
uses: pullreminders/slack-action@v1.0.7
env:
    SLACK_BOT_TOKEN: ${{ secrets.SLACK_TOKEN }}
with:
    args: '{\"channel\": \"${{ secrets.SLACK_STALE_CHANNEL_ID }}\", \"text\": \"\",
\"blocks\": ${{ steps.format-stale-output.outputs.blocks }} }'
```

## **Example Usage**

```
name: Stale Bot
 schedule:
   - cron: "0 */12 * * *"
 stale:
   runs-on: ubuntu-latest
   steps:
      - uses: actions/stale@v4
       name: stale
       id: stale
         days-before-stale: 20
         days-before-close: 40
      - name: Format Stale Output
       id: format-stale-output
       uses: ./.github/actions/format-stale-output
          staled-issues-prs: ${{ steps.stale.outputs.staled-issues-prs }}
         closed-issues-prs: ${{ steps.stale.outputs.closed-issues-prs }}
```

```
- name: Slack Report Closed Issues
    uses: pullreminders/slack-action@v1.0.7
    env:
        SLACK_BOT_TOKEN: ${{ secrets.SLACK_TOKEN }}
    with:
        args: '{\"channel\": \"${{ secrets.SLACK_STALE_CHANNEL_ID }}\", \"text\":
\"\", \"blocks\": ${{ steps.format-stale-output.outputs.blocks }} }'
```

## **Building this Action**

Use <a href="Movements-left">@vercel/ncc</a> to compile this action. You can run <a href="movements-left">npm</a> run <a href="movements-left">build</a> in this directory to run the command.