

An introduction to machine learning with scikit-learn

Section contents

In this section, we introduce the [machine learning](#) vocabulary that we use throughout scikit-learn and give a simple learning example.

Machine learning: the problem setting

In general, a learning problem considers a set of n [samples](#) of data and then tries to predict properties of unknown data. If each sample is more than a single number and, for instance, a multi-dimensional entry (aka [multivariate](#) data), it is said to have several attributes or **features**.

Learning problems fall into a few categories:

- [supervised learning](#), in which the data comes with additional attributes that we want to predict ([ref: Click here <supervised-learning>](#) to go to the scikit-learn supervised learning page). This problem can be either:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\tutorial\basic\ (scikit-learn-main) (doc) (tutorial) (basic) tutorial.rst, line 26); [backlink](#)

Unknown interpreted text role "ref".

- [classification](#): samples belong to two or more classes and we want to learn from already labeled data how to predict the class of unlabeled data. An example of a classification problem would be handwritten digit recognition, in which the aim is to assign each input vector to one of a finite number of discrete categories. Another way to think of classification is as a discrete (as opposed to continuous) form of supervised learning where one has a limited number of categories and for each of the n samples provided, one is to try to label them with the correct category or class.
 - [regression](#): if the desired output consists of one or more continuous variables, then the task is called *regression*. An example of a regression problem would be the prediction of the length of a salmon as a function of its age and weight.
- [unsupervised learning](#), in which the training data consists of a set of input vectors x without any corresponding target values. The goal in such problems may be to discover groups of similar examples within the data, where it is called [clustering](#), or to determine the distribution of data within the input space, known as [density estimation](#), or to project the data from a high-dimensional space down to two or three dimensions for the purpose of *visualization* ([ref: Click here <unsupervised-learning>](#) to go to the Scikit-Learn unsupervised learning page).

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\tutorial\basic\ (scikit-learn-main) (doc) (tutorial) (basic) tutorial.rst, line 50); [backlink](#)

Unknown interpreted text role "ref".

Training set and testing set

Machine learning is about learning some properties of a data set and then testing those properties against another data set. A common practice in machine learning is to evaluate an algorithm by splitting a data set into two. We call one of those sets the **training set**, on which we learn some properties; we call the other set the **testing set**, on which we test the learned properties.

Loading an example dataset

scikit-learn comes with a few standard datasets, for instance the [iris](#) and [digits](#) datasets for classification and the [diabetes dataset](#) for regression.

In the following, we start a Python interpreter from our shell and then load the `iris` and `digits` datasets. Our notational convention is that `$` denotes the shell prompt while `>>>` denotes the Python interpreter prompt:

```
$ python
>>> from sklearn import datasets
>>> iris = datasets.load_iris()
>>> digits = datasets.load_digits()
```

A dataset is a dictionary-like object that holds all the data and some metadata about the data. This data is stored in the `.data`

member, which is a `n_samples, n_features` array. In the case of supervised problem, one or more response variables are stored in the `.target` member. More details on the different datasets can be found in the [ref: dedicated section <datasets>](#).

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\tutorial\basic\ (scikit-learn-main) (doc) (tutorial) (basic) tutorial.rst, line 93); [backlink](#)

Unknown interpreted text role "ref".

For instance, in the case of the digits dataset, `digits.data` gives access to the features that can be used to classify the digits samples:

```
>>> print(digits.data)
[[ 0.  0.  5. ...  0.  0.  0.]
 [ 0.  0.  0. ... 10.  0.  0.]
 [ 0.  0.  0. ... 16.  9.  0.]
 ...
 [ 0.  0.  1. ...  6.  0.  0.]
 [ 0.  0.  2. ... 12.  0.  0.]
 [ 0.  0. 10. ... 12.  1.  0.]
```

and `digits.target` gives the ground truth for the digit dataset, that is the number corresponding to each digit image that we are trying to learn:

```
>>> digits.target
array([0, 1, 2, ..., 8, 9, 8])
```

Shape of the data arrays

The data is always a 2D array, shape `(n_samples, n_features)`, although the original data may have had a different shape. In the case of the digits, each original sample is an image of shape `(8, 8)` and can be accessed using:

```
>>> digits.images[0]
array([[ 0.,  0.,  5., 13.,  9.,  1.,  0.,  0.],
       [ 0.,  0., 13., 15., 10., 15.,  5.,  0.],
       [ 0.,  3., 15.,  2.,  0., 11.,  8.,  0.],
       [ 0.,  4., 12.,  0.,  0.,  8.,  8.,  0.],
       [ 0.,  5.,  8.,  0.,  0.,  9.,  8.,  0.],
       [ 0.,  4., 11.,  0.,  1., 12.,  7.,  0.],
       [ 0.,  2., 14.,  5., 10., 12.,  0.,  0.],
       [ 0.,  0.,  6., 13., 10.,  0.,  0.,  0.]])
```

The [ref: simple example on this dataset <sphinx_glr_auto_examples_classification_plot_digits_classification.py>](#) illustrates how starting from the original problem one can shape the data for consumption in scikit-learn.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\tutorial\basic\ (scikit-learn-main) (doc) (tutorial) (basic) tutorial.rst, line 136); [backlink](#)

Unknown interpreted text role "ref".

Loading from external datasets

To load from an external dataset, please refer to [ref: loading external datasets <external_datasets>](#).

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\tutorial\basic\ (scikit-learn-main) (doc) (tutorial) (basic) tutorial.rst, line 143); [backlink](#)

Unknown interpreted text role "ref".

Learning and predicting

In the case of the digits dataset, the task is to predict, given an image, which digit it represents. We are given samples of each of the 10 possible classes (the digits zero through nine) on which we *fit* an [estimator](#) to be able to *predict* the classes to which unseen samples belong.

In scikit-learn, an estimator for classification is a Python object that implements the methods `fit(X, y)` and `predict(T)`.

An example of an estimator is the class `sklearn.svm.SVC`, which implements [support vector classification](#). The estimator's constructor takes as arguments the model's parameters.

For now, we will consider the estimator as a black box:

```
>>> from sklearn import svm
>>> clf = svm.SVC(gamma=0.001, C=100.)
```

Choosing the parameters of the model

In this example, we set the value of `gamma` manually. To find good values for these parameters, we can use tools such as `ref`grid search <grid_search>`` and `ref`cross validation <cross_validation>``.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\tutorial\basic\scikit-learn-main) (doc) (tutorial) (basic) tutorial.rst, line 169); [backlink](#)

Unknown interpreted text role "ref".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\tutorial\basic\scikit-learn-main) (doc) (tutorial) (basic) tutorial.rst, line 169); [backlink](#)

Unknown interpreted text role "ref".

The `clf` (for classifier) estimator instance is first fitted to the model; that is, it must *learn* from the model. This is done by passing our training set to the `fit` method. For the training set, we'll use all the images from our dataset, except for the last image, which we'll reserve for our predicting. We select the training set with the `[:-1]` Python syntax, which produces a new array that contains all but the last item from `digits.data`:

```
>>> clf.fit(digits.data[:-1], digits.target[:-1])
SVC(C=100.0, gamma=0.001)
```

Now you can *predict* new values. In this case, you'll predict using the last image from `digits.data`. By predicting, you'll determine the image from the training set that best matches the last image.

```
>>> clf.predict(digits.data[-1:])
array([8])
```

The corresponding image is:



As you can see, it is a challenging task: after all, the images are of poor resolution. Do you agree with the classifier?

A complete example of this classification problem is available as an example that you can run and study:

`ref`sphx_glr_auto_examples_classification_plot_digits_classification.py``.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\tutorial\basic\scikit-learn-main) (doc) (tutorial) (basic) tutorial.rst, line 203); [backlink](#)

Unknown interpreted text role "ref".

Conventions

scikit-learn estimators follow certain rules to make their behavior more predictive. These are described in more detail in the `ref`glossary``.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\tutorial\basic\scikit-learn-main) (doc) (tutorial) (basic) tutorial.rst, line 210); [backlink](#)

Unknown interpreted text role "ref".

Type casting

Unless otherwise specified, input will be cast to `float64`:

```
>>> import numpy as np
>>> from sklearn import kernel_approximation

>>> rng = np.random.RandomState(0)
>>> X = rng.rand(10, 2000)
>>> X = np.array(X, dtype='float32')
>>> X.dtype
dtype('float32')
```

```
>>> transformer = kernel_approximation.RBFSampler()
>>> X_new = transformer.fit_transform(X)
>>> X_new.dtype
dtype('float64')
```

In this example, X is float32, which is cast to float64 by fit_transform(X).

Regression targets are cast to float64 and classification targets are maintained:

```
>>> from sklearn import datasets
>>> from sklearn.svm import SVC
>>> iris = datasets.load_iris()
>>> clf = SVC()
>>> clf.fit(iris.data, iris.target)
SVC()

>>> list(clf.predict(iris.data[:3]))
[0, 0, 0]

>>> clf.fit(iris.data, iris.target_names[iris.target])
SVC()

>>> list(clf.predict(iris.data[:3]))
['setosa', 'setosa', 'setosa']
```

Here, the first predict() returns an integer array, since iris.target (an integer array) was used in fit. The second predict() returns a string array, since iris.target_names was for fitting.

Refitting and updating parameters

Hyper-parameters of an estimator can be updated after it has been constructed via the `term`set_params()<set_params>`` method. Calling fit() more than once will overwrite what was learned by any previous fit():

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\tutorial\basic\scikit-learn-main) (doc) (tutorial) (basic) tutorial.rst, line 261); [backlink](#)

Unknown interpreted text role "term".

```
>>> import numpy as np
>>> from sklearn.datasets import load_iris
>>> from sklearn.svm import SVC
>>> X, y = load_iris(return_X_y=True)

>>> clf = SVC()
>>> clf.set_params(kernel='linear').fit(X, y)
SVC(kernel='linear')
>>> clf.predict(X[:5])
array([0, 0, 0, 0, 0])

>>> clf.set_params(kernel='rbf').fit(X, y)
SVC()
>>> clf.predict(X[:5])
array([0, 0, 0, 0, 0])
```

Here, the default kernel rbf is first changed to linear via `func`SVC.set_params()<sklearn.svm.SVC.set_params>`` after the estimator has been constructed, and changed back to rbf to refit the estimator and to make a second prediction.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\tutorial\basic\scikit-learn-main) (doc) (tutorial) (basic) tutorial.rst, line 281); [backlink](#)

Unknown interpreted text role "func".

Multiclass vs. multilabel fitting

When using `class`multiclass classifiers <sklearn.multiclass>``, the learning and prediction task that is performed is dependent on the format of the target data fit upon:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\tutorial\basic\scikit-learn-main) (doc) (tutorial) (basic) tutorial.rst, line 289); [backlink](#)

Unknown interpreted text role "class".

```
>>> from sklearn.svm import SVC
>>> from sklearn.multiclass import OneVsRestClassifier
>>> from sklearn.preprocessing import LabelBinarizer

>>> X = [[1, 2], [2, 4], [4, 5], [3, 2], [3, 1]]
>>> y = [0, 0, 1, 1, 2]

>>> classif = OneVsRestClassifier(estimator=SVC(random_state=0))
>>> classif.fit(X, y).predict(X)
array([0, 0, 1, 1, 2])
```

In the above case, the classifier is fit on a 1d array of multiclass labels and the `predict()` method therefore provides corresponding multiclass predictions. It is also possible to fit upon a 2d array of binary label indicators:

```
>>> y = LabelBinarizer().fit_transform(y)
>>> classif.fit(X, y).predict(X)
array([[1, 0, 0],
       [1, 0, 0],
       [0, 1, 0],
       [0, 0, 0],
       [0, 0, 0]])
```

Here, the classifier is `fit()` on a 2d binary label representation of `y`, using the `class: 'LabelBinarizer' <sklearn.preprocessing.LabelBinarizer>`. In this case `predict()` returns a 2d array representing the corresponding multilabel predictions.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\tutorial\basic\scikit-learn-main) (doc) (tutorial) (basic) tutorial.rst, line 316); [backlink](#)

Unknown interpreted text role "class".

Note that the fourth and fifth instances returned all zeroes, indicating that they matched none of the three labels `fit` upon. With multilabel outputs, it is similarly possible for an instance to be assigned multiple labels:

```
>>> from sklearn.preprocessing import MultiLabelBinarizer
>>> y = [[0, 1], [0, 2], [1, 3], [0, 2, 3], [2, 4]]
>>> y = MultiLabelBinarizer().fit_transform(y)
>>> classif.fit(X, y).predict(X)
array([[1, 1, 0, 0, 0],
       [1, 0, 1, 0, 0],
       [0, 1, 0, 1, 0],
       [1, 0, 1, 0, 0],
       [1, 0, 1, 0, 0]])
```

In this case, the classifier is fit upon instances each assigned multiple labels. The `class: 'MultiLabelBinarizer' <sklearn.preprocessing.MultiLabelBinarizer>` is used to binarize the 2d array of multilabels to `fit` upon. As a result, `predict()` returns a 2d array with multiple predicted labels for each instance.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\tutorial\basic\scikit-learn-main) (doc) (tutorial) (basic) tutorial.rst, line 335); [backlink](#)

Unknown interpreted text role "class".