

PrinterInfo Object

- `name` string - the name of the printer as understood by the OS.
- `displayName` string - the name of the printer as shown in Print Preview.
- `description` string - a longer description of the printer's type.
- `status` number - the current status of the printer.
- `isDefault` boolean - whether or not a given printer is set as the default printer on the OS.
- `options` Object - an object containing a variable number of platform-specific printer information.

The number represented by `status` means different things on different platforms: on Windows its potential values can be found [here](#), and on Linux and macOS they can be found [here](#).

Example

Below is an example of some of the additional options that may be set which may be different on each platform.

```
{
  name: 'Austin_4th_Floor_Printer___C02XK13BJHD4',
  displayName: 'Austin 4th Floor Printer @ C02XK13BJHD4',
  description: 'TOSHIBA ColorMFP',
  status: 3,
  isDefault: false,
  options: {
    copies: '1',
    'device-uri':
'dnssd://Austin%204th%20Floor%20Printer%20%40%20C02XK13BJHD4._ipps._tcp.local./?
uuid=71687f1e-1147-3274-6674-22de61b110bd',
    finishings: '3',
    'job-cancel-after': '10800',
    'job-hold-until': 'no-hold',
    'job-priority': '50',
    'job-sheets': 'none,none',
    'marker-change-time': '0',
    'number-up': '1',
    'printer-commands':
'ReportLevels,PrintSelfTestPage,com.toshiba.ColourProfiles.update,com.toshiba.EFiling.

    'printer-info': 'Austin 4th Floor Printer @ C02XK13BJHD4',
    'printer-is-accepting-jobs': 'true',
    'printer-is-shared': 'false',
    'printer-is-temporary': 'false',
    'printer-location': '',
    'printer-make-and-model': 'TOSHIBA ColorMFP',
    'printer-state': '3',
    'printer-state-change-time': '1573472937',
    'printer-state-reasons': 'offline-report,com.toshiba.snmp.failed',
    'printer-type': '10531038',
    'printer-uri-supported':
'ipp://localhost/printers/Austin_4th_Floor_Printer___C02XK13BJHD4',
    system_driverinfo: 'T'
```

