

:mod:`timeit` --- Measure execution time of small code snippets

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 1); [backlink](#)

Unknown interpreted text role "mod".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 4)

Unknown directive type "module".

```
.. module:: timeit
   :synopsis: Measure the execution time of small code snippets.
```

Source code: `:source:`Lib/timeit.py``

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 7); [backlink](#)

Unknown interpreted text role "source".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 9)

Unknown directive type "index".

```
.. index::
   single: Benchmarking
   single: Performance
```

This module provides a simple way to time small bits of Python code. It has both a `:ref:`timeit-command-line-interface`` as well as a `:ref:`callable <python-interface>` one. It avoids a number of common traps for measuring execution times. See also Tim Peters' introduction to the "Algorithms" chapter in the second edition of *Python Cookbook*, published by O'Reilly.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 15); [backlink](#)

Unknown interpreted text role "ref".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 15); [backlink](#)

Unknown interpreted text role "ref".

Basic Examples

The following example shows how the `:ref:`timeit-command-line-interface`` can be used to compare three different expressions:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 25); [backlink](#)

Unknown interpreted text role "ref".

```
$ python3 -m timeit '"-".join(str(n) for n in range(100))'
10000 loops, best of 5: 30.2 usec per loop
$ python3 -m timeit '"-".join([str(n) for n in range(100)])'
10000 loops, best of 5: 27.5 usec per loop
$ python3 -m timeit '"-".join(map(str, range(100)))'
10000 loops, best of 5: 23.2 usec per loop
```

This can be achieved from the `:ref:`python-interface`` with:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 37); [backlink](#)

Unknown interpreted text role "ref".

```
>>> import timeit
>>> timeit.timeit('"-".join(str(n) for n in range(100))', number=10000)
```

```
0.3018611848820001
>>> timeit.timeit('"-".join([str(n) for n in range(100)])', number=10000)
0.2727368790656328
>>> timeit.timeit('"-".join(map(str, range(100)))', number=10000)
0.23702679807320237
```

A callable can also be passed from the [ref`python-interface`](#):

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 47); [backlink](#)

Unknown interpreted text role "ref".

```
>>> timeit.timeit(lambda: "-".join(map(str, range(100))), number=10000)
0.19665591977536678
```

Note however that `:func:`timeit`` will automatically determine the number of repetitions only when the command-line interface is used. In the [ref`timeit-examples`](#) section you can find more advanced examples.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 52); [backlink](#)

Unknown interpreted text role "func".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 52); [backlink](#)

Unknown interpreted text role "ref".

Python Interface

The module defines three convenience functions and a public class:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 65)

Unknown directive type "function".

```
.. function:: timeit(stmt='pass', setup='pass', timer=<default timer>, number=1000000, globals=None)

Create a :class:`Timer` instance with the given statement, *setup* code and
*timer* function and run its :meth:`.timeit` method with *number* executions.
The optional *globals* argument specifies a namespace in which to execute the
code.

.. versionchanged:: 3.5
   The optional *globals* parameter was added.
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 76)

Unknown directive type "function".

```
.. function:: repeat(stmt='pass', setup='pass', timer=<default timer>, repeat=5, number=1000000, globals=None)

Create a :class:`Timer` instance with the given statement, *setup* code and
*timer* function and run its :meth:`.repeat` method with the given *repeat*
count and *number* executions. The optional *globals* argument specifies a
namespace in which to execute the code.

.. versionchanged:: 3.5
   The optional *globals* parameter was added.

.. versionchanged:: 3.7
   Default value of *repeat* changed from 3 to 5.
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 89)

Unknown directive type "function".

```
.. function:: default_timer()

The default timer, which is always :func:`time.perf_counter`.

.. versionchanged:: 3.3
   :func:`time.perf_counter` is now the default timer.
```

Class for timing execution speed of small code snippets.

The constructor takes a statement to be timed, an additional statement used for setup, and a timer function. Both statements default to 'pass'; the timer function is platform-dependent (see the module doc string). *stmt* and *setup* may also contain multiple statements separated by ; or newlines, as long as they don't contain multi-line string literals. The statement will by default be executed within *timeit*'s namespace; this behavior can be controlled by passing a namespace to *globals*.

To measure the execution time of the first statement, use the `meth.timeit` method. The `meth.repeat` and `meth.autorange` methods are convenience methods to call `meth.timeit` multiple times.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) timeit.rst, line 109); [backlink](#)

Unknown interpreted text role "meth".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) timeit.rst, line 109); [backlink](#)

Unknown interpreted text role "meth".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) timeit.rst, line 109); [backlink](#)

Unknown interpreted text role "meth".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) timeit.rst, line 109); [backlink](#)

Unknown interpreted text role "meth".

The execution time of *setup* is excluded from the overall timed execution run.

The *stmt* and *setup* parameters can also take objects that are callable without arguments. This will embed calls to them in a timer function that will then be executed by `meth.timeit`. Note that the timing overhead is a little larger in this case because of the extra function calls.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) timeit.rst, line 115); [backlink](#)

Unknown interpreted text role "meth".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) timeit.rst, line 120)

Unknown directive type "versionchanged".

```
.. versionchanged:: 3.5
   The optional *globals* parameter was added.
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) timeit.rst, line 123)

Unknown directive type "method".

```
.. method:: Timer.timeit(number=1000000)
```

Time **number** executions of the main statement. This executes the setup statement once, and then returns the time it takes to execute the main statement a number of times, measured in seconds as a float. The argument is the number of times through the loop, defaulting to one million. The main statement, the setup statement and the timer function to be used are passed to the constructor.

```
.. note::
```

By default, `:meth:`timeit`` temporarily turns off `:term:`garbage collection`` during the timing. The advantage of this approach is that it makes independent timings more comparable. The disadvantage is that GC may be an important component of the performance of the function being measured. If so, GC can be re-enabled as the first statement in the **setup** string. For example::

```
timeit.Timer('for i in range(10): oct(i)', 'gc.enable()').timeit()
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) timeit.rst, line 144)

Unknown directive type "method".

```
.. method:: Timer.autorange(callback=None)
```

Automatically determine how many times to call :meth:`.timeit`.

This is a convenience function that calls :meth:`.timeit` repeatedly so that the total time ≥ 0.2 second, returning the eventual (number of loops, time taken for that number of loops). It calls :meth:`.timeit` with increasing numbers from the sequence 1, 2, 5, 10, 20, 50, ... until the time taken is at least 0.2 second.

If **callback** is given and is not ``None``, it will be called after each trial with two arguments: ``callback(number, time_taken)``.

```
.. versionadded:: 3.6
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) timeit.rst, line 160)

Unknown directive type "method".

```
.. method:: Timer.repeat(repeat=5, number=1000000)
```

Call :meth:`.timeit` a few times.

This is a convenience function that calls the :meth:`.timeit` repeatedly, returning a list of results. The first argument specifies how many times to call :meth:`.timeit`. The second argument specifies the **number** argument for :meth:`.timeit`.

```
.. note::
```

It's tempting to calculate mean and standard deviation from the result vector and report these. However, this is not very useful. In a typical case, the lowest value gives a lower bound for how fast your machine can run the given code snippet; higher values in the result vector are typically not caused by variability in Python's speed, but by other processes interfering with your timing accuracy. So the :func:`min` of the result is probably the only number you should be interested in. After that, you should look at the entire vector and apply common sense rather than statistics.

```
.. versionchanged:: 3.7
   Default value of *repeat* changed from 3 to 5.
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) timeit.rst, line 185)

Unknown directive type "method".

```
.. method:: Timer.print_exc(file=None)
```

Helper to print a traceback from the timed code.

Typical use::

```
    t = Timer(...)          # outside the try/except
    try:
        t.timeit(...)       # or t.repeat(...)
    except Exception:
        t.print_exc()
```

The advantage over the standard traceback is that source lines in the compiled template will be displayed. The optional **file** argument directs where the traceback is sent; it defaults to :data:`sys.stderr`.

Command-Line Interface

When called as a program from the command line, the following form is used:

```
python -m timeit [-n N] [-r N] [-u U] [-s S] [-h] [statement ...]
```

Where the following options are understood:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) timeit.rst, line 213)

Unknown directive type "program".

```
.. program:: timeit
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 215)

Unknown directive type "cmdoption".

```
.. cmdoption:: -n N, --number=N
    how many times to execute 'statement'
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 219)

Unknown directive type "cmdoption".

```
.. cmdoption:: -r N, --repeat=N
    how many times to repeat the timer (default 5)
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 223)

Unknown directive type "cmdoption".

```
.. cmdoption:: -s S, --setup=S
    statement to be executed once initially (default ``pass``)
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 227)

Unknown directive type "cmdoption".

```
.. cmdoption:: -p, --process
    measure process time, not wallclock time, using :func:`time.process_time`
    instead of :func:`time.perf_counter`, which is the default

.. versionadded:: 3.3
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 234)

Unknown directive type "cmdoption".

```
.. cmdoption:: -u, --unit=U
    specify a time unit for timer output; can select ``nsec``, ``usec``, ``msec``, or ``sec``

.. versionadded:: 3.5
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 240)

Unknown directive type "cmdoption".

```
.. cmdoption:: -v, --verbose
    print raw timing results; repeat for more digits precision
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 244)

Unknown directive type "cmdoption".

```
.. cmdoption:: -h, --help
    print a short usage message and exit
```

A multi-line statement may be given by specifying each line as a separate statement argument; indented lines are possible by enclosing an argument in quotes and using leading spaces. Multiple `:option:`-s`` options are treated similarly.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 248); [backlink](#)

Unknown interpreted text role "option".

If `:option:'-n'` is not given, a suitable number of loops is calculated by trying increasing numbers from the sequence 1, 2, 5, 10, 20, 50, ... until the total time is at least 0.2 seconds.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) `timeit.rst`, line 253); [backlink](#)

Unknown interpreted text role "option".

`:func:'default_timer'` measurements can be affected by other programs running on the same machine, so the best thing to do when accurate timing is necessary is to repeat the timing a few times and use the best time. The `:option:'-r'` option is good for this; the default of 5 repetitions is probably enough in most cases. You can use `:func:'time.process_time'` to measure CPU time.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) `timeit.rst`, line 257); [backlink](#)

Unknown interpreted text role "func".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) `timeit.rst`, line 257); [backlink](#)

Unknown interpreted text role "option".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) `timeit.rst`, line 257); [backlink](#)

Unknown interpreted text role "func".

Note

There is a certain baseline overhead associated with executing a pass statement. The code here doesn't try to hide it, but you should be aware of it. The baseline overhead can be measured by invoking the program without arguments, and it might differ between Python versions.

Examples

It is possible to provide a setup statement that is executed only once at the beginning:

```
$ python -m timeit -s 'text = "sample string"; char = "g"' 'char in text'
5000000 loops, best of 5: 0.0877 usec per loop
$ python -m timeit -s 'text = "sample string"; char = "g"' 'text.find(char)'
1000000 loops, best of 5: 0.342 usec per loop
```

In the output, there are three fields. The loop count, which tells you how many times the statement body was run per timing loop repetition. The repetition count ('best of 5') which tells you how many times the timing loop was repeated, and finally the time the statement body took on average within the best repetition of the timing loop. That is, the time the fastest repetition took divided by the loop count.

```
>>> import timeit
>>> timeit.timeit('char in text', setup='text = "sample string"; char = "g"')
0.41440500499993504
>>> timeit.timeit('text.find(char)', setup='text = "sample string"; char = "g"')
1.7246671520006203
```

The same can be done using the `:class:'Timer'` class and its methods:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) `timeit.rst`, line 300); [backlink](#)

Unknown interpreted text role "class".

```
>>> import timeit
>>> t = timeit.Timer('char in text', setup='text = "sample string"; char = "g"')
>>> t.timeit()
0.3955516149999312
>>> t.repeat()
[0.40183617287970225, 0.37027556854118704, 0.38344867356679524, 0.3712595970846668, 0.37866875250654886]
```

The following examples show how to time expressions that contain multiple lines. Here we compare the cost of using `:func:'hasattr'` vs. `:keyword:'try'/'keyword:'except'` to test for missing and present object attributes:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) `timeit.rst`, line 310); [backlink](#)

Unknown interpreted text role "func".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\cpython-main) (Doc) (library) `timeit.rst`, line 310); [backlink](#)

Unknown interpreted text role "keyword".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 310); [backlink](#)

Unknown interpreted text role "keyword".

```
$ python -m timeit 'try: ' ' str.__bool__ ' 'except AttributeError: ' ' pass'
20000 loops, best of 5: 15.7 usec per loop
$ python -m timeit 'if hasattr(str, "__bool__"): pass'
50000 loops, best of 5: 4.26 usec per loop

$ python -m timeit 'try: ' ' int.__bool__ ' 'except AttributeError: ' ' pass'
200000 loops, best of 5: 1.43 usec per loop
$ python -m timeit 'if hasattr(int, "__bool__"): pass'
100000 loops, best of 5: 2.23 usec per loop
```

```
>>> import timeit
>>> # attribute is missing
>>> s = ""
... try:
...     str.__bool__
... except AttributeError:
...     pass
... ""
>>> timeit.timeit(stmt=s, number=100000)
0.9138244460009446
>>> s = "if hasattr(str, '__bool__'): pass"
>>> timeit.timeit(stmt=s, number=100000)
0.5829014980008651
>>>
>>> # attribute is present
>>> s = ""
... try:
...     int.__bool__
... except AttributeError:
...     pass
... ""
>>> timeit.timeit(stmt=s, number=100000)
0.04215312199994514
>>> s = "if hasattr(int, '__bool__'): pass"
>>> timeit.timeit(stmt=s, number=100000)
0.08588060699912603
```

To give the `mod:timeit` module access to functions you define, you can pass a *setup* parameter which contains an import statement:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 356); [backlink](#)

Unknown interpreted text role "mod".

```
def test():
    """Stupid test function"""
    L = [i for i in range(100)]

if __name__ == '__main__':
    import timeit
    print(timeit.timeit("test()", setup="from __main__ import test"))
```

Another option is to pass `func:globals` to the *globals* parameter, which will cause the code to be executed within your current global namespace. This can be more convenient than individually specifying imports:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library) timeit.rst, line 367); [backlink](#)

Unknown interpreted text role "func".

```
def f(x):
    return x**2
def g(x):
    return x**4
def h(x):
    return x**8

import timeit
print(timeit.timeit('[func(42) for func in (f,g,h)]', globals=globals()))
```