

npm-profile

Synopsis

```
npm profile enable-2fa [auth-only|auth-and-writes]
npm profile disable-2fa
npm profile get [<key>]
npm profile set <key> <value>
```

Note: This command is unaware of workspaces.

Description

Change your profile information on the registry. Note that this command depends on the registry implementation, so third-party registries may not support this interface.

- `npm profile get [<property>]`: Display all of the properties of your profile, or one or more specific properties. It looks like:

name	example
email	me@example.com (verified)
two factor auth	auth-and-writes
fullname	Example User
homepage	
freenode	
twitter	
github	
created	2015-02-26T01:38:35.892Z

| updated | 2017-10-02T21:29:45.922Z |
+-----+-----+

- **npm profile set <property> <value>**: Set the value of a profile property. You can set the following properties this way: email, fullname, homepage, freenode, twitter, github
- **npm profile set password**: Change your password. This is interactive, you'll be prompted for your current password and a new password. You'll also be prompted for an OTP if you have two-factor authentication enabled.
- **npm profile enable-2fa [auth-and-writes|auth-only]**: Enables two-factor authentication. Defaults to **auth-and-writes** mode. Modes are:
 - **auth-only**: Require an OTP when logging in or making changes to your account's authentication. The OTP will be required on both the website and the command line.
 - **auth-and-writes**: Requires an OTP at all the times **auth-only** does, and also requires one when publishing a module, setting the **latest** dist-tag, or changing access via **npm access** and **npm owner**.
- **npm profile disable-2fa**: Disables two-factor authentication.

Details

Some of these commands may not be available on non npmjs.com registries.

Configuration

registry

- Default: "https://registry.npmjs.org/"
- Type: URL

The base URL of the npm registry.

json

- Default: false
- Type: Boolean

Whether or not to output JSON data, rather than the normal output.

- In **npm pkg set** it enables parsing set values with `JSON.parse()` before saving them to your **package.json**.

Not supported by all npm commands.

parseable

- Default: false
- Type: Boolean

Output parseable results from commands that write to standard output. For **npm search**, this will be tab-separated table format.

otp

- Default: null
- Type: null or String

This is a one-time password from a two-factor authenticator. It's needed when publishing or changing package permissions with **npm access**.

If not set, and a registry response fails with a challenge for a one-time password, npm will prompt on the command line for one.

See Also

- **npm adduser**
- **npm registry**
- **npm config**
- **npmrc**
- **npm owner**
- **npm whoami**
- **npm token**