

## Card

Integrate information in a card container.

### Basic usage

Card includes title, content and operations.

:::demo Card is made up of `header` and `body`. `header` is optional, and its content distribution depends on a named slot.

```
<el-card class="box-card">
  <div slot="header" class="clearfix">
    <span>Card name</span>
    <el-button style="float: right; padding: 3px 0" type="text">Operation button</el-button>
  </div>
  <div v-for="o in 4" :key="o" class="text item">
    {{'List item ' + o }}
  </div>
</el-card>

<style>
  .text {
    font-size: 14px;
  }

  .item {
    margin-bottom: 18px;
  }

  .clearfix:before,
  .clearfix:after {
    display: table;
    content: "";
  }
  .clearfix:after {
    clear: both
  }

  .box-card {
    width: 480px;
  }
</style>

:::
```

## Simple card

The header part can be omitted.

```
<el-card class="box-card">
  <div v-for="o in 4" :key="o" class="text item">
    {{'List item ' + o }}
  </div>
</el-card>
```

```
<style>
  .text {
    font-size: 14px;
  }

  .item {
    padding: 18px 0;
  }

  .box-card {
    width: 480px;
  }
</style>
```

## With images

Display richer content by adding some configs.

:::demo The `body-style` attribute defines CSS style of custom body. This example also uses `el-col` for layout.

```
<el-row>
  <el-col :span="8" v-for="(o, index) in 2" :key="o" :offset="index > 0 ? 2 : 0">
    <el-card :body-style="{ padding: '0px' }">
      
      <div style="padding: 14px;">
        <span>Yummy hamburger</span>
        <div class="bottom clearfix">
          <time class="time">{{ currentDate }}</time>
          <el-button type="text" class="button">Operating</el-button>
        </div>
      </div>
    </el-card>
  </el-col>
</el-row>

<style>
  .time {
```

```

    font-size: 13px;
    color: #999;
  }

  .bottom {
    margin-top: 13px;
    line-height: 12px;
  }

  .button {
    padding: 0;
    float: right;
  }

  .image {
    width: 100%;
    display: block;
  }

  .clearfix:before,
  .clearfix:after {
    display: table;
    content: "";
  }

  .clearfix:after {
    clear: both
  }
</style>

<script>
export default {
  data() {
    return {
      currentDate: new Date()
    };
  }
}
</script>
:::

```

## Shadow

You can define when to show the card shadows

:::demo The **shadow** attribute determines when the card shadows are displayed.

It can be `always`, `hover` or `never`.

```
<el-row :gutter="12">
  <el-col :span="8">
    <el-card shadow="always">
      Always
    </el-card>
  </el-col>
  <el-col :span="8">
    <el-card shadow="hover">
      Hover
    </el-card>
  </el-col>
  <el-col :span="8">
    <el-card shadow="never">
      Never
    </el-card>
  </el-col>
</el-row>

:::
```

### Attributes

Attribute	Description	Type	Accepted Values	Default
header	title of the card. Also accepts a DOM passed by <code>slot#header</code>	string	—	—
body-style	CSS style of body	object	—	{ padding: '20px' }
shadow	when to show card shadows	string	always / hover / never	always