

Basically, antd naming requires **FULL NAME** instead of Abbreviation.

Props

- Initialize prop: **default + PropName**
- Force render: **forceRender**
 - Force render sub component: **force + Sub Component Name + Render**
- Sub render: **Sub Component Name + Render**
- Data Source: **dataSource**
- Panel visible: **popup only visible**, **dropdown open**, **additional popup**
popupName + Visible like **tooltipVisible**
- **children**:
 - Mainly display content. To avoid additional prop name.
 - Option list like **Select.Option** or **Tree.TreeNode**.
 - Customize wrapped component can consider use **component** prop if **children** may have other usage in future.
- Display related naming: **show + PropName**
- Functional: **PropName + able**
- Disable: **disabled**
 - sub component: **disabled + Sub Component Name**
- mainly icon: **icon**
 - Merge with function first: **functionName: { icon }**. e.g. **expandable: { icon: <Smile /> }**
 - Multiple icons: **FunctionName + Icon**
- Trigger: **trigger**
 - Sub function trigger: **Sub Function + Trigger**
 - Trigger on the time point: **xxx + On + EventName** (e.g. **destroyOnClose**)
- Component use other component config. Naming as component. (e.g. **<Table pagination={{...}} />**)

Event

- Trigger event: **on + EventName**
 - Trigger sub component event: **on + SubComponentName + EventName** (e.g. **onSearchChange**)
 - Trigger prop event: **on + PropName + EventName** (e.g. **onDragStart**)
- Before trigger event: **before + EventName**
- After trigger event: **after + EventName**

Current listing api & Chinese version

ref: #16048

API standard in the document

Examples

Property	Description	Type	Default
htmlType	xxx	string	button
type	xxx	horizontal vertical	horizontal
disabled	xxx	boolean	false
minLength	xxx	number	0
style	xxx	CSSProperties	-
character	xxx	(props) => ReactNode	-
offset	xxx	[number, number]	[0, 0]
value	xxx	string number	small

Promise

- When string type, the **Default** use ``.
- Can also list string optional values in **Type**.
- When boolean type, the **Default** value is true or false.
- When number type, the **Default** value use numbers directly.
- When function type, use an arrow function expression in **Type**.
- No default value use - .
- Capitalize the first letter in **Description** apart from **someProp**.
- No period at the end of the **Description**.
- API order is arranged in alphabetical order, and can be put together under special circumstances (such as: xs sm md).

ref: #25066