

# **Neural Architecture Search (NAS) for Medical Image Segmentation**

---

**Dr. Susana Lai-Yuen**

Associate Professor

Industrial & Management Systems Engineering  
University of South Florida

Visiting Professor

Visual Computing and Machine Intelligence (VCMI)  
INESC TEC, Porto


March 20, 2024

# Outline


- Neural Architecture Search (NAS)
- Multi-Objective NAS
- **NAS for Medical Image Segmentation**
  - Medical Image Segmentation
  - Efficient Multi-objective NAS (EMONAS-Net)
  - Experiments and Results

# Deep Neural Networks


- Automatically learn features from data through multiple layers of abstraction
- Very successful in many applications:
  - Computer vision
  - Object recognition
  - Image segmentation



Source: <https://www.google.com/selfdrivingcar>




<http://grand-challenge.org>




[www.image-net.org](http://www.image-net.org)

# Neural Network Architecture

- Performance is highly dependent on architecture
- Extensive number of design parameters
  - Hyperparameters



# Neural Network Architecture



- Time and expertise to design the best network architecture
- Can we learn good architectures automatically?


# Neural Architecture Search (NAS)

- Automate the design of neural networks through optimization algorithms
  - **Network topology:** nodes connections, operators, etc.
  - **Metrics:** Accuracy, model size, inference time, etc.
- Applications where NAS methods have outperformed manually designed architectures:
  - Image classification [Real 2019]
  - Object detection [Zoph 2018]
  - Semantic segmentation [Chen 2018]





Source: <https://www.automl.org/>

# Neural Architecture Search (NAS)




# NAS – Search Space

- Defines which architectures can be represented
- Incorporate prior knowledge about types of architectures suitable for the task
  - Reduces the size of search space
  - Can introduce human bias
- Examples:
  - Chain-structured
  - Cell-based




# Neural Architecture Search (NAS)



# NAS – Search Strategy

- Defines how to explore the search space
  - Exploration vs. exploitation
- Some strategies:
  - Random search
  - Reinforcement learning
  - Gradient-based methods
  - Evolutionary methods

# Neural Architecture Search (NAS)




# NAS – Performance Estimation Strategy

- Estimate the performance of the candidate architecture
  - Cannot train all the candidate architectures from scratch
- Some strategies:
  - Lower fidelity estimates
  - Network morphisms
  - Weight sharing
  - Surrogate models

# Neural Network Efficiency

- Current architectures can have tens of millions of parameters
  - Over-parametrized
  - Highly inefficient
  - Overfitting



# Multi-Objective NAS

- NAS is usually modeled as a single objective optimization problem
  - Maximize prediction accuracy
- **Multi-objective NAS** aims to identify architectures that optimize multiple objectives:
  - Maximize model's performance
  - Minimize model's size
  - Or other objectives

# **Efficient Multi-Objective NAS (EMONAS-Net) for Medical Image Segmentation**




UNIVERSITY OF  
SOUTH FLORIDA  
COLLEGE OF ENGINEERING

Baldeon-Calisto, M., and S. Lai-Yuen. "EMONAS-Net: Efficient Neural Architecture Search Framework using Surrogate-Assisted Evolutionary 15 Algorithm." *Artificial Intelligence in Medicine*, 119, 2021.

# Medical Image Segmentation


- Critical task for identifying structures in medical images
  - Studying anatomical structures
  - Identifying tumors and lesions
  - Assist in treatment planning before radiation therapy



Prostate segmentation


# Efficient Multi-Objective NAS (EMONAS-Net)

- Design an efficient multi-objective NAS framework for medical image segmentation
  - Automatically identifies accurate and small networks for a particular dataset
  - Improves search efficiency



# Efficient Multi-objective NAS (EMONAS-Net)



1. Novel search space
2. Surrogate-assisted Multi-objective Evolutionary based Algorithm (SaMEA)
  - ❑ Finds the best micro and macro hyperparameters




EMONAS-Net framework components

# Search Space

- Macro and micro search space to be optimized



# Micro Search Space



Cell represented as a directed acyclical graph.

# Decision Variables


- **1×1×1 3D convolution**
- **3×3×3 3D convolution**
- **5×5×5 3D convolution**
- **3×3×1 2D convolution**
- **5×5×1 2D convolution**
- **7×7×1 2D convolution**
- **3×3×3 Pseudo-3D convolution**
- **5×5×5 Pseudo-3D convolution**
- **7×7×7 Pseudo-3D convolution**
- **identity**

Table 1. Set of possible convolutional operations in a node.

Decision Variable	Formula	Search Range
Input to node 2 ( $I_2$ )	-	[Input tensor, node 1]
Input to node 3 ( $I_3$ )	-	[Input tensor, node 1, node 2]
Input to node 4 ( $I_4$ )	-	[Input tensor, node 1, node 2, node 3]
Type of Convolutional operation in node 1 ( $O_1$ )	-	Refer to Table 1.
Type of Convolutional operation in node 2 ( $O_2$ )	-	Refer to Table 1.
Type of Convolutional operation in node 3 ( $O_3$ )	-	Refer to Table 1.
Type of Convolutional operation in node 4 ( $O_4$ )	-	Refer to Table 1.
Number of cells ( $N_{cells}$ )	$2n_c + 1$	$n_c \in [2,3,4]$
Number of filters for $NF_1$	$2^{nf}$	$n_f \in [3,4,5]$
Learning rate	-	$[1 \times 10^{-5}, 9 \times 10^{-3}]$

Table 2. Decision variables constituting the hyperparameter search space and search range.

# Decision Variables




Hyperparameter Vector

Node 1	Input tensor	Node 2	3x3x3 P3D	3x3x3 3D	5x5x1 2D	1x1x1 3D	7	32	$3 \times 10^{-4}$
Input node 2	Input node 3	Input node 4	Conv. operation node 1	Conv. operation node 2	Conv. operation node 3	Conv. operation node 4	Number of cells	Number of filters	Learning rate

# Surrogate Assisted Multi-objective Evolutionary Algorithm (SaMEA)

- MOEA/D based algorithm with penalty-based boundary intersection (PBI) approach
  - Selection probabilities
  - Random forest surrogate



# SaMEA Algorithm

$$\left. \begin{array}{l} \text{Expected} \\ \text{Segmentation} \\ \text{Error} \end{array} \right\} \begin{aligned} \text{Minimize } f_1(x) &= \alpha(C - MCDice_{Train}(\theta)) + (C - MCDice_{Val}(\theta)) + \beta \left( \frac{E - e_{max}}{E} \right) \\ \text{Number of Trainable} \\ \text{Parameters} \end{aligned}$$
$$\left. \begin{array}{l} \\ \\ \end{array} \right\} \begin{aligned} \text{Minimize } f_2(x) &= \log(|\theta|) \\ \text{subject to } x &\in \Omega \end{aligned}$$

$\Omega$  = hyperparameter search space

$\theta$  = network parameters

MCDice( $\theta$ ) = multiclass Dice similarity coefficient

$\alpha, \beta$  = weight parameters

$E$  = maximum number of training epochs


$e_{max}$  = epoch with the maximum validation MCDice( $\theta$ )

# SaMEA Algorithm


- Three phases:
    1. Initialization phase
    2. Learning phase
    3. Exploitation phase
- 
- Exploring the search space
- Exploiting the search space  
(Implement selection probabilities,  
Random Forest surrogate)

# Initialization and Learning Phase

Phase I and II of the SaMEA Algorithm




# Exploitation Phase



Phase III of the SaMEA Algorithm

# Experiments


Dataset		
Cardiac	Hippocampus	Prostate
<ul style="list-style-type: none"><li>• ACDC Grand Challenge</li><li>• Left ventricle cavity</li><li>• Left ventricle myocardium</li><li>• Right ventricle cavity</li></ul>	<ul style="list-style-type: none"><li>• Medical Segmentation Decathlon</li><li>• Posterior part</li><li>• Anterior part</li></ul>	<ul style="list-style-type: none"><li>• PROMISE12 challenge</li><li>• Prostate</li></ul>



(Bernard, 2018)



(Simpson, 2019)



(Litjens, 2014)

**Prostate Dataset:** <https://promise12.grand-challenge.org/Home/>


**Cardiac Dataset:** <https://acdc.creatis.insa-lyon.fr/#challenge/>

**Hippocampus Dataset:** <https://decathlon-10.grand-challenge.org/>

# Best Hyperparameter Values for Datasets

Decision Variable	Prostate Dataset	Hippocampus Dataset	Cardiac Dataset
<b>Input to node 2 (<math>I_2</math>)</b>	Node 1	Input Tensor	Input Tensor
<b>Input to node 3 (<math>I_3</math>)</b>	Input Tensor	Node 1	Node 1
<b>Input to node 4 (<math>I_4</math>)</b>	Node 2	Node 1	Node 3
<b>Type of Convolutional operation in node 1 (<math>O_1</math>)</b>	3x3x3 P3D	3x3x3 3D Conv.	3x3x1 2D Conv.
<b>Type of Convolutional operation in node 2 (<math>O_2</math>)</b>	3x3x3 3D Conv.	3x3x3 P3D	3x3x3 P3D
<b>Type of Convolutional operation in node 3 (<math>O_3</math>)</b>	5x5x1 2D Conv.	3x3x3 P3D	1x1x1 3D Conv.
<b>Type of Convolutional operation in node 4 (<math>O_4</math>)</b>	1x1x1 3D Conv.	5x5x1 2D Conv.	7x7x1 2D Conv.
<b>Number of Cells (<math>N_{cells}</math>)</b>	7	7	7
<b>Number of filters for <math>NF_1</math></b>	32	32	32
<b>Learning Rate</b>	$3 \times 10^{-4}$	$4 \times 10^{-4}$	$4 \times 10^{-4}$
<b>Number of Parameters</b>	$5.9 \times 10^6$	$7.0 \times 10^6$	$7.1 \times 10^6$

# Best Architectures for Hippocampus and Cardiac Datasets



# Benchmark Results: Cardiac Dataset

Group	Method	Right Ventricle Cavity				Left Ventricle Cavity				Left Ventricle Myocardium				Size of the Network
		HD [mm]	Rank	DSC [%]	Rank	HD [mm]	Rank	DSC [%]	Rank	HD [mm]	Rank	DSC [%]	Rank	
EMONAS-1	Automatic	11.34	4	91.24	2	7.81	7	92.59	11	8.72	3	87.59	11	$7.1 \times 10^6$
EMONAS-5	Automatic	11.18	2	91.20	3	7.35	5	93.10	7	8.92	4	88.00	10	$35.5 \times 10^6$
Isensee et al.	Automatic	9.93	1	92.75	1	6.20	1	94.75	1	7.17	1	91.35	1	$235.5 \times 10^6$
Baldeon et al.	Automatic	11.21	3	90.99	5	7.12	2	93.03	9	8.26	2	88.40	9	$24.0 \times 10^6$
Zotti et al.	Manual	12.19	5	91.15	6	7.28	4	93.80	4	9.44	7	89.40	3	-
Zotti et al.	Manual	11.85	6	90.95	4	7.67	6	93.10	7	8.99	5	89.00	5	-
Painchaud et al.	Manual	13.52	8	90.85	7	7.22	3	93.60	6	9.12	6	88.90	7	-
Baumgartner et al.	Manual	13.68	9	90.75	8	785	8	93.70	5	9.67	8	89.65	2	-

**Table 3.** Evaluation metrics for the top competing methods in the ACDC challenge.

**DSC:** Dice Similarity Coefficient

**HD:** Hausdorff Distance

# Efficiency Evaluation: Cardiac Dataset


NAS Method	Right Ventricle Cavity		Left Ventricle Cavity		Left Ventricle Myocardium		Size of the Network	GPU days	GPU Specification
	HD [mm]	DSC [%]	HD [mm]	DSC [%]	HD [mm]	DSC [%]			
EMONAS-1	11.3	91.2	7.8	92.6	8.7	87.6	$7.1 \times 10^6$	11.4	1 GTX- 1070 Ti
Baldeon et al.	11.6	91.0	7.7	92.7	9.4	87.5	$7.0 \times 10^6$	23.8	1 GTX- 1070 Ti
Mortazi et al.	14.3	86.8	8.9	92.8	10.7	84.9	$30.0 \times 10^6$	10	15 GTX Titan X

**Table 4.** Efficiency and performance metrics for competing NAS methods in the ACDC challenge.

**DSC:** Dice Similarity Coefficient

**HD:** Hausdorff Distance

# Results: Cardiac Segmentation



# Benchmark Results: Hippocampus Dataset

Model	Method	DSC [%]		Size of the Network	GPU days	GPU Specification
		ANT	POS			
EMONAS-Net	Automatic	$89.08 \pm 0.39$	$87.54 \pm 0.34$	$7.0 \times 10^6$	4.22	1 GTX- 1070 Ti
Baldeon et al.	Automatic	$88.53 \pm 0.36$	$87.02 \pm 0.34$	$5.6 \times 10^6$	8.77	1 GTX- 1070 Ti
Yu et al.	Automatic	83.09	82.97	$17.0 \times 10^6$	5	<u>64</u> NVIDIA V100
Isensee et al.	Automatic	89.87	88.20	-	-	-
Wang et al.	Manual	87.93	88.69	-	NA	NA
Wang et al.	Manual	87.48	84.92	-	NA	NA
Wang et al.	Manual	85.75	88.29	-	NA	NA


**Table 5.** Evaluation metrics for competing methods in the Medical Decathlon Challenge dataset.

**DSC:** Dice Similarity Coefficient


**ANT:** Anterior Part of the Hippocampus

**POS:** Posterior Part of the Hippocampus

# Results: Hippocampus Segmentation



# Best Architecture for Prostate Dataset



Hyperparameter Vector

Node 1	Input tensor	Node 2	3x3x3 P3D	3x3x3 3D	5x5x1 2D	1x1x1 3D	7	32	$3 \times 10^{-4}$
Input node 2	Input node 3	Input node 4	Conv. operation node 1	Conv. operation node 2	Conv. operation node 3	Conv. operation node 4	Number of cells	Number of filters	Learning rate

# Benchmark Results: Prostate Dataset


Model	Method	DSC[%]			95 HD [mm]			Size of the Network	GPU days
		Whole	Apex	Base	Whole	Apex	Base		
EMONAS-Net	Automatic	91.01	88.16	89.50	4.40	3.69	4.37	$5.9 \times 10^6$	3.02
Baldeon et al.	Automatic	91.45	88.10	89.54	4.08	3.58	4.43	$27.5 \times 10^6$	7.68
Isensee et al. (I)	Automatic	91.61	91.61	90.29	4.00	3.79	4.05	$365.5 \times 10^6$	-
Isensee et al. (II)	Automatic	91.56	91.56	89.59	4.17	3.77	4.42	$365.5 \times 10^6$	-
Isensee et al. (III)	Automatic	91.93	88.82	91.93	3.95	3.69	4.21	$365.5 \times 10^6$	-

**Table 6.** Evaluation metrics for the top competing NAS methods in the Promise12 challenge.

**DSC:** Dice Similarity Coefficient

**95 HD:** 95% Hausdorff distance

# Results: Prostate Segmentation



# Summary

- Presented an efficient NAS framework for medical image segmentation
  - Novel search space for micro and macro structure of architecture
  - SaMEA algorithm to improve exploration of search space and convergence
  - Random forest surrogate to reduce search time
- Experiments demonstrate that the presented framework identifies accurate and small networks while improving search efficiency

# Some Additional Resources

- NAS Survey [Elsken 2019]
- Reinforcement Learning NAS [Jaafra 2019]
- Evolutionary Learning NAS [Liu 2021]
- Hardware-aware NAS [Benmeziane 2021]
- NAS for Transformers [Chitty-Venkata 2022]

# References

1. E. Real, A. Aggarwal, Y. Huang, and Q. V. Le, "Aging Evolution for Image Classifier Architecture Search," AAAI, 2019.
2. B. Zoph, V. Vasudevan, J. Shlens and L. Quoc V, "Learning transferable architectures for scalable image recognition.," in *IEEE Conference on Computer Vision and Pattern Recognition*, Salt Lake City, 2018
3. L.-C. Chen, M. Collins, Y. Zhu, et al., "Searching for Efficient Multi-scale Architectures for Dense Image Prediction," In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, 31, 2018.
4. T. Elsken, J. H. Metzen, and F. Hutter, "Neural architecture search: A survey," *J. Mach. Learn. Res.*, vol. 20, no. 1, pp. 1997–2017, 2019.
5. Y. Jaafra, J. L. Laurent, A. Deruyver, and M. S. Naceur, "Reinforcement learning for neural architecture search: A review," *Image Vis. Comput.*, vol. 89, pp. 57–66, Sep. 2019.
6. Y. Liu, Y. Sun, B. Xue, M. Zhang, G. G. Yen, and K.C.Tan, "A survey on evolutionary neural architecture search," *IEEE Trans. Neural Netw. Learn. Syst.*, early access, Aug. 6, 2021.
7. H. Benmeziane, K. El Maghraoui, H. Ouarnoughi, S. Niar, M. Wistuba, and N.Wang, "A comprehensive survey on hardware-aware neural architecture search," 2021.
8. K. T. Chitty-Venkata, M. Emani, V. Vishwanath, and A. K. Somani, "Neural Architecture Search for Transformers: A Survey," *IEEE Access*, 2022.

# Thank You!

# Questions?