# The potential for re-powering wind turbines: reducing turbines, increasing output

Peter Regner<sup>1</sup>, Katharina Gruber<sup>1</sup>, Johannes Schmidt<sup>1</sup>, Claude Klöckl<sup>1</sup>

 $^{1}$ Institute for Sustainable Economic Development, University of Natural Resources and Life Sciences, Vienna

2019-10-20, Vienna, INFORMS 2019








▶ Low carbon energy systems: land usage is a critical factor

- ► Low carbon energy systems: land usage is a critical factor
- repowering = replacing power plants with newer ones, which have a higher rated capacity or more efficiency

- Low carbon energy systems: land usage is a critical factor
- repowering = replacing power plants with newer ones, which have a higher rated capacity or more efficiency
- ► How much power generation gain can be expected in the US with newer wind turbine models?

- ► Low carbon energy systems: land usage is a critical factor
- repowering = replacing power plants with newer ones, which have a higher rated capacity or more efficiency
- ► How much power generation gain can be expected in the US with newer wind turbine models? How many wind turbines will be installed?



► ERA5: wind speed data, hourly (2001 - 2018), 0.25° spatial resolution

- ► **ERA5**: wind speed data, hourly (2001 2018), 0.25° spatial resolution
- ▶ United States Wind Turbine Database (USWTDB): 58,184 turbines including location, model name, rated capacity, rotor diameter, ...

- ► **ERA5**: wind speed data, hourly (2001 2018), 0.25° spatial resolution
- ▶ United States Wind Turbine Database (USWTDB): 58,184 turbines including location, model name, rated capacity, rotor diameter, ...
- ► Time series of **wind power net generation** provided by the U.S. Energy Information Administration (EIA) via the Electricity data browser: time series, monthly total power generation (2001 2018)


- ► ERA5: wind speed data, hourly (2001 2018), 0.25° spatial resolution
- ▶ United States Wind Turbine Database (USWTDB): 58,184 turbines including location, model name, rated capacity, rotor diameter. ...
- ► Time series of **wind power net generation** provided by the U.S. Energy Information Administration (EIA) via the Electricity data browser: time series, monthly total power generation (2001 2018)
- Data sheets for turbine models: rotor diameter, power curve

# Turbine models


| Model name        | Rated capacity | Rotor diameter |
|-------------------|----------------|----------------|
| GE-1.5 77         | 1.5 MW         | 77 m           |
| Senvion 3.4M114   | 3.4 MW         | 114 m          |
| Enercon E-138 EP3 | 3.5 MW         | 138 m          |
| Senvion 4.2M140   | 4.2 MW         | 140 m          |
| Enercon E-126     | 7.58MW         | 127 m          |

GE-1.5 77 is the most frequent model in the U.S. (14.7% of all turbines).

# Power curves



# Simulation of power generation



# Maximum power generation with different turbines

#### **Optimization problem:**

Existing turbines are replaced by newer ones at the location of the old turbines, such that:


- objective function: total power generation is maximized
- constraints: distance between turbines is not below a threshold


# Maximum power generation with different turbines


#### **Optimization problem**:


Existing turbines are replaced by newer ones at the location of the old turbines, such that:

- objective function: total power generation is maximized
- constraints: distance between turbines is not below a threshold, which depends on the direction relative to the prevailing wind direction at the location












# Minimum distances between turbine locations



# Repowering potential: power generation



# Repowering potential: number of turbines



#### Conclusions:

► repowering less than half of the existing turbines, roughly increases the power generation output by 50%

#### Conclusions:

- ► repowering less than half of the existing turbines, roughly increases the power generation output by 50%
- repowering leads to a significant drop of total number of turbines installed

#### Conclusions:

- ► repowering less than half of the existing turbines, roughly increases the power generation output by 50%
- repowering leads to a significant drop of total number of turbines installed
- minimum distances between wind turbines can be estimated by a linear model using the rotor diameter

#### Conclusions:

- ► repowering less than half of the existing turbines, roughly increases the power generation output by 50%
- repowering leads to a significant drop of total number of turbines installed
- minimum distances between wind turbines can be estimated by a linear model using the rotor diameter

# Thank you!

https://refuel.world/ peter.regner@boku.ac.at

http://bit.ly/wind-repower-us





