Play:	***1 - In field coaching***		
Purpose:	*Risk Communication*	***Objective:***	*Worker training/education*
Description:	During regular working processes, the device is used in the field to visually demonstrate to workers how hazard levels vary with location, work tasks, and work activities.		
Considerations:	Occupational hygiene professionals use the device to provide immediate visual evidence of variability in hazard levels across the workplace, helping workers and supervisors recognize how emission sources, work tasks, and worker activities influence exposure.		

Setup

Method overview:	This method involves the occupational hygiene professional conducting a walkthrough of the workplace with a handheld direct-reading instrument under normal working conditions. During the walkthrough, the professional engages workers in conversation to demonstrate the variability in hazard levels and how it may be influenced by emission sources, work tasks, and worker activities. The primary focus is on in-field coaching and risk communication.		
Typical deployment	Handheld by occupational hygiene professional	**Typical data interpretation**	Qualitatively
Typical measurement resolution	High resolution (seconds)	**Typical data availability**	Immediate on display
Potential additional information:	When recorded, the data can be analyzed after the shift either independently or alongside contextual information on emission sources, work tasks, and worker activities. An additional enhancement is the use of video recording to enrich this contextual information, which is described in a separate play.	**Worker engagement:**	Workers should be engaged throughout the play. Before monitoring begins, they should understand the purpose of the play so they perform their work as they normally would during the shift. During the shift, they should be actively involved in observing and discussing variability in hazard levels. After the shift, they should participate in conversations about the findings and their implications for improving work practices and reducing exposures.
Communication with:	Workers/supervisors	**Information shared**	The variability of hazard levels across the workplace.

Procedures

Measurement start:	Before use, the device should be inspected and its zero reading verified. An improper zero reading or false-positive response may lead to incorrect interpretation of the data and compromise the outcome of the play.
During measurement:	The occupational hygiene professional follows the worker(s) with the handheld device while observing and recording potential emission sources, work tasks, and worker activities. When appropriate and in accordance with safe work practices, the professional may engage the worker immediately to demonstrate elevated hazard levels and discuss the activities or conditions contributing to them.
After measurement:	After the sampling event or at the end of the shift, the occupational hygiene professional reviews the findings with the worker(s), emphasizing the variability in hazard levels observed throughout the workday. The contextual information collected during the monitoring is essential for interpreting the findings, understanding how sources, work tasks, and worker activities influenced exposure, and identifying opportunities for improvement.

Data interpretation and analysis

For this play, data analysis is intentionally kept to a minimum. The objective is to facilitate in-field coaching by using timely measurements to illustrate variability in hazard levels and stimulate discussion.