

# Introduction

## Numerical Methods for Deep Learning

# Learning From Data: The Core of Science - 1

Given inputs and outputs, how to choose  $f$ ?

**Option 1** (Fundamental(?) understanding): For example, Galileo's law of motion

$$x(t) = \frac{1}{2}gt^2,$$

with unknown parameter  $g$ .

# Learning From Data: The Core of Science - 1

Given inputs and outputs, how to choose  $f$ ?

**Option 1** (Fundamental(?) understanding): For example, Galileo's law of motion

$$x(t) = \frac{1}{2}gt^2,$$

with unknown parameter  $g$ .

To estimate  $g$  observe falling object

t	x
0	0
1	4.9
2	20.1
3	44.1

Goal: Derive model from theory, calibrate it using data.

# Learning From Data: The Core of Science - 2

Given inputs and outputs, how to choose  $f$ ?

**Option 2** (Phenomenological models): For example, Archie's law - what is the electrical resistivity of a rock and how it relates to its porosity,  $\phi$  and saturation,  $S_w$ ?

$$\rho(\phi, S_w) = a\phi^{n/2}S_w^p$$

$a, n, p$  unknown parameters

Obtaining parameters from observed data and lab experiments on rocks.

Goal: Find model that consistent with fundamental theory, without directly deriving it from theory.

# Phenomenological vs. Fundamental

**Fundamental laws** come from understanding(?) the underlying process. They are **assumed invariant** and can therefore be predictive(?).

**Phenomenological models** are data-driven. They “work” on some given data. Hard to know what their limitations are.

**But ...**

- ▶ models based on understanding can do poorly - weather, economics ...
- ▶ models based on data can sometimes do better
- ▶ how do we quantify understanding?

# Machine Learning in 3 slides - 1

*Machine learning (ML) is the scientific study of algorithms and statistical models that computer systems use to perform a specific task without using explicit instructions, relying on patterns and inference instead. (wiki)*

# Machine Learning in 3 slides - 1


*Machine learning (ML) is the scientific study of algorithms and statistical models that computer systems use to perform a specific task without using explicit instructions, relying on patterns and inference instead. (wiki)*

Two common tasks in machine learning:


- ▶ given data, cluster it and detect patterns in it (unsupervised learning)
- ▶ given data and labels, find a functional relation between them (supervised learning)

# Machine Learning in 3 slides - 2

unsupervised



semi-supervised



Unsupervised learning - given the data set  $\mathbf{Y} = [\mathbf{y}_1, \dots, \mathbf{y}_n]$  cluster the data into "similar" groups (labels).


- ▶ helps find hidden patterns
- ▶ often explorative and open-ended

Semisupervised - label the data based on a few examples




# Machine Learning in 3 slides - 3

training data



trained model



Supervised learning - given the data set  $\mathbf{Y} = [\mathbf{y}_1, \dots, \mathbf{y}_n] \in \mathcal{Y}$  and their labels  $\mathbf{C} = [\mathbf{c}_1, \dots, \mathbf{c}_n] \in \mathcal{C}$ , find the relation  $f : \mathcal{Y} \rightarrow \mathcal{C}$

- ▶ models range in complexity
- ▶ older models based on support vector machines (SVM) and kernel methods
- ▶ recently, deep neural networks (DNNs) dominate

# Deep Neural Networks: History

- ▶ Neural Networks with a particular (deep) architecture
- ▶ Exist for a long time (70's and even earlier) [11, 12, 9]
- ▶ Recent revolution - computational power and lots of data [1, 10, 8]
- ▶ Can perform very well when trained with lots of data
- ▶ Applications
  - ▶ Image recognition [5, 7, 8], segmentation, natural language processing [2, 3, 6]

# Deep Neural Networks: History

- ▶ Neural Networks with a particular (deep) architecture
- ▶ Exist for a long time (70's and even earlier) [11, 12, 9]
- ▶ Recent revolution - computational power and lots of data [1, 10, 8]
- ▶ Can perform very well when trained with lots of data
- ▶ Applications
  - ▶ Image recognition [5, 7, 8], segmentation, natural language processing [2, 3, 6]
- ▶ A few recent news articles:
  - ▶ Apple Is Bringing the AI Revolution to Your iPhone, WIRED 2016
  - ▶ Why Deep Learning Is Suddenly Changing Your Life, FORTUNE 2016
  - ▶ Data Scientist: Sexiest Job of the 21st Century, Harvard Business Rev '17

# Learning Objective: Demystify Deep Learning

Artificial Intelligence / Machine Learning

---

## The Dark Secret at the Heart of AI

No one really knows how the most advanced algorithms do what they do. That could be a problem.

by **Will Knight**

Apr 11, 2017

---

Learning objectives of this minicourse:

- ▶ look under the hood of some deep learning examples
- ▶ describe deep learning mathematically (see also [4])
- ▶ expose numerical challenges / approaches to improve DL

# DNN - A Quick Overview - 1

Neural networks are data interpolator/classifier when the underlying model is unknown.

A generic way to write it is


$$\mathbf{c} = f(\mathbf{y}, \boldsymbol{\theta}).$$

- ▶ the function  $f$  is the computational model
- ▶  $\mathbf{y} \in \mathbb{R}^{n_f}$  is the input data (e.g., an image)
- ▶  $\mathbf{c} \in \mathbb{R}^{n_c}$  is the output (e.g. class of the image)
- ▶  $\boldsymbol{\theta} \in \mathbb{R}^{n_p}$  are parameters of the model  $f$


In supervised learning we have examples

$\{(\mathbf{y}_j, \mathbf{c}_j) : j = 1, \dots, n\}$  and the goal is to estimate or “learn” the parameters  $\boldsymbol{\theta}$ .

# DNN - A Quick Overview - 2



# DNN - A Quick Overview - 2



$$\left\{ \begin{array}{lcl} \mathbf{y}_{l+1} & = & \sigma(\mathbf{K}_l \mathbf{y}_l + \mathbf{b}_l) \\ \mathbf{y}_{l+1} & = & \mathbf{y}_l + \sigma(\mathbf{K}_l \mathbf{y}_l + \mathbf{b}_l) \\ \mathbf{y}_{l+1} & = & \mathbf{y}_l + \sigma(\mathbf{L}_l \sigma(\mathbf{K}_l \mathbf{y}_l + \mathbf{b}_l)) \\ & \vdots & \end{array} \right.$$

Here:

- ▶  $l = 0, 1, 2, \dots, N$  is the layer
- ▶  $\sigma : \mathbb{R} \rightarrow \mathbb{R}$  is the activation function
- ▶  $\mathbf{y}_0 = \mathbf{y} \in \mathbb{R}^{n_f}$  is the input data (e.g., an image)
- ▶  $\mathbf{c} \in \mathbb{R}^{n_c}$  is the output (e.g. class of the image)
- ▶  $\mathbf{L}_l, \mathbf{K}_l, \mathbf{b}_l$  are parameters of the model  $f$

# Machine Learning in 3 slides

*Machine learning (ML) is the scientific study of algorithms and statistical models that computer systems use to perform a specific task without using explicit instructions, relying on patterns and inference instead. (wiki)*



# Machine Learning in 3 slides


*Machine learning (ML) is the scientific study of algorithms and statistical models that computer systems use to perform a specific task without using explicit instructions, relying on patterns and inference instead. (wiki)*

Two common tasks in machine learning:


- ▶ given data, cluster it and detect patterns in it (unsupervised learning)
- ▶ given data and labels, find a functional relation between them (supervised learning)

# Machine Learning in 3 slides

unsupervised



semi-supervised




Unsupervised learning - given the data set  $\mathbf{Y} = [\mathbf{y}_1, \dots, \mathbf{y}_n]$  cluster the data into "similar" groups (labels).

- ▶ helps find hidden patterns
- ▶ often explorative and open-ended


Semisupervised - label the data based on a few examples

# Machine Learning in 3 slides

training data



trained model



Supervised learning - given the data set  $\mathbf{Y} = [\mathbf{y}_1, \dots, \mathbf{y}_n] \in \mathcal{Y}$  and their labels  $\mathbf{C} = [\mathbf{c}_1, \dots, \mathbf{c}_n] \in \mathcal{C}$ , find the relation  $f : \mathcal{Y} \rightarrow \mathcal{C}$

- ▶ models range in complexity
- ▶ older models based on support vector machines (SVM) and kernel methods
- ▶ recently, deep neural networks (DNNs) dominate

# Generalization - 1

Suppose that we have examples  $\{\mathbf{y}_j, \mathbf{c}_j\}$ ,  $j = 1, \dots, n$ , a model  $f(\mathbf{y}, \boldsymbol{\theta})$  and some optimal parameter  $\boldsymbol{\theta}^*$ .

Let  $\{(\mathbf{y}_j^t, \mathbf{c}_j^t) : j = 1, \dots, s\}$  be some test set, that was not used to compute  $\boldsymbol{\theta}^*$ .

# Generalization - 1

Suppose that we have examples  $\{\mathbf{y}_j, \mathbf{c}_j\}$ ,  $j = 1, \dots, n$ , a model  $f(\mathbf{y}, \boldsymbol{\theta})$  and some optimal parameter  $\boldsymbol{\theta}^*$ .

Let  $\{(\mathbf{y}_j^t, \mathbf{c}_j^t) : j = 1, \dots, s\}$  be some test set, that was not used to compute  $\boldsymbol{\theta}^*$ .

Loosely speaking, if

$$\|f(\mathbf{y}_j^t, \boldsymbol{\theta}^*) - \mathbf{c}_j^t\|_p \text{ is small}$$

then the model is predictive - it generalizes well

# Generalization - 1

Suppose that we have examples  $\{\mathbf{y}_j, \mathbf{c}_j\}$ ,  $j = 1, \dots, n$ , a model  $f(\mathbf{y}, \boldsymbol{\theta})$  and some optimal parameter  $\boldsymbol{\theta}^*$ .

Let  $\{(\mathbf{y}_j^t, \mathbf{c}_j^t) : j = 1, \dots, s\}$  be some test set, that was not used to compute  $\boldsymbol{\theta}^*$ .

Loosely speaking, if

$$\|f(\mathbf{y}_j^t, \boldsymbol{\theta}^*) - \mathbf{c}_j^t\|_p \text{ is small}$$

then the model is predictive - it generalizes well


For phenomenological models, there is no reason why the model should generalize, but in practice it often does.

## Generalization - 2

Why would a model generalize poorly?

$$1 \ll \|f(\mathbf{y}_j^t, \boldsymbol{\theta}^*) - \mathbf{c}_j^t\|_p$$

## Generalization - 2



Why would a model generalize poorly?



$$1 \ll \|f(\mathbf{y}_j^t, \boldsymbol{\theta}^*) - \mathbf{c}_j^t\|_p$$

Two common reasons:

1. Our “optimal”  $\boldsymbol{\theta}^*$  was optimal for the training but is less so for other data



## Generalization - 2



Why would a model generalize poorly?

$$1 \ll \|f(\mathbf{y}_j^t, \boldsymbol{\theta}^*) - \mathbf{c}_j^t\|_p$$

Two common reasons:

1. Our “optimal”  $\boldsymbol{\theta}^*$  was optimal for the training but is less so for other data
2. The chosen computational model  $f$  is poor (e.g. quadratic model for a nonlinear function).

# Example: Classification of Hand-written Digits

- ▶ Let  $\mathbf{y}_j \in \mathbb{R}^{n_f}$  and let  $\mathbf{c}_j \in \mathbb{R}^{n_c}$ .
- ▶ The vector  $\mathbf{c}$  is the probability of  $\mathbf{y}$  belonging to a certain class. Clearly,  $0 \leq \mathbf{c}_j \leq 1$  and  $\sum_{j=1}^{n_c} \mathbf{c}_j = 1$ .

Examples (MNIST):

$\mathbf{y}_1$



$\mathbf{y}_2$



$$\mathbf{c}_1 = [0, 0, 0, 0, 1, 0, 0, 0, 0, 0]^T \quad \mathbf{c}_2 = [0, 0.3, 0, 0, 0, 0, 0, 0, 0.7, 0]^T$$

# Example: Classification of Natural Images

Image classification of natural images

Examples (CIFAR-10):



# Example: Semantic Segmentation - 1

- ▶ let  $\mathbf{y}_j \in \mathbb{R}^n$  be an RGB or grey valued image.
- ▶ let the pixels in  $\mathbf{c}_j \in \{1, 2, 3, \dots\}^k$  denote the labels.

$\mathbf{y}$ , input image



$\mathbf{c}$ , segmentation (labeled image)



Goal: Find map  $\mathbf{c} = f(\mathbf{y}, \theta)$

## Example: Semantic Segmentation - 2

Problem: Given image  $\mathbf{y}$  and label  $\mathbf{c}$ , find a map  $f(\cdot, \boldsymbol{\theta})$  such that  $\mathbf{c} \approx f(\mathbf{y}, \boldsymbol{\theta})$

## Example: Semantic Segmentation - 2

Problem: Given image  $\mathbf{y}$  and label  $\mathbf{c}$ , find a map  $f(\cdot, \boldsymbol{\theta})$  such that  $\mathbf{c} \approx f(\mathbf{y}, \boldsymbol{\theta})$

First step: Reduce the dimensionality of problem.

- ▶ extract features from the image
- ▶ classify in the feature space

Reduce the problem of learning from the image to feature detection and classification

## Example: Semantic Segmentation - 2

Problem: Given image  $\mathbf{y}$  and label  $\mathbf{c}$ , find a map  $f(\cdot, \boldsymbol{\theta})$  such that  $\mathbf{c} \approx f(\mathbf{y}, \boldsymbol{\theta})$

First step: Reduce the dimensionality of problem.

- ▶ extract features from the image
- ▶ classify in the feature space

Reduce the problem of learning from the image to feature detection and classification

Possible features: Color, neighbors, edges ...

## Example: Semantic Segmentation - 3

Problem: Given image  $\mathbf{y}$  and label  $\mathbf{c}$  find a map  $f(\cdot, \boldsymbol{\theta})$  such that  $\mathbf{c} \approx f(\mathbf{y}, \boldsymbol{\theta})$



## Example: Semantic Segmentation - 3

Problem: Given image  $\mathbf{y}$  and label  $\mathbf{c}$  find a map  $f(\cdot, \boldsymbol{\theta})$  such that  $\mathbf{c} \approx f(\mathbf{y}, \boldsymbol{\theta})$

First step: Reduce the dimensionality of problem.

- ▶ extract features from the image
- ▶ classify in the feature space

Reduce the problem of learning from the image to feature detection and classification

## Example: Semantic Segmentation - 3

Problem: Given image  $\mathbf{y}$  and label  $\mathbf{c}$  find a map  $f(\cdot, \boldsymbol{\theta})$  such that  $\mathbf{c} \approx f(\mathbf{y}, \boldsymbol{\theta})$

First step: Reduce the dimensionality of problem.

- ▶ extract features from the image
- ▶ classify in the feature space

Reduce the problem of learning from the image to feature detection and classification

Possible features: Color, neighbors, edges ...


# Example: Semantic Segmentation - 3

## Simpler setup

- ▶ input:  $\mathbf{y}$  is the RGB value of the pixel (and its neighbors?)
- ▶ output:  $\mathbf{c}$  is a labeled pixel
- ▶ goal: map  $\mathbf{c} = f(\mathbf{y}, \boldsymbol{\theta})$



input image and segmentation



3D representation of RGB values

# References

- [1] Y. Bengio et al. Learning deep architectures for AI. *Foundations and trends® in Machine Learning*, 2(1):1–127, 2009.
- [2] A. Bordes, S. Chopra, and J. Weston. Question Answering with Subgraph Embeddings. *arXiv preprint arXiv:1406.3676*, 2014.
- [3] R. Collobert, J. Weston, L. Bottou, M. Karlen, K. Kavukcuoglu, and P. Kuksa. Natural Language Processing (Almost) from Scratch. *Journal of Machine Learning Research*, 12:2493–2537, 2011.
- [4] C. F. Higham and D. J. Higham. Deep Learning: An Introduction for Applied Mathematicians. *arXiv.org*, Jan. 2018.
- [5] G. Hinton, L. Deng, D. Yu, G. E. Dahl, A.-r. Mohamed, N. Jaitly, A. Senior, V. Vanhoucke, P. Nguyen, T. N. Sainath, et al. Deep neural networks for acoustic modeling in speech recognition: The shared views of four research groups. *IEEE Signal Processing Magazine*, 29(6):82–97, 2012.
- [6] S. Jean, K. Cho, R. Memisevic, and Y. Bengio. On Using Very Large Target Vocabulary for Neural Machine Translation. *arXiv preprint arXiv:1412.2007*, 2014.
- [7] A. Krizhevsky, I. Sutskever, and G. Hinton. Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 61:1097–1105, 2012.
- [8] Y. LeCun, Y. Bengio, and G. Hinton. Deep learning. *Nature*, 521(7553):436–444, 2015.

# References (cont.)

- [9] Y. LeCun, B. E. Boser, and J. S. Denker. Handwritten digit recognition with a back-propagation network. In *Advances in neural information processing systems*, pages 396–404, 1990.
- [10] R. Raina, A. Madhavan, and A. Y. Ng. Large-scale deep unsupervised learning using graphics processors. In *the 26th Annual International Conference*, pages 873–880. ACM, June 2009.
- [11] F. Rosenblatt. The perceptron: A probabilistic model for information storage and organization in the brain. *Psychological review*, 65(6):386–408, 1958.
- [12] D. Rumelhart, G. Hinton, and J. Williams, R. Learning representations by back-propagating errors. *Nature*, 323(6088):533–538, 1986.