



# Theorembeweiserpraktikum

## Even More Tactics

Jakob von Raumer, Sebastian Ullrich | SS 2021



THEOREM PROVER

## focus vs. •

A correction: `focus` does not actually force the first goal to be closed

```
example (hp : p) (hq : q) : p ∧ q := by
  constructor
  focus -- `! p`
    skip
  focus
    -- still `! p`
  exact hq -- type mismatch
```

We introduced `•` (input as `\centerdot`) as a (prettier) way to do just that:

```
constructor
• skip -- unsolved goals: ... ! p
• exact hq -- is still checked
```

This is basically an unnamed case

While `focus` is not strictly structuring given this insight, we'll allow both this semester

# What's Up with Those Dots Anyway

We've seen `·` before: in *terms*, it can be used as a nameless lambda

```
set_option pp.binder_types false
#check (· :: ·) -- fun a a_1 => a :: a_1 : ...
#check (1 + 2 * ·) -- fun a => 1 + 2 * a : Nat → Nat
#check [0, 1].map (·.succ) -- List.map (fun a => Nat.succ a) [0, 1] : List Nat
```

All occurrences of `·` are bound to the nearest surrounding parentheses, from left to right

# refine

We already know we can arbitrarily nest terms and tactics:

```
example (hr : r) (hrp : r → p) (hq : q) : p ∧ q := by
  exact ⟨(by simp_all), hq⟩
```

We can use `refine` to move out nested tactic blocks

```
refine ⟨?p, hq⟩
case p => -- h p
  simp_all
```

`apply e` where `e : (h : p) → ... → q` can be thought of as a special case of `refine` : `refine e ?h ...`

# Fun with Recursors

We've learned that pattern matching (and induction and recursion) is expressed internally via *recursors*:

```
recursor Option.rec.{u_1, u} : {α : Type u} → {motive : Option α → Sort u_1} →  
  motive none →  
  ((val : α) → motive (some val)) →  
  (t : Option α) → motive t
```

# Fun with Recursors

We can also write our own recursor and use them in `cases` / `induction` !

```

theorem Option.rec_rec (p : Option (Option α) → Prop)
  (hsome_some : ∀ x, p (some (some x)))
  (hsome_none : p (some none))
  (hnone : p none) : ∀ o, p o
| some (some x) => hsome_some x
| some none => hsome_none
| none => hnone

example (p : Option (Option α) → Prop) : p o := by
cases o using Option.rec_rec with
| hsome_some x => done -- case hsome_some: ⊢ p (some (some x))
| _ => done -- case hsome_none: ..., case hnone: ...

-- also works without `with`
cases o using Option.rec_rec <|> simp_all

```