PRODUCT SPECIFICATION

Antimony trioxide, grade 99.50

High-purity antimony trioxide produced at the Chatkal Chemical Smelting Complex by re-volatilising refined antimony metal under controlled conditions. Used mainly as a flame-retardant synergist in plastics and textiles, and in glass, including glass for solar panels.



The Chatkal Chemical Smelting Complex, Urmaral gorge.

Typical specification

PARAMETER	VALUE
Sb_2O_3, % not less than	99.50
As_2O_3, % not more than	0.060
PbO, % not more than	0.100
Fe_2O_3, % not more than	0.005
Whiteness, % not less than	95
Mean particle size, µm	0.8 to 1.5

Form and packing

ITEM	DETAILS
Form	Fine white powder
Packing	Paper bags of 25 kg on pallets, or bulk bags of 1 t
Shipment	By rail from the Chatkal siding, or by truck, north through Kazakhstan
Documents	Certificate of analysis from the Chatkal laboratory with each lot

Storage and handling

Store dry in closed packaging. Avoid raising dust; use dust masks and gloves when handling. A safety data sheet is supplied with the first delivery under each contract.

This specification is provided for information. It is not an offer to sell, and products are supplied only under contract with the Combine. The Combine does not sell through agents or intermediaries, and does not request advance payments or changes of bank details by e-mail.

Iradi Antimony and Rare Metals Combine, Sales Department, 14 Metallurgy Avenue, Talas. Tel. +996-39-6-21-40-20