

# **Requirements for the SCF Module STL2STLXML**

# Contents

<b>Disclaimer.....</b>	<b>4</b>
<b>Structure of the requirements.....</b>	<b>5</b>
<b>Requirements for Sub-module STL2STLXML.....</b>	<b>6</b>
requirement-164: Code Page 850 - GSI Header (20h - 7Fh).....	6
requirement-165: Character Code table 00 - TTI blocks - Code Range 20h-7Eh.....	6
requirement-166: Character Code table 00 - TTI blocks (A0h - FFh).....	6
requirement-171: Decoding Code Page dependent.....	7
requirement-172: Code Page Number mapping.....	7
requirement-173: Disk Format Code mapping.....	7
requirement-174: Display Standard Code mapping.....	8
requirement-175: Character Code Table Number mapping.....	8
requirement-176: Language Code mapping.....	8
requirement-177: Original Programme Title (OPT), Bytes 16 to 47, OPT.....	9
requirement-178: Original Episode Title mapping.....	9
requirement-179: Translated Programme Title mapping.....	9
requirement-180: Translated Episode Title mapping.....	10
requirement-181: Translator's Name mapping.....	10
requirement-182: Translator's Contact Details mapping.....	10
requirement-183: Subtitle List Reference Code mapping.....	11
requirement-184: Creation Date mapping.....	11
requirement-185: Revision Date mapping.....	11
requirement-186: Revision Number mapping.....	12
requirement-187: Total Number of Text and Timing Information blocks mapping.....	12
requirement-188: Total Number of Subtitles mapping.....	12
requirement-189: Total Number of Subtitle Groups mapping.....	13
requirement-190: Maximum Number of Displayable Characters in any text row mapping.....	13
requirement-191: Maximum Number of Displayable Rows mapping.....	13
requirement-192: Time Code: Status mapping.....	14
requirement-193: Time Code: Start-of-Programme mapping.....	14
requirement-194: Time Code: First In-Cue mapping.....	14
requirement-195: Total Number of Disks mapping.....	15
requirement-196: Disk Sequence Number mapping.....	15
requirement-197: Country of Origin mapping.....	15
requirement-198: Publisher mapping.....	16
requirement-199: Editor's Name mapping.....	16
requirement-200: Editor's Contact Details mapping.....	16
requirement-201: User-Defined Area mapping.....	17
requirement-206: Subtitle Group Number mapping.....	17
requirement-207: Subtitle Number mapping.....	17
requirement-208: Extension Block Number mapping.....	18
requirement-209: Cumulative Status mapping.....	18
requirement-210: Time Code In mapping.....	18
requirement-211: Time Code Out mapping.....	19
requirement-212: Vertical Position mapping.....	19
requirement-213: Justification Code mapping.....	20

requirement-214: Comment Flag mapping.....	20
requirement-215: Text Field mapping.....	20
requirement-217: Space mapping.....	21
requirement-218: Text Field mapping - Text.....	21
requirement-219: AlphaBlack Control mode mapping.....	21
requirement-220: Alpha Red Control Code mapping.....	22
requirement-221: Alpha Green Control Code mapping.....	22
requirement-222: Alpha Yellow Control Code mapping.....	22
requirement-223: Alpha Blue Control Code mapping.....	23
requirement-224: Alpha Magenta Control Code mapping.....	23
requirement-225: Alpha Cyan Control Code mapping.....	23
requirement-226: Alpha White Control Code mapping.....	24
requirement-227: Flash Control Code mapping.....	24
requirement-228: Steady Control Code mapping.....	24
requirement-229: End Box Control Code mapping.....	25
requirement-230: Start Box Control Code mapping.....	25
requirement-231: Normal Height Control Code mapping.....	25
requirement-232: Double Height Control Code mapping.....	26
requirement-233: Double Width Control Code mapping.....	26
requirement-234: Double Size Control Code mapping.....	26
requirement-246: Black Background Control Code mapping.....	27
requirement-247: New Background Control Code mapping.....	27
requirement-250: CR/LF Control Code mapping.....	27
requirement-460: Parameter for setting the TTI block merging behaviour.....	28

# Disclaimer

---

Copyright 2017 Institut für Rundfunktechnik GmbH, Munich, Germany

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License.

You may obtain a copy of the License at <http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, the subject work distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

See the License for the specific language governing permissions and limitations under the License.

# Structure of the requirements

---

The structure of the requirements is as follows:

- **Title:** a short title, prepended with the internal ID of the requirement
- **Description:** the requirement text. The specified text will be used to test the implementation.
- **Area:** Apart from more general requirements the requirements are categorized by modules (e.g. STLXML2EBU-TT or EBU-TT2EBU-TT-D)
- **Requirement Review Status:** This is the internal review status of the requirement itself (especially of the requirement text).
- **Status Implementation:** This status indicates if the requirement is already met by the implementation. The possible status codes are:
  - *outstanding* - the corresponding code has not yet been written, or the requirement has been implemented but there are no test files for it
  - *waitingReview* - the code to implement the requirement has been written but nobody (except the developer) has reviewed the code yet
  - *underReview* - the corresponding code is under review and has not yet been accepted by the first reviewer
  - *reviewed* - the corresponding code has been reviewed and accepted by the first reviewer
  - *accepted* - the corresponding code has been accepted by the developer team and is ready to be published
- **Priority according to MoSCoW:** the priority that is the base to decide when the feature will be implemented. The possible values are:
  - *M* - must
  - *S* - should
  - *C* - could
  - *W* - won't

For more information see: [https://en.wikipedia.org/wiki/MoSCoW\\_method](https://en.wikipedia.org/wiki/MoSCoW_method)

## Requirements for Sub-module STL2STLXML

---

### requirement-164: Code Page 850 - GSI Header (20h - 7Fh)

---

**Description**

The STL to STLXML module supports the Code Page 850 for the GSI Header block. Only the chars 0x20 to 0xFF (except 0x7F) are considered, as the other chars are usually treated as control chars.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

### requirement-165: Character Code table 00 - TTI blocks - Code Range 20h-7Eh

---

**Description**

The STL to STLXML module supports the character code table 00 (ISO 6937/2) for the TTI Blocks in the code range 20h - 7Eh.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

### requirement-166: Character Code table 00 - TTI blocks (A0h - FFh)

---

**Description**

The STL to STLXML module supports the character code table 00 (ISO 6937/2) for the TTI Blocks in the code range A0h - FFh.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

**requirement-171: Decoding Code Page dependent**

---

**Description**

The values of the GSI element's children are decoded depending on the used Code Page that's given in the CPN-field of the GSI Header as described in EBU Tech 3264 Table 1 (p.4).

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

**requirement-172: Code Page Number mapping**

---

**Description**

The Code Page Number (CPN) field in the STL file (Bytes 0 to 2) is mapped to the CPN element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

**requirement-173: Disk Format Code mapping**

---

**Description**

The Disk Format Code (DFC) field in the STL file (Bytes 3 to 10) is mapped to the DFC element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

**requirement-174: Display Standard Code mapping**

---

**Description**

The Display Standard Code (DSC) field in the STL file (Byte 11) is mapped to the DSC element. The Display Standard Code "Blank" for the value "Undefined" is translated as a space (20h).

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

**requirement-175: Character Code Table Number mapping**

---

**Description**

The Character Code Table Number (CCT) field in the STL file (Bytes 12 to 13) is mapped to the CCT element. If the character code in the STL is not defined by Tech 3264 the conversion is stopped.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

**requirement-176: Language Code mapping**

---

**Description**

The Language Code (LC) field in the STL file (Bytes 14 to 15) is mapped to the LC element.

**Area**



STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

## requirement-177: Original Programme Title (OPT), Bytes 16 to 47, OPT

---

**Description**

The Original Programme Title (OPT) field in the STL file (Bytes 16 to 47) is mapped to OPT element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

## requirement-178: Original Episode Title mapping

---

**Description**

The Original Episode Title (OET) field in the STL file (Bytes 48 to 79) is mapped to the OET element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

## requirement-179: Translated Programme Title mapping

---

**Description**

The Translated Programme Title (TPT) field in the STL file (Bytes 80 to 111) is mapped to the TPT element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

**requirement-180: Translated Episode Title mapping**

---

**Description**

The Translated Episode Title (TET) field in the STL file (Bytes 112 to 143) is mapped to the TET element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

**requirement-181: Translator's Name mapping**

---

**Description**

The Translator's Name (TN) field in the STL file (Bytes 144 to 175) is mapped to the TN element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

**requirement-182: Translator's Contact Details mapping**

---

**Description**

The Translator's Contact Details (TCD) field in the STL file (Bytes 176 to 207) is mapped to the TCD element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

#### **Status Implementation**

accepted

#### **Priority according to MoSCoW**

s

## **requirement-183: Subtitle List Reference Code mapping**

---

#### **Description**

The Subtitle List Reference Code (SLR) field in the STL file (Bytes 208 to 223) is mapped to the SLR element.

#### **Area**

STL2STLXML

#### **Requirement Review Status**

accepted

#### **Status Implementation**

accepted

#### **Priority according to MoSCoW**

m

## **requirement-184: Creation Date mapping**

---

#### **Description**

The Creation Date (CD) field in the STL file (Bytes 224 to 229) is mapped to the CD element.

#### **Area**

STL2STLXML

#### **Requirement Review Status**

accepted

#### **Status Implementation**

accepted

#### **Priority according to MoSCoW**

s

## **requirement-185: Revision Date mapping**

---

#### **Description**

The Revision Date (RD) field in the STL file (Bytes 230 to 235) is mapped to the RD element.

#### **Area**

STL2STLXML

#### **Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

**requirement-186: Revision Number mapping**

---

**Description**

The Revision Number (RN) field in the STL file (Bytes 236 to 237) is mapped to the element RN.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

**requirement-187: Total Number of Text and Timing Information blocks mapping**

---

**Description**

The Total Number of Text and Timing Information (TNB) field in the STL file (Bytes 238 to 242) is mapped to the TNB element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

**requirement-188: Total Number of Subtitles mapping**

---

**Description**

The Total Number of Subtitles (TNS) field in the STL file (Bytes 243 to 247) is mapped to the TNS element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

## requirement-189: Total Number of Subtitle Groups mapping

---

**Description**

The Total Number of Subtitle Groups (TNG) field in the STL file (Bytes 248 to 250) is mapped to TNG element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

## requirement-190: Maximum Number of Displayable Characters in any text row mapping

---

**Description**

The Maximum Number of Displayable Characters in any text row (MNC) field in the STL file (Bytes 251 to 252) is mapped to the MNC element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

## requirement-191: Maximum Number of Displayable Rows mapping

---

**Description**

The Maximum Number of Displayable Rows (MNR) field in the STL file (Bytes 253 to 254) is mapped to the MNR element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

## requirement-192: Time Code: Status mapping

---

**Description**

The Time Code: Status (TCS) field in the STL file (Byte 255) is mapped to the TCS element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

## requirement-193: Time Code: Start-of-Programme mapping

---

**Description**

The Time Code: Start-of-Programme (TCP) field in the STL file (Bytes 256 to 263) is mapped to the TCP element. The format of the element TCP is HHMMSSFF (hours, minutes, seconds, frames).

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

## requirement-194: Time Code: First In-Cue mapping

---

**Description**

The Time Code: First In-Cue (TCF) in the STL file (Bytes 264 to 271) is mapped to the TCF element. The format of the element TCF is HHMMSSFF (hours, minutes, seconds, frames)

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

**requirement-195: Total Number of Disks mapping**

---

**Description**

The Total Number of Disks (TND) field in the STL file (Byte 272) is mapped to the TND element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

**requirement-196: Disk Sequence Number mapping**

---

**Description**

The Disk Sequence Number (DSN) field in the STL file (Byte 273) is mapped to the DSN element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

**requirement-197: Country of Origin mapping**

---

**Description**

The Country of Origin (CO) field in the STL file (Bytes 274 to 276) is mapped to the CO element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

## requirement-198: Publisher mapping

---

**Description**

The Publisher (PUB) field in the STL file (Bytes 277 to 308) is mapped to the PUB element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

## requirement-199: Editor's Name mapping

---

**Description**

The Editor's Name (EN) field in the STL file (Bytes 309 to 340) is mapped to the EN element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

## requirement-200: Editor's Contact Details mapping

---

**Description**

The Editor's Contact Details (ECD) field in the STL file (Bytes 341 to 372) is mapped to the ECD element.

**Area**

STL2STLXML



**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

**requirement-201: User-Defined Area mapping**

---

**Description**

The User-Defined Area (UDA) field in the STL file (Bytes 448 to 1023) is mapped to the UDA element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

c

**requirement-206: Subtitle Group Number mapping**

---

**Description**

The Subtitle Group Number (SGN) field in the STL file (Byte 0) is mapped to the SGN element. The value is encoded as decimal.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

**requirement-207: Subtitle Number mapping**

---

**Description**

The Subtitle Number (SN) field in the STL file (Bytes 1 to 2) is mapped to the SN element. The value is encoded as decimal. The TTI

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

**requirement-208: Extension Block Number mapping**

---

**Description**

The Extension Block Number (EBN) field in the STL file (Byte 3) is mapped to the EBN element. The TF field of a TTI Blocks that has a EBN number in the Range 00-EF is concatenated with following one until a TTI Block has an EBN with the value FF (except an optional parameter disables the concatenation). TTI Blocks with the value FE (User Data) are output with the Text Field (TF) content converted to Base64. TTI Blocks with an EBN in the range F0-FD (Reserved Codes) are ignored.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

**requirement-209: Cumulative Status mapping**

---

**Description**

The Cumulative Status (CS) field in the STL file (Byte 4) is mapped to the CS element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s

**requirement-210: Time Code In mapping**

---

**Description**

The Time Code In (TCI) field in the STL file (Bytes 5 to 8) is mapped to the TCI element. The hex values are encoded as decimal.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

## requirement-211: Time Code Out mapping

---

**Description**

The Time Code Out (TCO) field in the STL file (Bytes 9 to 12) is mapped to the TCO element. Hex values are encoded as decimals.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

## requirement-212: Vertical Position mapping

---

**Description**

The Vertical Position (VP) field in the STL file (Byte 13) is mapped to the VP element.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

## requirement-213: Justification Code mapping

---

### Description

The Justification Code (JC) field in the STL file (Byte 14) is mapped to the JC element.

### Area

STL2STLXML

### Requirement Review Status

accepted

### Status Implementation

accepted

### Priority according to MoSCoW

m

## requirement-214: Comment Flag mapping

---

### Description

The Comment Flag (CF) field in the STL file (Byte 15) is mapped to the CF element.

### Area

STL2STLXML

### Requirement Review Status

accepted

### Status Implementation

accepted

### Priority according to MoSCoW

s

## requirement-215: Text Field mapping

---

### Description

The Text Field (TF) field in the STL file (Bytes 16 to 127) is mapped to the TF element. If the respective TTI block contains User Data (EBN value 0xFE), the content is converted to Base64.

### Area

STL2STLXML

### Requirement Review Status

accepted

### Status Implementation

accepted

### Priority according to MoSCoW

m

## requirement-217: Space mapping

---

### Description

A Space (20h) within a TTI block's Text field (TF) is mapped to the element space. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

### Area

STL2STLXML

### Requirement Review Status

accepted

### Status Implementation

accepted

### Priority according to MoSCoW

m

## requirement-218: Text Field mapping - Text

---

### Description

Text within a TTI block's Text field (TF) is decoded according to the Character Code Table (CCT) in EBU Tech 3264 stored in the Bytes 12 to 13 of the GSI Header. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

### Area

STL2STLXML

### Requirement Review Status

accepted

### Status Implementation

accepted

### Priority according to MoSCoW

m

## requirement-219: AlphaBlack Control mode mapping

---

### Description

A Alpha Black Control code (00h) within a TTI block's Text field (TF) is mapped to the element AlphaBlack. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

### Area

STL2STLXML

### Requirement Review Status

accepted

### Status Implementation

accepted

### Priority according to MoSCoW

m

## requirement-220: Alpha Red Control Code mapping

---

### Description

An Alpha Red Control codes (01h) within a TTI block's Text field (TF) is mapped to the element AlphaRed. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

### Area

STL2STLXML

### Requirement Review Status

accepted

### Status Implementation

accepted

### Priority according to MoSCoW

m

## requirement-221: Alpha Green Control Code mapping

---

### Description

An Alpha Green Control code (02h) within a TTI block's Text field (TF) is mapped to the element AlphaGreen. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

### Area

STL2STLXML

### Requirement Review Status

accepted

### Status Implementation

accepted

### Priority according to MoSCoW

m

## requirement-222: Alpha Yellow Control Code mapping

---

### Description

An Alpha Yellow Control code (03h) within a TTI block's Text field (TF) is mapped to the element AlphaYellow. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

### Area

STL2STLXML

### Requirement Review Status

accepted

### Status Implementation

accepted

**Priority according to MoSCoW**

m

**requirement-223: Alpha Blue Control Code mapping**

---

**Description**

An Alpha Blue Control code (04h) within a TTI block's Text field (TF) is mapped to the element AlphaBlue. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

**requirement-224: Alpha Magenta Control Code mapping**

---

**Description**

An Alpha Magenta Control codes (05h) within a TTI block's Text field (TF) is mapped to the element AlphaMagenta. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

**requirement-225: Alpha Cyan Control Code mapping**

---

**Description**

An Alpha Cyan Control code (06h) within a TTI block's Text field (TF) is mapped to the element AlphaCyan. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

## requirement-226: Alpha White Control Code mapping

---

### Description

An Alpha White Control code (07h) within a TTI block's Text field (TF) is mapped to the elements AlphaWhite. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

### Area

STL2STLXML

### Requirement Review Status

accepted

### Status Implementation

accepted

**Priority according to MoSCoW**

m

## requirement-227: Flash Control Code mapping

---

### Description

A Flash Control codes (08h) within a TTI block's Text field (TF) is mapped to the element Flash. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

### Area

STL2STLXML

### Requirement Review Status

accepted

### Status Implementation

accepted

**Priority according to MoSCoW**

s

## requirement-228: Steady Control Code mapping

---

### Description

Steady Control codes (09h) within a TTI block's Text field (TF) is mapped to the element Steady. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

### Area

STL2STLXML

### Requirement Review Status

accepted



**Status Implementation**

accepted

**Priority according to MoSCoW**

s

**requirement-229: End Box Control Code mapping**

---

**Description**

An End Box Control code (0Ah) within a TTI block's Text field (TF) is mapped to the element EndBox. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

**requirement-230: Start Box Control Code mapping**

---

**Description**

A Start Box Control codes (0Bh) within a TTI block's Text field (TF) is mapped to the elements StartBox. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

**requirement-231: Normal Height Control Code mapping**

---

**Description**

A Normal Height Control code (0Ch) within a TTI block's Text field (TF) is mapped to the element NormalHeight. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

**Area**

STL2STLXML

**Requirement Review Status**

accepted

#### **Status Implementation**

accepted

#### **Priority according to MoSCoW**

m

## **requirement-232: Double Height Control Code mapping**

---

#### **Description**

A Double Height Control code (0Dh) within a TTI block's Text field (TF) is mapped to the DoubleHeight element. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

#### **Area**

STL2STLXML

#### **Requirement Review Status**

accepted

#### **Status Implementation**

accepted

#### **Priority according to MoSCoW**

m

## **requirement-233: Double Width Control Code mapping**

---

#### **Description**

A Double Width Control code (0Eh) within a TTI block's Text field (TF) is mapped to the element DoubleWidth. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

#### **Area**

STL2STLXML

#### **Requirement Review Status**

accepted

#### **Status Implementation**

accepted

#### **Priority according to MoSCoW**

c

## **requirement-234: Double Size Control Code mapping**

---

#### **Description**

A Double Size Control code (0Fh) within a TTI block's Text field (TF) is mapped to a DoubleSize element. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

#### **Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

c

**requirement-246: Black Background Control Code mapping**

---

**Description**

A Black Background Control code (1Ch) within a TTI block's Text field (TF) is mapped to a BlackBackground elements. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

**requirement-247: New Background Control Code mapping**

---

**Description**

A New Background Control codes (1Dh) within a TTI block's Text field (TF) is mapped to a NewBackground element. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

**requirement-250: CR/LF Control Code mapping**

---

**Description**

A CR/LF Control codes (8Ah) within a TTI block's Text field (TF) is mapped to the element newline. Does not apply to TTI Blocks with User Data (EBN value 0xFE).

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

m

**requirement-460: Parameter for setting the TTI block merging behaviour**

---

**Description**

A parameter (-s) exists, that allows for disabling the TTI block merging of subtitles that are split into several TTI blocks. Merging these TTI blocks is the default behaviour. When the parameter "-s" is set, TTI blocks are not merged.

**Area**

STL2STLXML

**Requirement Review Status**

accepted

**Status Implementation**

accepted

**Priority according to MoSCoW**

s