

Requirements for the SCF Module
EBU-TT-D2EBU-TT-D-Basic-DE

Contents

Disclaimer.....	3
Structure of the requirements.....	4
Requirements for Sub-module EBU-TT-D2EBU-TT-D-Basic-DE.....	5
requirement-375: ttp:timebase attribute mapping.....	5
requirement-376: ttp:cellResolution attribute mapping.....	5
requirement-377: xml:lang attribute mapping.....	5
requirement-378: XML comment.....	6
requirement-381: ebuttm:documentEbuttVersion element mapping.....	6
requirement-383: tt:styling element mapping.....	6
requirement-385: tt:style element - tts:textAlign.....	7
requirement-386: tt:style element - tts:color.....	7
requirement-387: tt:region element mapping.....	8
requirement-388: tt:div element mapping.....	8
requirement-390: tt:p element mapping - content.....	8
requirement-391: tt:p element - style.....	9
requirement-392: tt:p element mapping - region.....	9
requirement-393: tt:p element mapping - begin and end attributes.....	9
requirement-394: tt:span element mapping - content.....	10
requirement-395: tt:span element mapping - style.....	10
requirement-396: tt:span element mapping - background color.....	11

Disclaimer

Copyright 2016 Institut für Rundfunktechnik GmbH, Munich, Germany

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License.

You may obtain a copy of the License at <http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, the subject work distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

See the License for the specific language governing permissions and limitations under the License.

Structure of the requirements

The structure of the requirements are as follows:

- **title:** a short title with the internal id of the requirement in brackets
- **description:** the requirement text - the specified text will be taken to test the implementation
- **area:** apart from more general requirements the requirements are categorized by modules (e.g. STLXML2EBUTT oder EBUTT2EBUTTD)
- **requirement review status:** this is the internal review status of the requirement itself (esp. of the requirement text)
- **status implementation:** this status indicates if the requirement is already met by the implementation the status codes are:
 - *outstanding* - the corresponding code has not been written yet or the requirement has been implemented but there are no test files for it
 - *waitingReview* - the code to implement the requirement has been written but with exception of the developer nobody has reviewed the code yet
 - *underReview* - the corresponding code is underReview and has not been accepted by the first reviewer yet
 - *reviewed* - the corresponding code has been reviewed and accepted by the first reviewer
 - *Priority* according to MoSCoW (the priority that is the base to decide when the feature will be implemented: m - MUST, S-Should, C-could, W-Won't. For more information see http://en.wikipedia.org/wiki/MoSCoW_method))

Requirements for Sub-module EBU-TT-D2EBU-TT-D-Basic-DE

requirement-375: ttp:timebase attribute mapping

Description

The ttp:timebase attribute of the EBU-TT-D-Basic-DE file's tt:tt root element is set to "media" according to XML-Format für die Distribution von Untertiteln in den ARD Mediatheken (EBU-TT-D-Basic-DE) v1.2 (p.2).

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

accepted

Priority according to MoSCoW

s

requirement-376: ttp:cellResolution attribute mapping

Description

The ttp:cellResolution attribute of the EBU-TT-D-Basic-DE file's tt:tt root element is set to "50 30" according to XML-Format für die Distribution von Untertiteln in den ARD Mediatheken (EBU-TT-D-Basic-DE) v1.2 (p.2).

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

accepted

Priority according to MoSCoW

s

requirement-377: xml:lang attribute mapping

Description

The xml:lang attribute of the EBU-TT-D-Basic-DE file's tt:tt root element is taken from the EBU-TT-D file's tt:tt root element's xml:lang attribute according to XML-Format für die Distribution von Untertiteln in den ARD Mediatheken (EBU-TT-D-Basic-DE) v1.2 (p.2).

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

accepted

Priority according to MoSCoW

s

requirement-378: XML comment

Description

An XML comment set prior to the tt:tt root element hints to the used profile in the EBU-TT-D-Basic-DE file according to XML-Format für die Distribution von Untertiteln in den ARD Mediatheken (EBU-TT-D-Basic-DE) v1.2 (p.2).

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

accepted

Priority according to MoSCoW

s

requirement-381: ebuttm:documentEbuttVersion element mapping

Description

The EBU-TT-D-Basic-DE file's ebuttm:documentEbuttVersion element has its value set to "v1.0" according to EBU Tech 3350 3.1.1.1 (p.19).

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

accepted

Priority according to MoSCoW

s

requirement-383: tt:styling element mapping

Description

The EBU-TT-D-Basic-DE file's tt:styling element in the tt:head element has a tt:style element with its xml:id attribute set to "defaultStyle" according to XML-Format für die Distribution von Untertiteln in den ARD Mediatheken

(EBU-TT-D-Basic-DE) v1.2 (p.3). Its other attributes are set as follows: `tts:fontFamily="Verdana, Arial, Tiresias"`, `tts:fontSize="160%"`, `tts:lineHeight="125%"`.

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

accepted

Priority according to MoSCoW

m

requirement-385: `tt:style` element - `tts:textAlign`

Description

There are exactly three style elements in the EBU-TT-D-Basic-DE file that have a `tts:textAlign` attribute set. Exactly one `tt:style` element has the value "center" set, exactly one has the value "left" set and exactly one has the value "right" set according to XML-Format für die Distribution von Untertiteln in den ARD Mediatheken (EBU-TT-D-Basic-DE) v1.2 (p.9). These styles are only referenced by `tt:p` elements.

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

accepted

Priority according to MoSCoW

m

requirement-386: `tt:style` element - `tts:color`

Description

There are only eight allowed style elements in the EBU-TT-D-Basic-DE file that have their `tts:color` attributes set. The supported values are #000000 hex, #ffffff hex, #ff0000 hex, #00ff00 hex, #0000ff hex, #ffff00 hex, #ff00ff hex, #00ffff hex. Each of these eight elements has a different value set so each of the values is set exactly once. Each of these elements has its `tts:backgroundColor` attribute set to the value "#000000c2"

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

accepted

Priority according to MoSCoW

s

requirement-387: tt:region element mapping

Description

The EBU-TT-D file's tt:region elements are not mapped to the EBU-TT-D-Basic-DE file. The EBU-TT-D-Basic-DE file has two tt:region elements. For both of them the tts:origin attribute is set to "10% 10%". For both of them the tts:extent attribute is set to "80% 80%". For one of them the tts:displayAlign attribute is set to "after", for the other one it's set to "before" according to XML-Format für die Distribution von Untertiteln in den ARD Mediatheken (EBU-TT-D-Basic-DE) v1.2 (p.8).

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

accepted

Priority according to MoSCoW

s

requirement-388: tt:div element mapping

Description

The EBU-TT-D-Basic-DE file created from the EBU-TT-D file has exactly one tt:div element. This element's style attribute is set to "defaultStyle".

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

accepted

Priority according to MoSCoW

s

requirement-390: tt:p element mapping - content

Description

The EBU-TT-D file's tt:p elements' textual content is copied to the EBU-TT-D-Basic-DE file's tt:p elements. Every textual content is enclosed in a tt:span element. The tt:span elements are not nested.

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

accepted

Priority according to MoSCoW

s

requirement-391: tt:p element - style

Description

In the EBU-TT-D-Basic-DE file every tt:p element's style attribute is referencing a style whose tts:textAlign attribute is set according to the subtitle block's intended horizontal alignment according to XML-Format für die Distribution von Untertiteln in den ARD Mediatheken (EBU-TT-D-Basic-DE) v1.2 (p.9). If there's no horizontal alignment given for this particular subtitle block in the EBU-TT-D file, a style whose tts:textAlign attribute is set to "center" is referenced.

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

accepted

Priority according to MoSCoW

m

requirement-392: tt:p element mapping - region

Description

In the EBU-TT-D-Basic-DE file every tt:p element's region attribute is referencing one of the two defined regions depending on its position relative to the height of the video within the EBU-TT-D file. If the upper corner of the tt:p element lies in the upper half of the root container in the EBU-TT-D file, the region attribute of the tt:p element in the EBU-TT-D-Basic-DE file is referencing the region whose tts:displayAlign attribute is set to "before", otherwise it references to region whose tts:displayAlign attribute is set to "after" according to XML-Format für die Distribution von Untertiteln in den ARD Mediatheken (EBU-TT-D-Basic-DE) v1.2 (p.10).

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

outstanding

Priority according to MoSCoW

s

requirement-393: tt:p element mapping - begin and end attributes

Description

In the EBU-TT-D-Basic-DE file a tt:p element's begin and end attributes' values are taken from the respective tt:p element's begin and end attributes in the EBU-TT-D file according to XML-Format für die Distribution von Untertiteln in den ARD Mediatheken (EBU-TT-D-Basic-DE) v1.2 (p.9). The Milliseconds part is truncated to 3 digits.

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

accepted

Priority according to MoSCoW

s

requirement-394: tt:span element mapping - content

Description

In the EBU-TT-D-Basic-DE file every form of textual content is enclosed by a tt:span element according to XML-Format für die Distribution von Untertiteln in den ARD Mediatheken (EBU-TT-D-Basic-DE) v1.2 (p.9).

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

accepted

Priority according to MoSCoW

s

requirement-395: tt:span element mapping - style

Description

In the EBU-TT-D-Basic-DE file every tt:span element's style attribute is referencing a style with the appropriate text color according to XML-Format für die Distribution von Untertiteln in den ARD Mediatheken (EBU-TT-D-Basic-DE) v1.2 (p.11). The referenced style has its tts:color attribute set to a value that's properly representing the textcolor of the respective tt:span element in the EBU-TT-D file. For example if a tt:span element in the EBU-TT-D file references a style element that results in a reddish colouring of the contained text, the corresponding tt:span element in the EBU-TT-D-Basic-DE file references a style element that has its tts:color attribute set to "#ff0000" and its tts:backgroundColor attribute to "#000000c2" (the only allowed value for the tts:backgroundColor attribute of a style in EBU-TT-D-Basic-DE).

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

accepted

Priority according to MoSCoW

s

requirement-396: tt:span element mapping - background color

Description

In the transformation of an EBU-TT-D file to an EBU-TT-D-Basic-DE file tt:span elements changing the background color are not mapped to the EBU-TT-D-Basic-DE file since other than the default background colour no colours are supported according to XML-Format für die Distribution von Untertiteln in den ARD Mediatheken (EBU-TT-D-Basic-DE) v1.2 (p.11).

Area

EBU-TT-D2EBU-TT-D-Basic-DE

Requirement Review Status

accepted

Status Implementation

accepted

Priority according to MoSCoW

s