

# The $G$ -Wishart Weighted Proposal Algorithm: Efficient Posterior Computation for Gaussian Graphical Models

**Willem van den Boom**

Yong Loo Lin School of Medicine, National University of Singapore

2022 World Meeting of the  
International Society for Bayesian Analysis

June 29, 2022

# Coauthors



Alexandros Beskos  
UCL, ATI



Maria De Iorio  
NUS, A\*STAR, UCL




# Motivation

- Inference in graphical models is hard:  $2^{p(p-1)/2}$  possible graphs on  $p$  nodes
- Variety of approaches
  - Estimating the precision through penalized likelihood: Graphical lasso (Friedman et al., 2007), nodewise regression (Zhou et al., 2011), precision factor model (Chandra et al., 2022)
  - Continuous spike-and-slab prior (Wang, 2015; Li et al., 2020)
  - Subset of graph space: Decomposable graphs (Giudici and Green, 1999)
  - Full graph space with the  $G$ -Wishart prior (Giudici, 1996), e.g., BDgraph (Mohammadi and Wit, 2019) and the double conditional Bayes factor sampler (Hinne et al., 2014)
- The  $G$ -Wishart weighted proposal algorithm (WWA): Speed up through advances in MCMC
  - Informed proposal (Zanella, 2019)
  - Delayed Metropolis-Hastings acceptance (Christen and Fox, 2005)

# Gaussian graphical models

- $Y_i \mid K, G \sim \mathcal{N}(0, K^{-1})$  independently for  $i = 1, \dots, n$ 
  - $Y_i \in \mathbb{R}^p$
- Graph  $G$  specifies conditional independencies.
  - $G = \{(1,2), (2,3)\}$
  - $Y_{i1} \perp Y_{i3} \mid Y_{i2}$  if and only if  $K_{13} = 0$
  - $(i,j) \notin G \Rightarrow K_{ij} = 0$



$$Y_i \in \mathbb{R}^3$$
$$Y_{i1} \perp Y_{i3} \mid Y_{i2}$$

# Prior specification

- Hierarchical prior  $p(K, G) = p(K \mid G) p(G)$
- $G$ -Wishart distribution as prior on the precision matrix (Giudici, 1996)
  - Wishart distribution truncated to matrices with  $K_{ij} = 0$  for  $(i, j) \notin G$
  - $$p(K \mid G) = \mathcal{W}_G(K \mid \delta, D) = \frac{1}{I_G(\delta, D)} |K|^{\delta/2-1} \exp \left\{ -\frac{1}{2} \text{tr}(K^\top D) \right\}$$
- $K \mid G, Y \sim \mathcal{W}_G(\delta^\star, D^\star)$  where  $\delta^\star = \delta + n$  and  $D^\star = D + Y^\top Y$

# Goal

- The objective is inference on the graph  $G$ .

$$p(G \mid Y) \propto p(G) \int p(K \mid G) p(Y \mid K) dK = \frac{p(G) I_G(\delta^\star, D^\star)}{(2\pi)^{np/2} I_G(\delta, D)}$$

- The normalizing constant  $I_G(\delta, D)$  is intractable.
- Posterior computation is challenging and of interest.
  - Roverato, 2002; Dellaportas et al., 2003; Atay-Kayis and Massam, 2005; Moghaddam et al., 2009; Lenkoski and Dobra, 2011; Wang and Li, 2012; Cheng and Lenkoski, 2012; Lenkoski, 2013; Hinne et al., 2014; Mohammadi and Wit, 2015, 2019; Mohammadi et al., 2021

# WWA's speedups

**Problem:** Expensive to resample the full precision matrix  $K$

**Solution:** Gibbs update based on the Cholesky decomposition

**Problem:** Exploring the large discrete space of graphs


**Solution:** Informed proposal (Zanella, 2019) using a posterior approximation (Mohammadi et al., 2021) resulting in more efficient exploration

**Problem:** Most computational effort on proposed graphs that are rejected

**Solution:** Reject fast and cheaply using delayed Metropolis-Hastings acceptance (Christen and Fox, 2005)

# Review: Exchange algorithm

- The exchange algorithm (Murray et al, 2006) avoids evaluating  $I_G(\delta, D)$  (Wang and Li, 2012).



- Augmented state space  $(K, G, \tilde{K}^0, \tilde{G})$ :
  - Propose  $\tilde{G}$  from  $G$  by changing one edge.
  - “Prior” precision  $\tilde{K}^0 \mid \tilde{G} \sim \mathcal{W}_{\tilde{G}}(\delta, D)$

- Metropolis-Hastings acceptance ratio:


$$\frac{p(\tilde{K}, \tilde{G}, K^0, G)}{p(K, G, \tilde{K}^0, \tilde{G})} = \frac{p(\tilde{K} \mid \tilde{G}) p(\tilde{G}) p(Y \mid \tilde{K}) p(K^0 \mid G) q(G \mid \tilde{G})}{p(K \mid G) p(G) p(Y \mid K) p(\tilde{K}^0 \mid \tilde{G}) q(\tilde{G} \mid G)}$$

Exchange



# Review: Exchange algorithm

- The exchange algorithm (Murray et al, 2006) avoids evaluating  $I_G(\delta, D)$  (Wang and Li, 2012).



- Augmented state space  $(K, G, \tilde{K}^0, \tilde{G})$ :
  - Propose  $\tilde{G}$  from  $G$  by changing one edge.
  - “Prior” precision  $\tilde{K}^0 \mid \tilde{G} \sim \mathcal{W}_{\tilde{G}}(\delta, D)$

- Metropolis-Hastings acceptance ratio:

$$\frac{p(\tilde{K}, \tilde{G}, K^0, G)}{p(K, G, \tilde{K}^0, \tilde{G})} = \frac{\boxed{p(\tilde{K} \mid \tilde{G})} p(\tilde{G}) p(Y \mid \tilde{K}) \boxed{p(K^0 \mid G)} q(G \mid \tilde{G})}{\boxed{p(K \mid G)} p(G) p(Y \mid K) \boxed{p(\tilde{K}^0 \mid \tilde{G})} q(\tilde{G} \mid G)}$$

Exchange

$I_G(\delta, D)$  and  $I_{\tilde{G}}(\delta, D)$  cancel out.

**Problem:** Expensive to resample the full precision matrix  $K$

**Solution:** Gibbs update based on the Cholesky decomposition

- Augmenting the state space by sampling  $K \mid G \sim \mathcal{W}_G(\delta^\star, D^\star)$  is the main computational bottleneck.
- If  $\tilde{G}$  is accepted, update  $K$  such that it is distributed as  $\mathcal{W}_{\tilde{G}}(\delta^\star, D^\star)$ .
- Sampling one element of a Cholesky decomposition suffices.
  - Distribution of the Cholesky decomposition of a permuted  $K$  differs in only one element for  $G$  and  $\tilde{G}$ .
  - WWA samples this element from its Gaussian full conditional.

**Problem:** Exploring the large discrete space of graphs

**Solution:** Informed proposal

- Informed proposal puts more mass on regions with higher posterior probability (Zanella, 2019):

$$Q(\tilde{G} \mid G) \propto g \left\{ \frac{p(\tilde{G} \mid Y)}{p(G \mid Y)} \right\} q(\tilde{G} \mid G)$$

- ▶ Embarrassingly parallel scan over all  $\tilde{G}$  that differ from  $G$  by one edge.
- ▶ WWA uses balancing function  $g(t) = t/(1 + t)$ .
- WWA uses a modified version because  $p(G \mid Y)$  is intractable:
$$Q(\tilde{G} \mid K, G) \propto g \left\{ \frac{p(K, \tilde{G} \mid Y)}{p(K, G \mid Y)} \right\} q(\tilde{G} \mid G)$$
  - ▶ The ratio involves a ratio of intractable normalization constants  $I_G(\delta, D)$ .
  - ▶ Fast approximation of this ratio (Mohammadi et al., 2021)

**Problem:** Most computational effort on proposed graphs that are rejected

**Solution:** Reject fast and cheaply

- Delayed Metropolis-Hasting acceptance exploits a fast approximate acceptance probability (Christen and Fox, 2005).
- Approximation of ratio of  $I_G(\delta, D)$  (Mohammadi et al., 2021) provides approximate acceptance without:
  - Exchange algorithm
  - The computational bottleneck of sampling  $\tilde{K}^0 \mid \tilde{G} \sim \mathcal{W}_{\tilde{G}}(\delta, D)$
- The exchange algorithm only if  $\tilde{G}$  is “promoted” to be considered for delayed acceptance



# Overview of WWA


- MCMC step with  $p(K, G \mid Y)$  as stationary distribution:
  - Propose  $\tilde{G}$  from the informed proposal  $Q(\tilde{G} \mid K, G)$ .
  - Obtain  $\tilde{K} \sim \mathcal{W}_{\tilde{G}}(\delta^*, D^*)$  by a Gibbs update and compute  $Q(G \mid \tilde{K}, \tilde{G})$ .
  - “Promote”  $\tilde{G}$  using an approximate acceptance probability.
  - If promoted, sample  $\tilde{K}^0 \mid \tilde{G} \sim \mathcal{W}_{\tilde{G}}(\delta, D)$  and set  $(K, G) = (\tilde{K}, \tilde{G})$  with probability deriving from the exchange algorithm and delayed acceptance.
- Computation of  $Q(\tilde{G} \mid K, G)$  is embarrassingly parallel.
- The computational bottleneck  $\mathcal{W}_{\tilde{G}}(\delta, D)$  only occurs if  $\tilde{G}$  is promoted.

# Empirical results


- Quantify MCMC efficiency:
  - Computational cost of a single MCMC iteration
  - MCMC mixing, e.g., effective sample size

$$\text{cost of an independent sample} = \frac{\text{number of MCMC steps}}{\text{effective sample size}} \times \text{cost per step}$$

# Data simulated from cycle graphs




# Data simulated from cycle graphs





# Data simulated from uniformly sampled graphs



# Conceptual comparison of MCMC

<i>Feature</i>	(Exact) exchange algorithm	Gibbs update for $K$	Embarrassingly parallel
<i>Benefit</i>	Stationary distribution equals the posterior	Reduced computational cost	Exploit available compute power
Wang and Li (2012)	✗	✗	✗
Cheng and Lenkoski (2012)	✗	✓	✗
Hinne et al. (2014)	✓	✗	✗
Mohammadi and Wit (2015)	✓	✗	✓
WWA	✓	✓	✓

# Conclusion

- WWA provides a major speedup in MCMC with the  $G$ -Wishart prior.
  - Avoid resampling of the precision matrix via a Gibbs update
  - Informed proposal (Zanella, 2019) on the graph space
  - Reject fast and cheaply via delayed acceptance (Christen and Fox, 2005)
- Single edge update limits performance.
- WWA enables inference on the whole graph space in more scenarios:
  - Sparse seemingly unrelated regression (work in progress)
  - Learning of graph substructures (van den Boom et al., 2022)

# Related article

van den Boom, W., Beskos, A., and De Iorio, M. (2022). The G-Wishart weighted proposal algorithm: Efficient posterior computation for Gaussian graphical models. *Journal of Computational and Graphical Statistics*, advance online publication.





# References

- Atay-Kayis, A., and Massam, H. (2005), A Monte Carlo Method for Computing the Marginal Likelihood in Nondecomposable Gaussian Graphical Models, *Biometrika*, 92:317–335.
- Bhadra, A., and Mallick, B. K. (2013), Joint High-dimensional Bayesian Variable and Covariance Selection with an Application to eQTL Analysis, *Biometrics*, 69:47–457.
- Chandra, N. K., Müller, P., and Sarkar, A. (2022), Bayesian Scalable Precision Factor Analysis for Massive Sparse Gaussian Graphical Models. [arXiv:2107.11316v3](https://arxiv.org/abs/2107.11316v3)
- Cheng, Y., and Lenkoski, A. (2012), Hierarchical Gaussian Graphical Models: Beyond Reversible Jump, *Electronic Journal of Statistics*, 6:2309–2331.
- Christen, J. A., and Fox, C. (2005), Markov Chain Monte Carlo Using an Approximation, *Journal of Computational and Graphical Statistics*, 14:795–810.
- Dellaportas, P., Giudici, P., and Roberts, G. (2003), Bayesian Inference for Nondecomposable Graphical Gaussian Models, *Sankhyā: The Indian Journal of Statistics*, 65:43–55.
- Friedman, J., Hastie, T., and Tibshirani, R. (2007), Sparse Inverse Covariance Estimation with the Graphical Lasso, *Biostatistics*, 9:432–441.
- Giudici, P. (1996), Learning in Graphical Gaussian Models, in *Bayesian Statistics 5*, pp. 621–628.
- Giudici, P., and Green, P. J. (1999), Decomposable Graphical Gaussian Model Determination, *Biometrika*, 86:785–801.
- Hinne, M., Lenkoski, A., Heskes, T., and van Gerven, M. (2014), Efficient Sampling of Gaussian Graphical Models Using Conditional Bayes Factors, *Stat*, 3:326–336.
- Lenkoski, A. (2013), A Direct Sampler for G-Wishart Variates, *Stat*, 2:119–128.
- Lenkoski, A., and Dobra, A. (2011), Computational Aspects Related to Inference in Gaussian Graphical Models with the G-Wishart Prior, *Journal of Computational and Graphical Statistics*, 20:140–157.

# References

- Li, Z. R., McCormick, T. H., and Clark, S. J. (2020), Using Bayesian Latent Gaussian Graphical Models to Infer Symptom Associations in Verbal Autopsies, *Bayesian Analysis*, 15:781–807.
- Moghaddam, B., Khan, E., Murphy, K. P., and Marlin, B. M. (2009), “Accelerating Bayesian Structural Inference for Non-decomposable Gaussian Graphical Models,” in *Advances in Neural Information Processing Systems* (Vol. 22).
- Mohammadi, R., Massam, H., and Letac, G. (2021), Accelerating Bayesian Structure Learning in Sparse Gaussian Graphical Models, *Journal of the American Statistical Association*, advance online publication.
- Mohammadi, A., and Wit, E. C. (2015), Bayesian Structure Learning in Sparse Gaussian Graphical Models, *Bayesian Analysis*, 10:109–138.
- Mohammadi, R., and Wit, E. C. (2019). BDgraph: An R package for Bayesian Structure Learning in Graphical Models. *Journal of Statistical Software*, 89(3).
- Murray, I., Ghahramani, Z., and MacKay, D. J. C. (2006), MCMC for Doubly-intractable Distributions, in *Proceedings of the Twenty-Second Conference on Uncertainty in Artificial Intelligence*, pp. 359–366.
- Roverato, A. (2002). Hyper inverse Wishart distribution for non-decomposable graphs and its application to Bayesian inference for Gaussian graphical models. *Scandinavian Journal of Statistics*, 29:391–411.
- van den Boom, W., De Iorio, M., and Beskos, A. (2022). Bayesian Learning of Graph Substructures. *arXiv:2203.11664*
- Wang, H. (2015), Scaling it Up: Stochastic Search Structure Learning in Graphical Models, *Bayesian Analysis*, 10:351–377.
- Wang, H., and Li, S. Z. (2012), Efficient Gaussian Graphical Model Determination Under G-Wishart Prior Distributions, *Electronic Journal of Statistics*, 6:168–198.
- Zanella, G. (2019), Informed Proposals for Local MCMC in Discrete Spaces, *Journal of the American Statistical Association*, 115:852–865.
- Zhou, S., Rütimann, P., Xu, M., and Bühlmann, P. (2011), High-dimensional Covariance Estimation Based on Gaussian Graphical Models, *The Journal of Machine Learning Research*, 12:2975–3026.



# NUS

National University  
of Singapore

Yong Loo Lin  
School of Medicine

## We are hiring!

Division of Biomedical Data Science  
led by Prof. Maria De Iorio

Postdoc positions, PhD studentships

**Thank you!**



