

```

## Load libraries
library(splines)
library(MASS)
library(FDRreg)

## Loading required package: fda
## Loading required package: Matrix
##
## Attaching package: 'fda'
## The following object is masked from 'package:graphics':
##
##      matplot
## Loading required package: BayesLogit
## Loading required package: mtnorm

library(curl)

library(doParallel) ##to make cluster (on Windows)

## Warning: package 'doParallel' was built under R version 3.3.2
## Loading required package: foreach
## Loading required package: iterators
## Loading required package: parallel

library(foreach) ##to use foreach function that does the parallel processing
library(doRNG) ##for reproducible seeds when doing parallel processing

## Loading required package: rngtools
## Loading required package: pkgmaker
## Loading required package: registry
##
## Attaching package: 'pkgmaker'
## The following object is masked from 'package:base':
##
##      isNamespaceLoaded

```

1 Probability of being a false positive as a linear function of time

Load simulations and (re)define some variables:

```

load("simResults_1.RData")

nSims <- length(pValuesSims)
ntest <- length(pValuesSims[[1]])

```

```
## Set up the time vector and the probability of being null
tme <- seq(-1,2,length=ntest)
pi0 <- 1/4*tme+1/2
```

Perform estimation and save estimates:

```
cl<-makeCluster(8) ##specify number of cores less than or equal to number of cores on your computer
registerDoParallel(cl)

set.seed(31084)

pi0hatScottMat <- foreach(sim=1:nSims, .combine="rbind", .packages="FDRreg", .errorhandling="ignore") {
  ##first transform the p-values into z-scores
  ##randomly assign positive or negative sign
  zScores <- qnorm(1-pValuesSims[[sim]]/2)##*sample(c(-1,1), replace=TRUE, size=length(pValuesSims[[sim]])
  fdr <- FDRreg(zScores, matrix(tme, ncol=1),
               nulltype = 'empirical',
               control=list(lambda=1));
  pi0hatScott.sim <- 1-fdr$priorprob
}

##close the cluster
stopCluster(cl)

dim(pi0hatScottMat)

## [1] 8883 1000

pi0hatScottMean <- colMeans(pi0hatScottMat)
pi0hatScottVar <- apply(pi0hatScottMat,2,var)

length(pi0hatScottMean)

## [1] 1000

##save results
save(file="simResults_pi0x_Scott_1.RData",
     list=c("tme", "pi0",
            "pi0hatScottMean", "pi0hatScottVar"))
```

2 Probability of being a false positive as a smooth function of time

Load simulations and (re)define some variables:

```

load("simResults_2.RData")

nSims <- length(pValuesSims)
ntest <- length(pValuesSims[[1]])

## Set up the time vector and the probability of being null
tme <- seq(-1,2,length=ntest)
pi0 <- pnorm(tme)

splineMat <- ns(tme,df=3)

```

Perform estimation and save estimates:

```

cl<-makeCluster(8) ##specify number of cores less than or equal to number of cores on your
registerDoParallel(cl)

set.seed(31084)

pi0hatScottMatFitLin <- foreach(sim=1:nSims, .combine="rbind", .packages="FDRreg", .errorhan
  zScores <- qnorm(1-pValuesSims[[sim]]/2) ##*sample(c(-1,1), replace=TRUE, size=length(pVal
  fdr <- FDRreg(zScores, tme,
    nulltype = 'empirical',
    control=list(lambda=1));
  pi0hatScottMatFitLin.sim <- 1-fdr$priorprob
}

##close the cluster
stopCluster(cl)

cl<-makeCluster(8) ##specify number of cores less than or equal to number of cores on your
registerDoParallel(cl)

set.seed(31084)

pi0hatScottMatFitSpl <- foreach(sim=1:nSims, .combine="rbind", .packages="FDRreg", .errorhan
  zScores <- qnorm(1-pValuesSims[[sim]]/2) ##*sample(c(-1,1), replace=TRUE, size=length(pVal
  fdr <- FDRreg(zScores, splineMat,
    nulltype = 'empirical',
    control=list(lambda=1));
  pi0hatScottMatFitSpl.sim <- 1-fdr$priorprob
}

##close the cluster
stopCluster(cl)

```

```

dim(pi0hatScottMatFitLin)

## [1] 8779 1000

dim(pi0hatScottMatFitSpl)

## [1] 8779 1000

pi0hatLin.ScottMean <- colMeans(pi0hatScottMatFitLin)
pi0hatLin.ScottVar <- apply(pi0hatScottMatFitLin,2,var)

pi0hatSpl.ScottMean <- colMeans(pi0hatScottMatFitSpl)
pi0hatSpl.ScottVar <- apply(pi0hatScottMatFitSpl,2,var)

length(pi0hatLin.ScottMean)

## [1] 1000

length(pi0hatSpl.ScottMean)

## [1] 1000

##save results
save(file="simResults_pi0x_Scott_2.RData",
      list=c("tme", "pi0",
             "pi0hatLin.ScottMean", "pi0hatLin.ScottVar",
             "pi0hatSpl.ScottMean", "pi0hatSpl.ScottVar"))

```

3 Probability of being a false positive as a sine + step function

Load simulations and (re)define some variables:

```

load("simResults_3.RData")

nSims <- length(pValuesSims)
ntest <- length(pValuesSims[[1]])

## Set up the time vector and the probability of being null
tme1 <- seq(-1*pi,2*pi,length=ntest)
tme2 <- rep(1:0, each=ntest/2)

pi0 <- 1/4*sin(tme1) + tme2/4 + 1/2
range(pi0)

```

```
## [1] 0.2500028 0.9999972

splineMat3 <- cbind(ns(tme1,df=3), tme2)
splineMat20 <- cbind(ns(tme1,df=20), tme2)
```

Perform estimation and save estimates:

```
cl<-makeCluster(8) ##specify number of cores less than or equal to number of cores on your
registerDoParallel(cl)

set.seed(31084)

pi0hatScottMat3 <- foreach(sim=1:nSims, .combine="rbind", .packages="FDRreg", .errorhandling
  zScores <- qnorm(1-pValuesSims[[sim]]/2)###sample(c(-1,1), replace=TRUE, size=length(pVal
  fdr <- FDRreg(zScores, splineMat3,
               nulltype = 'empirical',
               control=list(lambda=1));
  pi0hatScottMat3.sim <- 1-fdr$priorprob
}

##close the cluster
stopCluster(cl)

cl<-makeCluster(8) ##specify number of cores less than or equal to number of cores on your
registerDoParallel(cl)

set.seed(31084)

pi0hatScottMat20 <- foreach(sim=1:nSims, .combine="rbind", .packages="FDRreg", .errorhandling
  zScores <- qnorm(1-pValuesSims[[sim]]/2)###sample(c(-1,1), replace=TRUE, size=length(pVal
  fdr <- FDRreg(zScores, splineMat20,
               nulltype = 'empirical',
               control=list(lambda=1));
  pi0hatScottMat20.sim <- 1-fdr$priorprob
}

##close the cluster
stopCluster(cl)

dim(pi0hatScottMat3)

## [1] 9045 1000

dim(pi0hatScottMat20)

## [1] 9045 1000
```

```

pi0hat3.ScottMean <- colMeans(pi0hatScottMat3)
pi0hat3.ScottVar <- apply(pi0hatScottMat3,2,var)

pi0hat20.ScottMean <- colMeans(pi0hatScottMat20)
pi0hat20.ScottVar <- apply(pi0hatScottMat20,2,var)

length(pi0hat3.ScottMean)

## [1] 1000

length(pi0hat20.ScottMean)

## [1] 1000

##save results
save(file="simResults_pi0x_Scott_3.RData",
      list=c("tme1", "tme2", "pi0",
              "pi0hat3.ScottMean", "pi0hat3.ScottVar",
              "pi0hat20.ScottMean", "pi0hat20.ScottVar"))

```

Session info:

```

devtools::session_info()

## Session info -----
## setting value
## version R version 3.3.1 (2016-06-21)
## system x86_64, mingw32
## ui RTerm
## language (EN)
## collate English_United States.1252
## tz America/New_York
## date 2016-12-31

## Packages -----
## package * version date
## assertthat 0.1 2013-12-06
## BayesLogit * 0.5.1 2014-07-21
## codetools 0.2-14 2015-07-15
## colorspace 1.2-6 2015-03-11
## curl * 1.0 2016-07-24
## DBI 0.4-1 2016-05-08
## devtools 1.12.0 2016-06-24
## digest 0.6.9 2016-01-08
## doParallel * 1.0.10 2015-10-14

```

```

## doRNG      * 1.6      2014-03-07
## dplyr      0.5.0     2016-06-24
## evaluate   0.10      2016-10-11
## fda        * 2.4.4    2014-12-16
## FDRreg     * 0.2-1    2016-08-30
## foreach    * 1.4.3    2015-10-13
## ggdendro   0.1-20    2016-04-27
## ggplot2    2.1.0     2016-03-01
## gridExtra  2.2.1     2016-02-29
## gtable     0.2.0     2016-02-26
## highr      0.6       2016-05-09
## iterators  * 1.0.8    2015-10-13
## knitr       * 1.15.1   2016-11-22
## lattice    0.20-33   2015-07-14
## lazyeval   0.2.0     2016-06-12
## magrittr    1.5      2014-11-22
## MASS        * 7.3-45   2016-04-21
## Matrix      * 1.2-6    2016-05-02
## memoise     1.0.0     2016-01-29
## mosaic      0.14.4    2016-07-29
## mosaicData  0.14.0    2016-06-17
## munsell     0.4.3     2016-02-13
## mvtnorm     * 1.0-5    2016-02-02
## pkgmaker    * 0.22     2014-05-14
## plyr        1.8.4     2016-06-08
## R6          2.1.2     2016-01-26
## Rcpp        0.12.6    2016-07-19
## registry    * 0.3      2015-07-08
## rngtools    * 1.2.4    2014-03-06
## scales      0.4.0     2016-02-26
## stringi     1.1.1     2016-05-27
## stringr     1.0.0     2015-04-30
## tibble      1.1       2016-07-04
## tidyr       0.5.1     2016-06-14
## withr       1.0.2     2016-06-20
## xtable      1.8-2     2016-02-05
## source
## CRAN (R 3.3.1)
## CRAN (R 3.3.0)
## CRAN (R 3.3.1)
## CRAN (R 3.3.1)
## CRAN (R 3.3.1)
## CRAN (R 3.3.1)
## CRAN (R 3.3.1)
## CRAN (R 3.3.1)

```

[illegible]