

UB20XX BLOWER/EXHAUSTER



THE COMPACT, LIGHTWEIGHT AND POWERFUL ATEX-CERTIFIED FAN FOR CONFINED SPACES.

The compact, powerful and lightweight ATEX-certified fan for confined spaces.

This high-pressure explosion-proof axial fan is ideal for hazardous environments.

- Compact and lightweight
- Ultra-quiet operation
- PC/ABS anti-static casing strengthened with glass fibre
- Starter secured in an explosion-proof enclosure to prevent risk of ignition when powered on
- Weatherproof, dent resistant, flame retardant and chemical resistant
- IP55 switch enclosure
- Delivered with a duct adapter

TECHNICAL DATA

		UB20xx (115V)	UB20xx (230V)
	AIRFLOW Free Air	980 cfm (1,666 m³/hr)	819 cfm (1,392 m³/hr)
	AIRFLOW Through Duct 15'/4.6 m w/ one 90' turn: 15'/4.6 m w/ two 90' turns: 25'/7.6 m w/ one 90' turn: 25'/7.6 m w/ two 90' turns:	789 cfm (1,341 m³/hr) 666 cfm(1,132 m³/hr) 722 cfm (1,227 m³/hr) 614 cfm (1,044 m³/hr)	659 cfm (1,120 m³/hr) 558 cfm (948 m³/hr) 603 cfm (1,025 m3/hr) 510 cfm (867 m ₃ /hr)
	Motor	0.33 Hp	0.25 kW
	Motor Type	Totally Encapsulated Air Over Flame Proof	Totally Encapsulated Air Over Flame Proof
	Power supply	115V, 50/60Hz, 1ø	230V, 50/60Hz, 1ø
	Power consumption	7A / 2A	7A / 1.2A
	Cable Lenghts	25', 16AWG	7.6m, 1.5 mm²
	Plug Types	A.T.X. 100/130V	A.T.X. 240V
	Noise	74 dB @ 3' (1 m)	74 dB @ 3' (1 m)
	Weight	27 lbs	12 kg
	Size	14 x 14 x 15.5 in	35 x 35 x 39 cm
	Duct Adapter	2	2

ACCESSORIES:



CONDUCTIVE QUICK COUPLE CANISTER

Allows you to switch quickly from ventilation to extraction while protecting the duct (available in 4.6m or 7.6m versions)







TURBO COUPLE

Connects two or more UB20s to increase the flow by up to 50%



CONDUCTIVE DUCT

Anti-static, Flame retardant and non-collapsible duct with integrated steel helix wire



MANHOLE ENTRY SYSTEM

Enables workers to operate in confined spaces while maintaining ventilation