



v: 2024.05 SIM7670X系列

SIMCom LTE Cat 1bis Module



SIM7670X系列是基于最新QCX216芯片组的LTE Cat 1bis模块,支持LTE-FDD/LTE-TDD无线通信模式。它支 持最高10Mbps的下行速率和5Mbps 上行链路速率。



SIM7670X系列采用LCC+LGA外形,兼容A7670系列 (Cat1模块)、SIM7000/SIM7070系列(NB/Cat M模块) 和SIM800/SIM800F系列(2G模块), 使2G/NB/Cat M 产品能够顺利迁移到LTE Cat1产品,极大地提高了兼容 性满足客户需求的产品设计。

SIM7670X系列支持多种内置网络协议和三种主要操作系 统的驱动程序(适用于Windows、Linux和Android的 USB驱动程序)。软件功能、AT命令与A7670X系列模 块兼容。SIM7670X还集成了GPS/GLONASS/Galileo/北 斗多GNSS接收机,以及丰富的工业标准接口,具有强 大的扩展性,如UART、USB、I2C和GPIO,非常适合远 程信息处理、计量、监控设备、工业路由器和远程 诊断等。

Key Benefits

- ◆ 体积小巧,具有丰富的接口和GNSS
- ◆ 丰富的软件功能: FOTA、SSL、LBS*
- ◆ 集成高性能的多卫星系统接收机
- ◆ 外形尺寸与A7670/SIM7000/SIM7070系列和2G SIM800F/SIM800兼容



产品		SIM7670G	SIM7670NA	SIM7670E
封装形式		LCC+LGA	LCC+LGA	LCC+LGA
尺寸 (mm)		24.0*24.0*2.4	24.0*24.0*2.4	24.0*24.0*2.4
alizant prins	LTE-FDD	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28/B66/B71#	B2/B4/B5/B12/B13/B14 <mark>#/</mark> B66/B71#	B1/B3/B5/B7/B8/B20/B28
频段	LTE-TDD	B34/B38/B39/B40/B41	NA	NA
	GSM	NA	NA	NA
普通工作温度		-30°C ~ +75°C	-30°C ~ +75°C	-30°C ~ +75°C
广展工作温度		-40°C ~ +85°C	-40°C ~ +85°C	-40°C ~ +85°C
电气性能				
工作电压(V)		3.4~ 4.2	3.4~ 4.2	3.4~ 4.2
功耗(mA)	LTE	4.2mA@Idle mode 800uA@Sleep mode, DRX=0.64s	4.2mA@Idle mode 800uA@Sleep mode, DRX=0.64s	4.2mA@Idle mode 800uA@Sleep mode, DRX=0.64s
数据传输				
_TE(Mbps)		10(DL)/5(UL)	10(DL)/5(UL)	10(DL)/5(UL)
软件特性				TOP (IP (IP) (A (IP) (O IA A (I)
支持协议		TCP/IP/IPV4/IPV6/Multi-PDP/FTP/ FTPS /HTTP/HTTPS/DNS/MQTT	TCP/IP/IPV4/IPV6/Multi-PDP/FTP/ FTPS /HTTP/HTTPS/DNS/MQTT	, TCP/IP/IPV4/IPV6/Multi- PDP/FTP/ FTPS /HTTP/HTTPS/DNS/MQTT
ΓLS		•	•	•
文件系统		•	•	•
WIFISCAN		•	•	•
LBS		0	0	0
FOTA		•	•	•
Android RIL		Android 5.0/6.0/7.0/8.0/9.0	Android 5.0/6.0/7.0/8.0/9.0	Android 5.0/6.0/7.0/8.0/9.0
USB驱动		Microsoft Windows 7/8/10 Linux/Android	Microsoft Windows 7/8/10 Linux/Android	Microsoft Windows 7/8/10 Linux/Android
WWAN (RNDIS)		•	•	•
VoLTE		NA	NA	NA
ECM		•	•	•
嵌入式AT命令		0	0	0
固件升级方式		USB/FOTA	USB/FOTA	USB/FOTA
接口				
SIM Card		1.8V/3.0V	1.8V/3.0V	1.8V/3.0V
UART		•	•	•
USB		•	•	•
ADC		•	•	•
PCM		•	•	•
GPIO		•	•	•
12C		•	•	•
GNSS		0	0	0
人证				
Certification		CE-RED/FCC/TELEC/JATE/ GCF/PTCRB/RCM*/IC/NCC*/KC/CC C*/CTA*/SRRC*/RoHS/REACH/ AT&T*/TMOBILE*/VERIZON*	FCC/IC/GCF/PTCRB/ RoHS/REACH/AT&T*/ T-MOBILE*/VERIZON*	CE-RED/UKCA*/RCM*/ RoHS/REACH/DT*/GCF*

●: 支持 o/#: 可选 *: 进行中或者计划中