

Interferometric Phase Image Estimation via Sparse Coding in the Complex Domain

José M. Bioucas Dias

Instituto Superior Técnico and Instituto de Telecomunicações
Technical University of Lisbon

PORTUGAL

bioucas@lx.it.pt, www.lx.it.pt/~bioucas



Joint work with *Hao Hongxing* (IST)
 Gonçalo Valadão (IT)
 Vladimir Katkovnik (TUT)



Outline

1. The phase estimation problem
2. Examples in InSAR and in MRI
3. Phase unwrapping
4. Interferometric phase estimation via sparse coding
5. Non-Gaussian and non-additive noise
6. Concluding remarks

Absolute Phase Estimation problem

Given a set of observations $e^{j\phi_p} \equiv (\cos \phi_p, \sin \phi_p)$,
for $p \in \mathcal{V} \equiv \{1, \dots, n\}$, determine ϕ_p (up to a constant)

$e^{j\phi_p}$ is 2π -periodic \Rightarrow nonlinear and ill-posed inverse problem

Continuous/discrete flavor:

$$\phi = \mathcal{W}[\phi] + 2k\pi \quad \mathcal{W} : \mathbb{R} \rightarrow [\pi, \pi[$$

Phase Unwrapping (PU)



Estimation of $k \in \mathbb{Z}$

Phase Denoising (PD)




Estimation of $\mathcal{W}(\phi) \in [\pi, \pi[$
(wrapped phase)

Applications


- ❑ Synthetic aperture radar/sonar
- ❑ Magnetic resonance imaging
- ❑ Doppler weather radar
- ❑ Doppler echocardiography
- ❑ Optical interferometry
- ❑ Diffraction tomography

Absolute Phase Estimation in InSAR (Interferometric SAR)





InSAR Problem: Estimate $\phi_2 - \phi_1$ from signals read by s_1 and s_2

InSAR Example




Mountainous terrain around
Long's Peak, Colorado


Interferogram $\mathcal{W}(\phi_1 - \phi_2)$



Differential Interferometry




Differential Interferometry




Differential InSAR derived subsidence in Las Vegas between 1992 and 1997 (from [Amelung et al., 1999]).

Magnetic Resonance Imaging - MRI

Intensity



Interferometric phase



Interferometric phase

- measure temperature
- visualize veins in tissues
- water-fat separation
- map the principal magnetic field

Forward Problem: Sensor Model

$$z_i = \cos \phi + n_i \quad n = (n_i, n_q)$$


$$z_q = \sin \phi + n_q \quad z = (z_i, z_q)$$

$$(n_i, n_q) \sim \mathcal{N}(0, \sigma^2 \mathbf{I}_2)$$

$$p(z|\phi) \propto c e^{\lambda \cos(\phi - \eta)}$$

$$\eta = \arg(z)$$

$$\lambda = \frac{2|z|}{\sigma^2}$$




$$\hat{\phi}_{ML} = \eta + 2k\pi$$



Simulated Interferograms

Images of $\eta = \arg(e^{j\phi} + n)$


$$\text{SNR} \equiv \frac{1}{2\sigma^2}$$





SNR=4




SNR=1




SNR= ∞



histogram of $\mathcal{W}(\phi - \eta)$




histogram of $\mathcal{W}(\phi - \eta)$




Real Interferograms


MRI




MRI



InSAR



InSAR





Bayesian Approach

data density: $p(\mathbf{z}|\boldsymbol{\phi}) = \prod_{p \in \mathcal{V}} p(z_p|\phi_p)$

$$p(\boldsymbol{\phi}) = \frac{1}{Z} e^{-\sum_{\{p,q\} \in \mathcal{E}} E_{pq}(\phi_p - \phi_q)}$$

prior (MRF):

- $\mathcal{E} = \{\{p, q\} : p \sim q\}$ clique set
- $E_{pq}(\cdot)$ clique potential (pairwise interaction)



Maximum a Posteriori Estimation Criterion

□ $\hat{\phi} \in \arg \max_{\phi \in \mathbb{R}^n} p(\phi|\mathbf{z})$ $p(\phi|\mathbf{z}) \propto p(\mathbf{z}|\phi) p(\phi)$ posterior density

$$= \arg \min_{\phi} E(\phi) \quad E(\phi) = -\log p(\phi|\mathbf{z}) + c^{te}$$

$$E(\phi) = \sum_{p \in \mathcal{V}} -\lambda_p \cos(\phi_p - \eta_p) + \sum_{\{p,q\} \in \mathcal{E}} E_{pq}(\phi_p - \phi_q)$$

□ Phase unwrapping ($\lambda_p \rightarrow \infty$):

$$\phi_p = \eta_p + 2k_p\pi \quad \text{for } k_p \in \{0, 1, \dots, K-1\}$$

$$\hat{\phi} \in \arg \min_{\mathbf{k} \in \mathbb{Z}^n} E(\mathbf{k}) \quad E(\mathbf{k}) = \sum_{\{p,q\} \in \mathcal{E}} V_{pq}(k_p - k_q)$$

$$V_{pq}(k_p - k_q) = E_{pq}(\eta_p - \eta_q + 2\pi(k_p - k_q))$$

Phase Unwrapping Algorithms

$$E(\mathbf{k}) = \sum_{\{p,q\} \in \mathcal{E}} V_{pq}(k_p - k_q)$$

- $E_{pq}(\cdot) = |\cdot|_{2\pi\text{-quantized}}$

[Flynn, 97] (exact) \rightarrow sequence of positive cycles on a graph

[Costantini, 98] (exact) \rightarrow min-cost flow on a graph ($|\mathcal{V}| = n, |\mathcal{E}| = 4n$)

- $E_{pq}(\cdot) = (\cdot)^2$

[B & Leitao, 01] (exact) \rightarrow sequence of positive cycles on a graph ($|\mathcal{V}| = n, |\mathcal{E}| = 4n$)

[Frey et al., 01] (approx) \rightarrow belief propagation on a 1st order MRF

- $E_{pq}(\cdot)$ convex

[B & Valadao, 05,07,09] (exact) \rightarrow Sequence of K min cuts ($KT(n, 6n)$)

- $E_{pq}(\cdot)$ non-convex

[Ghiglia, 96] \rightarrow LPN0 (continuous relaxation)

[B & G. Valadao, 05, 07,09] \rightarrow Sequence of min cuts ($KT(n, 6n)$)

PUMA (Phase Unwrapping MAX-flow)

[B & Valadao, 05,07,09]

```
 $\phi^{(0)} = \eta$   
while success == false  
     $\delta' := \arg \min_{\delta \in \{0,1\}^{|\nu|}} E(\phi + 2\delta\pi)$   
    if  $E(\phi + 2\delta'\pi) < E(\phi)$  then  $\phi := \phi + 2\delta'\pi$   
    else success = true  
end
```

PUMA finds a sequence of steepest descent binary images

PUMA: Convex Priors

- A local minimum is a global minimum
- Takes at most K iterations
- E is submodular: $2V_{pq}(0) \leq V_{pq}(1) + V_{pq}(-1)$
 \Rightarrow each binary optimization has the complexity of a min cut $T(n, 6n)$







$$E(\mathbf{k}) = \sum_{p \in \mathcal{V}} U_p(k_p) + \sum_{\{p,q\} \in \mathcal{E}} V_{pq}(k_p - k_q)$$

- Related algorithms

[Veksler, 99] (1-jump moves)
[Murota, 03] (steepest descent algorithm for L-convex functions)
[Ishikawa, 03] (MRFs with convex priors)
[Kolmogorov & Shiyoura, 05,07], [Darbon, 05] (Include unary terms)
[Ahuja, Hochbaum, Orlin, 03] (convex dual network flow problem)


Results

$$E_{pq}(\cdot) = (\cdot)^2$$




Results


Convex priors do not preserve discontinuities



$$E_{pq}(x) = x^2$$




$$E_{pq}(x) = |x|$$



$$E_{pq}(x) = \begin{cases} x^2 & |x| \leq \pi \\ \pi^2 |x/\pi|^{0.5} & |x| > \pi \end{cases}$$

E_{pq} is not graph representable




PUMA: Non-convex priors

Ex: $E(x) = \min(x^2, \pi^2)$

Models discontinuities

Models Gaussian noise



Shortcomings

- ❑ Local minima are no more global minima
- ❑ Energy contains nonsubmodular terms (NP-hard)


Proposed suboptimal solution: majorization minimization applied To PUMA binary problem

Other suboptimal approaches

- ❑ Quadratic Pseudo Boolean Optimization (Probing [Boros et al., 2006], Improving [Rother et al., 2007])
- ❑ Sequential Tree-Reweighted Message Passing (TRW-S) [Kolmogorov, 2006]
- ❑ Dual decomposition (DD) [Komodakis et al., 2011]

Majorizing Nonsubmodular Terms

Majorization Minimization (MM) [Lange & Fessler, 95]



$$\begin{cases} \tilde{V}(\mathbf{k}) = V(\mathbf{k}) \\ \tilde{V}(\mathbf{k} + \boldsymbol{\delta}) \geq V(\mathbf{k} + \boldsymbol{\delta}) \end{cases}$$

$$\boldsymbol{\delta}' = \arg \min_{\boldsymbol{\delta}} \tilde{V}(\mathbf{k} + \boldsymbol{\delta})$$


Non-increasing property

$$V(\mathbf{k} + \boldsymbol{\delta}') \leq V(\mathbf{k})$$


[Rother et al., 05] \rightarrow similar approach for alpha expansion moves

Results with PUMA (MM)

Interferogram η




$\hat{\phi}(\text{MM})$ (8 iter)




Interferogram η



$\hat{\phi}(\text{MM})$ (8 iter)





Multi-jump version of PUMA (MM)
jumps $d \in [1 \ 2 \ 3 \ 4]$

$$\delta' := \arg \min_{\delta \in \{0, d\}^{|V|}} E(\phi + 2\delta\pi)$$

