NAME

gbz80 — CPU opcode reference

DESCRIPTION

This is the list of opcodes supported by rgbasm(1), including a short description, the number of bytes needed to encode them and the number of CPU cycles at 1MHz (or 2MHz in GBC dual speed mode) needed to complete them.

Note: All arithmetic/logic operations that use register **A** as destination can omit the destination as it is assumed it's register **A**. The following two lines have the same effect:

```
OR A,B
OR B
```

LEGEND

List of abbreviations used in this document.

r8   Any of the 8-bit registers (**A**, **B**, **C**, **D**, **E**, **H**, **L**).

r16   Any of the general-purpose 16-bit registers (**BC**, **DE**, **HL**).

n8   8-bit integer constant.

n16   16-bit integer constant.

e8   8-bit offset (**−128** to **127**).

u3   3-bit unsigned integer constant (**0** to **7**).

cc   Condition codes:
   Z: Execute if Z is set.
   NZ: Execute if Z is not set.
   C: Execute if C is set.
   NC: Execute if C is not set.

vec   One of the *RST* vectors (**0x00**, **0x08**, **0x10**, **0x18**, **0x20**, **0x28**, **0x30** and **0x38**).

INSTRUCTION OVERVIEW

8-bit Arithmetic and Logic Instructions

ADC A,r8
ADC A,[HL]
ADC A,n8
ADD A,r8
ADD A,[HL]
ADD A,n8
AND A,r8
AND A,[HL]
AND A,n8
CP A,r8
CP A,[HL]
CP A,n8
DEC r8
DEC [HL]
INC r8
INC [HL]

OR A,r8
OR A,[HL]
OR A,n8
SBC A,r8
SBC A,[HL]
SBC A,n8
SUB A,r8
SUB A,[HL]
SUB A,n8
XOR A,r8
XOR A,[HL]
XOR A,n8

16-bit Arithmetic Instructions
ADD HL,r16
DEC r16
INC r16

Bit Operations Instructions
BIT u3,r8
BIT u3,[HL]
RES u3,r8
RES u3,[HL]
SET u3,r8
SET u3,[HL]
SWAP r8
SWAP [HL]

Bit Shift Instructions
RL r8
RL [HL]
RLA
RLC r8
RLC [HL]
RLCA
RR r8
RR [HL]
RRA
RRC r8
RRC [HL]
RRCA
SLA r8
SLA [HL]
SRA r8
SRA [HL]
SRL r8
SRL [HL]

Load Instructions

LD r8,r8
LD r8,n8
LD r16,n16
LD [HL],r8
LD [HL],n8
LD r8,[HL]
LD [r16],A
LD [n16],A
LD [$FF00+n8],A
LD [$FF00+C],A
LD A,[r16]
LD A,[n16]
LD A,[$FF00+n8]
LD A,[$FF00+C]
LD [HL+],A
LD [HL-],A
LD A,[HL+]
LD A,[HL-]

Jumps and Subroutines
CALL n16
CALL cc,n16
JP HL
JP n16
JP cc,n16
JR e8
JR cc,e8
RET cc
RET
RETI
RST vec

Stack Operations Instructions
ADD HL,SP
ADD SP,e8
DEC SP
INC SP
LD SP,n16
LD [n16],SP
LD HL,SP+e8
LD SP,HL
POP AF
POP r16
PUSH AF
PUSH r16

Miscellaneous Instructions
CCF
CPL

DAA
DI
EI
HALT
NOP
SCF
STOP

INSTRUCTION REFERENCE

ADC A,r8

Add the value in `r8` plus the carry flag to **A**.

Cycles: 1

Bytes: 1

Flags:
- **Z**: Set if result is 0.
- **N**: 0
- **H**: Set if overflow from bit 3.
- **C**: Set if overflow from bit 7.

ADC A,[HL]

Add the value pointed by **HL** plus the carry flag to **A**.

Cycles: 2

Bytes: 1

Flags: See **ADC A,r8**

ADC A,n8

Add the value `n8` plus the carry flag to **A**.

Cycles: 2

Bytes: 2

Flags: See **ADC A,r8**

ADD A,r8

Add the value in `r8` to **A**.

Cycles: 1

Bytes: 1

Flags:
- **Z**: Set if result is 0.
- **N**: 0
- **H**: Set if overflow from bit 3.
- **C**: Set if overflow from bit 7.

ADD A,[HL]

Add the value pointed by **HL** to **A**.

Cycles: 2

Bytes: 1

Flags: See **ADD A,r8**

ADD A,n8

Add the value $n8$ to **A**.

Cycles: 2

Bytes: 2

Flags: See **ADD A,r8**

ADD HL,r16

Add the value in $r16$ to **HL**.

Cycles: 2

Bytes: 1

Flags:
- **N**: 0
- **H**: Set if overflow from bit 11.
- **C**: Set if overflow from bit 15.

ADD HL,SP

Add the value in **SP** to **HL**.

Cycles: 2

Bytes: 1

Flags: See **ADD HL,r16**

ADD SP,e8

Add the signed value $e8$ to **SP**.

Cycles: 4

Bytes: 2

Flags:
- **Z**: 0
- **N**: 0
- **H**: Set if overflow from bit 3.
- **C**: Set if overflow from bit 7.

AND A,r8

Bitwise AND between the value in $r8$ and **A**.

Cycles: 1

Bytes: 1

Flags:
- **Z**: Set if result is 0.
- **N**: 0

- **H**: 1
- **C**: 0

AND A,[HL]

Bitwise AND between the value pointed by **HL** and **A**.

Cycles: 2

Bytes: 1

Flags: See **AND A,r8**

AND A,n8

Bitwise AND between the value in `n8` and **A**.

Cycles: 2

Bytes: 2

Flags: See **AND A,r8**

BIT u3,r8

Test bit `u3` in register `r8`, set the zero flag if bit not set.

Cycles: 2

Bytes: 2

Flags:
- **Z**: Set if the selected bit is 0.
- **N**: 0
- **H**: 1

BIT u3,[HL]

Test bit `u3` in the byte pointed by **HL**, set the zero flag if bit not set.

Cycles: 3

Bytes: 2

Flags: See **BIT u3,r8**

CALL n16

Call address `n16`.

Cycles: 6

Bytes: 3

Flags: None affected.

CALL cc,n16

Call address `n16` if condition `cc` is met.

Cycles: 6/3

Bytes: 3

Flags: None affected.

CCF

   Complement Carry Flag.

   Cycles: 1

   Bytes: 1

   Flags:
   • **N**: 0
   • **H**: 0
   • **C**: Complemented.

CP A,r8

   Subtract the value in *r8* from **A** and set flags accordingly, but don't store the result.

   Cycles: 1

   Bytes: 1

   Flags:
   • **Z**: Set if result is 0.
   • **N**: 1
   • **H**: Set if no borrow from bit 4.
   • **C**: Set if no borrow (set if *r8* > **A**) .

CP A,[HL]

   Subtract the value pointed by **HL** from **A** and set flags accordingly, but don't store the result.

   Cycles: 2

   Bytes: 1

   Flags: See **CP A,r8**

CP A,n8

   Subtract the value *n8* from **A** and set flags accordingly, but don't store the result.

   Cycles: 2

   Bytes: 2

   Flags: See **CP A,r8**

CPL

   Complement accumulator (**A** = ˜**A**) .

   Cycles: 1

   Bytes: 1

   Flags:
   • **N**: 1
   • **H**: 1

DAA

   Decimal adjust register A to get a correct BCD representation after an arithmetic instruction.

   Cycles: 1

Bytes: 1

Flags:
- **Z**: Set if result is 0.
- **H**: 0
- **C**: Set or reset depending on the operation.

DEC r8
Decrement value in register `r8` by 1.

Cycles: 1

Bytes: 1

Flags:
- **Z**: Set if result is 0.
- **N**: 1
- **H**: Set if no borrow from bit 4.

DEC [HL]
Decrement the value pointed by **HL** by 1.

Cycles: 3

Bytes: 1

Flags: See **DEC r8**

DEC r16
Decrement value in register `r16` by 1.

Cycles: 2

Bytes: 1

Flags: None affected.

DEC SP
Decrement value in register **SP** by 1.

Cycles: 2

Bytes: 1

Flags: None affected.

DI
Disable Interrupts.

Cycles: 1

Bytes: 1

Flags: None affected.

EI
Enable Interrupts.

Cycles: 1

Bytes: 1

Flags: None affected.

HALT

Enter CPU low power mode.

Cycles: -

Bytes: 1

Flags: None affected.

INC r8

Increment value in register `r8` by 1.

Cycles: 1

Bytes: 1

Flags:
- **Z**: Set if result is 0.
- **N**: 0
- **H**: Set if overflow from bit 3.

INC [HL]

Increment the value pointed by **HL** by 1.

Cycles: 3

Bytes: 1

Flags: See **INC r8**

INC r16

Increment value in register `r16` by 1.

Cycles: 2

Bytes: 1

Flags: None affected.

INC SP

Increment value in register **SP** by 1.

Cycles: 2

Bytes: 1

Flags: None affected.

JP n16

Absolute jump to address `n16`.

Cycles: 4

Bytes: 3

Flags: None affected.

JP cc,n16
    Absolute jump to address *n16* if condition *cc* is met.

    Cycles: 4/3

    Bytes: 3

    Flags: None affected.

JP HL
    Jump to address in **HL**, that is, load **PC** with value in register **HL**.

    Cycles: 1

    Bytes: 1

    Flags: None affected.

JR e8
    Relative jump by adding *e8* to the current address.

    Cycles: 3

    Bytes: 2

    Flags: None affected.

JR cc,e8
    Relative jump by adding *e8* to the current address if condition *cc* is met.

    Cycles: 3/2

    Bytes: 2

    Flags: None affected.

LD r8,r8
    Store value in register on the right into register on the left.

    Cycles: 1

    Bytes: 1

    Flags: None affected.

LD r8,n8
    Load value *n8* into register *r8*.

    Cycles: 2

    Bytes: 2

    Flags: None affected.

LD r16,n16
    Load value *n16* into register *r16*.

    Cycles: 3

    Bytes: 3

Flags: None affected.

LD [HL],r8

Store value in register `r8` into byte pointed by register **HL**.

Cycles: 2

Bytes: 1

Flags: None affected.

LD [HL],n8

Store value `n8` into byte pointed by register **HL**.

Cycles: 3

Bytes: 2

Flags: None affected.

LD r8,[HL]

Load value into register `r8` from byte pointed by register **HL**.

Cycles: 2

Bytes: 1

Flags: None affected.

LD [r16],A

Store value in register **A** into address pointed by register `r16`.

Cycles: 2

Bytes: 1

Flags: None affected.

LD [n16],A

Store value in register **A** into address `n16`.

Cycles: 4

Bytes: 3

Flags: None affected.

LD [$FF00+n8],A

Store value in register **A** into high RAM or I/O registers.

The following synonym forces this encoding: **LDH [$FF00+n8],A**

Cycles: 3

Bytes: 2

Flags: None affected.

LD [$FF00+C],A

Store value in register **A** into high RAM or I/O registers.

Cycles: 2

Bytes: 1

Flags: None affected.

LD A,[r16]

Load value in register **A** from address pointed by register *r16*.

Cycles: 2

Bytes: 1

Flags: None affected.

LD A,[n16]

Load value in register **A** from address *n16*.

Cycles: 4

Bytes: 3

Flags: None affected.

LD A,[$FF00+n8]

Load value in register **A** from high RAM or I/O registers.

The following synonym forces this encoding: **LDH A,[$FF00+n8]**

Cycles: 3

Bytes: 2

Flags: None affected.

LD A,[$FF00+C]

Load value in register **A** from high RAM or I/O registers.

Cycles: 2

Bytes: 1

Flags: None affected.

LD [HL+],A

Store value in register **A** into byte pointed by **HL** and post-increment **HL**.

Cycles: 2

Bytes: 1

Flags: None affected.

LD [HL-],A

Store value in register **A** into byte pointed by **HL** and post-decrement **HL**.

Cycles: 2

Bytes: 1

Flags: None affected.

LD A,[HL+]
> Load value into register **A** from byte pointed by **HL** and post-increment **HL**.
>
> Cycles: 2
>
> Bytes: 1
>
> Flags: None affected.

LD A,[HL-]
> Load value into register **A** from byte pointed by **HL** and post-decrement **HL**.
>
> Cycles: 2
>
> Bytes: 1
>
> Flags: None affected.

LD SP,n16
> Load value *n16* into register **SP**.
>
> Cycles: 3
>
> Bytes: 3
>
> Flags: None affected.

LD [n16],SP
> Store **SP** into addresses *n16* (LSB) and *n16* + 1 (MSB).
>
> Cycles: 5
>
> Bytes: 3
>
> Flags: None affected.

LD HL,SP+e8
> Add the signed value *e8* to **SP** and store the result in **HL.**
>
> Cycles: 3
>
> Bytes: 2
>
> Flags:
> * **Z**: 0
> * **N**: 0
> * **H**: Set if overflow from bit 3.
> * **C**: Set if overflow from bit 7.

LD SP,HL
> Load register **HL** into register **SP**.
>
> Cycles: 2
>
> Bytes: 1
>
> Flags: None affected.

NOP

No operation.

Cycles: 1

Bytes: 1

Flags: None affected.

OR A,r8

Bitwise OR between the value in *r8* and **A**.

Cycles: 1

Bytes: 1

Flags:
- **Z**: Set if result is 0.
- **N**: 0
- **H**: 0
- **C**: 0

OR A,[HL]

Bitwise OR between the value pointed by **HL** and **A**.

Cycles: 2

Bytes: 1

Flags: See **OR A,r8**

OR A,n8

Bitwise OR between the value in *n8* and **A**.

Cycles: 2

Bytes: 2

Flags: See **OR A,r8**

POP AF

Pop register **AF** from the stack.

Cycles: 3

Bytes: 1

Flags: None affected.

POP r16

Pop register *r16* from the stack.

Cycles: 3

Bytes: 1

Flags: None affected.

PUSH AF
　　Push register **AF** into the stack.

　　Cycles: 4

　　Bytes: 1

　　Flags: None affected.

PUSH r16
　　Push register `r16` into the stack.

　　Cycles: 4

　　Bytes: 1

　　Flags: None affected.

RES u3,r8
　　Set bit `u3` in register `r8` to 0.

　　Cycles: 2

　　Bytes: 2

　　Flags: None affected.

RES u3,[HL]
　　Set bit `u3` in the byte pointed by **HL** to 0.

　　Cycles: 4

　　Bytes: 2

　　Flags: None affected.

RET
　　Return from subroutine.

　　Cycles: 4

　　Bytes: 1

　　Flags: None affected.

RET cc
　　Return from subroutine if condition `cc` is met.

　　Cycles: 5/2

　　Bytes: 1

　　Flags: None affected.

RETI
　　Return from subroutine and enable interrupts.

　　Cycles: 4

　　Bytes: 1

Flags: None affected.

RL r8

Rotate register `r8` left through carry.

   C <- [7 <- 0] <- C

Cycles: 2

Bytes: 2

Flags:
- **Z**: Set if result is 0.
- **N**: 0
- **H**: 0
- **C**: Set according to result.

RL [HL]

Rotate value pointed by **HL** left through carry.

   C <- [7 <- 0] <- C

Cycles: 4

Bytes: 2

Flags: See **RL r8**

RLA

Rotate register **A** left through carry.

   C <- [7 <- 0] <- C

Cycles: 1

Bytes: 1

Flags:
- **Z**: 0
- **N**: 0
- **H**: 0
- **C**: Set according to result.

RLC r8

Rotate register `r8` left.

   C <- [7 <- 0] <- [7]

Cycles: 2

Bytes: 2

Flags:
- **Z**: Set if result is 0.
- **N**: 0
- **H**: 0
- **C**: Set according to result.

RLC [HL]

  Rotate value pointed by **HL** left.

        C <- [7 <- 0] <- [7]

  Cycles: 4

  Bytes: 2

  Flags: See **RLC r8**

RLCA

  Rotate register **A** left.

        C <- [7 <- 0] <- [7]

  Cycles: 1

  Bytes: 1

  Flags:
  • **Z**: 0
  • **N**: 0
  • **H**: 0
  • **C**: Set according to result.

RR r8

  Rotate register *r8* right through carry.

        C -> [7 -> 0] -> C

  Cycles: 2

  Bytes: 2

  Flags:
  • **Z**: Set if result is 0.
  • **N**: 0
  • **H**: 0
  • **C**: Set according to result.

RR [HL]

  Rotate value pointed by **HL** right through carry.

        C -> [7 -> 0] -> C

  Cycles: 4

  Bytes: 2

  Flags: See **RR r8**

RRA

  Rotate register **A** right through carry.

        C -> [7 -> 0] -> C

  Cycles: 1

  Bytes: 1

Flags:
- **Z**: 0
- **N**: 0
- **H**: 0
- **C**: Set according to result.

RRC r8

Rotate register `r8` right.

[0] -> [7 -> 0] -> C

Cycles: 2

Bytes: 2

Flags:
- **Z**: Set if result is 0.
- **N**: 0
- **H**: 0
- **C**: Set according to result.

RRC [HL]

Rotate value pointed by **HL** right.

[0] -> [7 -> 0] -> C

Cycles: 4

Bytes: 2

Flags: See **RRC r8**

RRCA

Rotate register **A** right.

[0] -> [7 -> 0] -> C

Cycles: 1

Bytes: 1

Flags:
- **Z**: 0
- **N**: 0
- **H**: 0
- **C**: Set according to result.

RST vec

Call restart vector `vec`.

Cycles: 4

Bytes: 1

Flags: None affected.

SBC A,r8

Subtract the value in `r8` and the carry flag from **A**.

Cycles: 1

Bytes: 1

Flags:
- **Z**: Set if result is 0.
- **N**: 1
- **H**: Set if no borrow from bit 4.
- **C**: Set if no borrow (set if $r8 > $ **A**).

SBC A,[HL]

Subtract the value pointed by **HL** and the carry flag from **A**.

Cycles: 2

Bytes: 1

Flags: See **SBC A,r8**

SBC A,n8

Subtract the value $n8$ and the carry flag from **A**.

Cycles: 2

Bytes: 2

Flags: See **SBC A,r8**

SCF

Set Carry Flag.

Cycles: 1

Bytes: 1

Flags:
- **N**: 0
- **H**: 0
- **C**: 1

SET u3,r8

Set bit $u3$ in register $r8$ to 1.

Cycles: 2

Bytes: 2

Flags: None affected.

SET u3,[HL]

Set bit $u3$ in the byte pointed by **HL** to 1.

Cycles: 4

Bytes: 2

Flags: None affected.

SLA r8

Shift left arithmetic register `r8`.

C <- [7 <- 0] <- 0

Cycles: 2

Bytes: 2

Flags:
- **Z**: Set if result is 0.
- **N**: 0
- **H**: 0
- **C**: Set according to result.

SLA [HL]

Shift left arithmetic value pointed by **HL**.

C <- [7 <- 0] <- 0

Cycles: 4

Bytes: 2

Flags: See **SLA r8**

SRA r8

Shift right arithmetic register `r8`.

[7] -> [7 -> 0] -> C

Cycles: 2

Bytes: 2

Flags:
- **Z**: Set if result is 0.
- **N**: 0
- **H**: 0
- **C**: Set according to result.

SRA [HL]

Shift right arithmetic value pointed by **HL**.

[7] -> [7 -> 0] -> C

Cycles: 4

Bytes: 2

Flags: See **SRA r8**

SRL r8

Shift right logic register `r8`.

0 -> [7 -> 0] -> C

Cycles: 2

Bytes: 2

Flags:
- **Z**: Set if result is 0.
- **N**: 0
- **H**: 0
- **C**: Set according to result.

SRL [HL]

Shift right logic value pointed by **HL**.

        0 -> [7 -> 0] -> C

Cycles: 4

Bytes: 2

Flags: See **SRA r8**

STOP

Enter CPU very low power mode. Also used to switch between double and normal speed CPU modes in GBC.

Cycles: -

Bytes: 2

Flags: None affected.

SUB A,r8

Subtract the value in `r8` from **A**.

Cycles: 1

Bytes: 1

Flags:
- **Z**: Set if result is 0.
- **N**: 1
- **H**: Set if no borrow from bit 4.
- **C**: Set if no borrow (set if `r8` > **A**) .

SUB A,[HL]

Subtract the value pointed by **HL** from **A**.

Cycles: 2

Bytes: 1

Flags: See **SUB A,r8**

SUB A,n8

Subtract the value `n8` from **A**.

Cycles: 2

Bytes: 2

Flags: See **SUB A,r8**

SWAP r8
> Swap upper 4 bits in register `r8` and the lower ones.
>
> Cycles: 2
>
> Bytes: 2
>
> Flags:
> - **Z**: Set if result is 0.
> - **N**: 0
> - **H**: 0
> - **C**: 0

SWAP [HL]
> Swap upper 4 bits in the byte pointed by **HL** and the lower ones.
>
> Cycles: 4
>
> Bytes: 2
>
> Flags: See **SWAP r8**

XOR A,r8
> Bitwise XOR between the value in `r8` and **A**.
>
> Cycles: 1
>
> Bytes: 1
>
> Flags:
> - **Z**: Set if result is 0.
> - **N**: 0
> - **H**: 0
> - **C**: 0

XOR A,[HL]
> Bitwise XOR between the value pointed by **HL** and **A**.
>
> Cycles: 2
>
> Bytes: 1
>
> Flags: See **XOR A,r8**

XOR A,n8
> Bitwise XOR between the value in `n8` and **A**.
>
> Cycles: 2
>
> Bytes: 2
>
> Flags: See **XOR A,r8**

SEE ALSO
rgbasm(1), rgbds(7)

HISTORY
rgbds was originally written by Carsten Sørensen as part of the ASMotor package, and was later packaged in RGBDS by Justin Lloyd. It is now maintained by a number of contributors at

https://github.com/rednex/rgbds