

Lab No : 10
Name of the Lab : Implementation of Round Robin Scheduling Algorithm
ID : IT-17005

Objectives:

- i) What is Round Robin Scheduling Algorithm?
- ii) How to implementation in C?

Answer no (i):

Round Robin scheduling :

Let's take one example to understand it.

Time Quantum = 2

Process	Arrival time	Burst time
P1	0	4
P2	1	5
P3	2	2
P4	3	1
P5	4	6
P6	5	3

Hence the GANTT chart will be following:

P1	P2	P3	P1	P4	P5	P2	P6	P5	P2	P6	P5
----	----	----	----	----	----	----	----	----	----	----	----

0 2 4 6 8 9 11 13 15 17 18 19 21

Process	A.T	B.T	W.T=(s.t-a.t) + (s.t-l.c.t)	T.A.T=B.T+W.T	R.T= s.t- a.t
P1	0	4	4	8	0
P2	1	5	12	17	1
P3	2	2	2	4	2
P4	3	1	5	6	5
P5	4	6	11	17	5
P6	6	3	10	13	7

$$\text{Average waiting time} = \frac{4+12+2+5+11+10}{6} = 7.33 \text{ ms}$$

$$\text{Average turn around time} = \frac{8+17+4+6+17+13}{6} = 10.83 \text{ ms}$$

Answer no (ii):

The implementation of Round Robin scheduling algorithm in C is given below:

Code:

```
//implementation of Round Robin scheduling algorithm
#include <iostream>
#include <vector>
using namespace std;
int main()
{
    int i,n,time,remain,temps=0,time_quantum;
    int wt=0,tat=0;
    cout<<"Enter the total number of process:";
    cin>>n;
    remain=n;

    vector<int>at(n);
    vector<int>bt(n);
    vector<int>rt(n);

    for(i=0; i<n; i++)
    {
```

```

    cout<<"Enter the Arrival time & Burst time of the processes:"<<i+1<<" ";
    cin>>at[i]>>bt[i];
    rt[i]=bt[i];
}
cout<<"Enter the value of time QUANTUM:"<<endl;
cin>>time_quantum;
cout<<"Process\tA.T\tB.T\tW.T\tT.A.T\n";
for(time=0,i=0; remain!=0;)
{
    if(rt[i]<=time_quantum && rt[i]>0)
    {
        time += rt[i];
        rt[i]=0;
        temps=1;
    }

    else if(rt[i]>0)
    {
        rt[i] -= time_quantum;
        time += time_quantum;
    }

    if(rt[i]==0 && temps==1)
    {
        remain--;
        cout<<i+1<<"\t"<<at[i]<<"\t"<<bt[i]<<"\t"<<time-at[i]-
bt[i]<<"\t"<<time-at[i];
        cout<<endl;
        wt += time-at[i]-bt[i];
        tat += time-at[i];
        temps=0;
    }

    if(i == n-1)
        i=0;
    else if(at[i+1] <= time)
        i++;
    else
        i=0;
}

cout<<"Average waiting time "<<wt*1.0/n<<endl;
cout<<"Average turn around time "<<tat*1.0/n<<endl;;

```

```
    return 0;  
}
```

Output:

```
Enter the total number of process:4  
Enter the Arrival time & Burst time of the processes:1 1 4  
Enter the Arrival time & Burst time of the processes:2 2 3  
Enter the Arrival time & Burst time of the processes:3 3 5  
Enter the Arrival time & Burst time of the processes:4 4 7  
Enter the value of time QUANTUM:  
2  
Process A.T    B.T    W.T    T.A.T  
1        1      4      5      9  
2        2      3      6      9  
3        3      5      8      13  
4        4      7      8      15  
Average waiting time 6.75  
Average turn around time 11.5  
  
Process returned 0 (0x0)    execution time : 49.919 s
```