



Welcome to
IT-Tool
“The Army Knife
for Windows”

“This document is under
construction”

IT-Tool is a compact plug and play handheld assistant for PCs that simplifies everyday technical work. It combines 3.5” touch color display, and smart software to help users diagnose systems, automate tasks, and navigate computers quickly—without the need for heavy installations.

It includes several key functions:

- ReadyUSB runs trusted automation scripts to perform common IT operations like opening tools, collecting data, or applying fixes via USB or Bluetooth.
- Keyboard acts like a portable keyboard to type reliably on any connected PC.
- Mouse allows pointer movement and clicking using the device’s controls.
- Shortcuts It is a set of keys that serve as shortcuts for tasks such as cutting, pasting, saving documents, and more—all with a single button. It is an excellent app to use in conjunction with your PC mouse.
- Settings lets you adjust brightness, language, Bluetooth, and other preferences.

Designed for ethical and consent-based support.

Contents

ReadyUSB	2
A.OS_System	2
A.Windows	3
A__Admin_And_Security	3
B__Networks	11
C_Folder_and_Files	19
D__Storage	26
E__Monitoring	28
F__External_links_tools	32
G__Nmap	34
H__App_Downloader	37

ReadyUSB

A.OS_System

With these first 4 scripts, open your PowerShell or Linux command console—with or without administrator privileges.

1.Powershell_Admin

2.Terminal_sudo_-i

3.Powershell

4.Linux_Terminal

A.Windows

A__Admin_And_Security

A.A__Admin_User_Create_Delete

5.Change_password_account. Prompts for a username and launches Windows' interactive password change for that local account. *Example: A user forgot their password — run this, type the username, and set a new one.*

6.Check_User_Admin_group. Checks if a local user exists and whether they belong to the Administrators group. *Example: You need to verify if "john" has admin rights before giving them access to a tool.*

7.Create_admin. Creates a new local user account and immediately adds it to the Administrators group. *Example: On a fresh machine, quickly create a backup admin account "ittool" with a known password.*

8.Delete_Admin_Account. Permanently deletes a local user account from the system. *Example: After a job is done, remove the temporary admin account that was created for access.*

A.B__Firewall_and_Security

9.Apps_And_Locations. Lists all installed applications from the registry, sorted by install date (newest first), with their install path. *Example: A client says "something installed yesterday broke my PC" — run this to see exactly what and where.*

10.Bluetooth_SwiftPair_Permises. Disables Bluetooth Swift Pair via registry, restarts all Bluetooth-related services, and power-cycles the Bluetooth network adapter. *Example: A client's PC keeps showing Bluetooth pairing popups — run this to disable Swift Pair and reset the stack.*

11.Close_Persistent_File. Force-deletes a file that is locked by another process. Uses the Restart Manager API to find and kill the locking process, then deletes the file. If still locked, schedules deletion on next reboot. *Example: Can't delete a DLL because "it's in use by another program" — paste the path and this kills the lock.*

12.Gpedit_Local_Group_Policy_Editor Sends a Win+R keystroke and launches gpedit.msc to open the Local Group Policy Editor directly. *Example: Quickly access GPO settings on a client machine without navigating through Control Panel or Settings.*

13.Local_Security_Policy Sends a Win+R keystroke and launches secpol.msc to open the Local Security Policy console. *Example: Jump straight into audit policies, user rights assignments, or password policy settings on a Windows machine.*

14.Services Sends a Win+R keystroke and launches services.msc to open the Windows Services management console. *Example: Quickly check, start, stop, or disable a service on a client PC during a troubleshooting session.*

15.Windows_Defender_Firewall Sends a Win+R keystroke and launches wf.msc to open the Windows Defender Firewall with Advanced Security console. *Example: Inspect inbound and outbound firewall rules on a machine without opening Windows Security settings.*

A.C__Font_Color_CMD_Powershell

16.FontColorPowershell. System-wide interactive menu to set the console color to orange or dark green (affects ConHost registry + Windows Terminal), or restore defaults. *Example: Set all consoles to orange for a client presentation, then restore defaults when done.*

17.FontColorPowershell2. Interactive theme selector: Green, Purple, Cyan, or restore default Windows blue. Applies via registry and saves permanently to the PowerShell profile. *Example: Prefer cyan over the default blue — run this once and every new PowerShell window opens in cyan.*

18.FontColorReset Downloads and executes a PowerShell script from the IT-Tool GitHub repository that resets console font colors back to their defaults. The script is saved locally to the user's Documents under the ITTOOL folder before running. *Example: After a color customization script left the terminal in an unreadable state, run this to restore the original console appearance.*

19.ResetPowershell Downloads and executes a PowerShell script from the IT-Tool GitHub repository that resets the PowerShell environment to its default configuration. The script is saved to the user's Documents under the ITTOOL folder before execution. *Example: A technician's PowerShell profile has broken aliases or conflicting settings — run this to wipe the slate clean and restore a stock environment.*

A.D__Create_Restore_Point

20.A.System_Restore_rstrui.exe Sends a Win+R keystroke and launches rstrui.exe to open the Windows System Restore wizard directly. *Example: A client's machine became unstable after a software install — launch System Restore in seconds without digging through Control Panel.*

21.B.Enable_SystemProtection Downloads and executes a PowerShell script from the IT-Tool GitHub repository that enables System Protection on the machine. The script is saved to the user's Documents under the ITTOOL folder before running. *Example: System Restore is greyed out on a client PC because protection is disabled — run this to turn it on and allow restore points to be created.*

22.C._Enable_VSS_Snapshot_Service. Sets the Volume Shadow Copy Service (VSS) to start automatically and starts it immediately. Requires admin. *Example: System Restore or backup software fails because VSS is disabled — run this to bring it back.*

23.D._Check_protection_status_on_all_units. Queries WMI to report whether System Protection (restore points) is enabled or disabled on each drive. Falls back to vssadmin if WMI is unavailable. Requires admin. *Example: Before creating a restore point, run this to confirm which drives actually have protection active.*

24.E._RestoreFreqUnlock. Sets SystemRestorePointCreationFrequency to 0 in the registry, removing Windows' built-in 24-hour cooldown between restore point creation. Requires admin. *Example: You need to create multiple restore points in the same day during a complex repair — run this first to remove the time lock.*

25.F._CheckRestoreFreq. Reads the SystemRestorePointCreationFrequency registry key and reports whether restore point creation is unlocked (0), restricted to a specific interval in minutes, or running on Windows default (key absent = 24h cooldown). *Example: After running script 24 to unlock restore points, run this to confirm the change took effect.*

26.G._Create_a_restore_point. Creates a Windows System Restore point labeled ReadyUSB_RestorePoint of type MODIFY_SETTINGS. If the 24-hour cooldown is still active, displays a tip to run script 24 first. Requires admin. *Example: Before installing a new driver or making registry changes, run this to create a safe rollback point.*

27.H._RestoreFreqLock. Sets SystemRestorePointCreationFrequency back to 1440 minutes, re-enabling Windows' default 24-hour cooldown between restore points. Requires admin. *Example: After finishing a repair session where you used script 24 to unlock frequency, run this to put the restriction back.*

A.E__Local_User_Create_Delete

28.A.New_Local_User Downloads and executes a PowerShell script from the IT-Tool GitHub repository that creates a new local user account on the machine. The script is saved to the user's Documents under the ITTOOL folder before running. Example: A client needs a secondary local account set up on a workstation without domain access — run this to create it quickly without opening Computer Management.

29.B._Delete_Local_User. Prompts for a username and permanently removes that local account using Remove-LocalUser. Requires admin. Example: A temp account created for a repair visit needs to be cleaned up after the job.

30.C._Check_User_Admin_group. Checks whether a local user account exists and reports if it belongs to the Administrators group. No admin required. Example: Verify if the account "john" has admin rights before handing a machine back to a client.

A.F__Close_All_Interface_App

31.Close_app_with_open_interface-1. Uses taskkill to force-close all running processes that have a visible window title. Broad — hits everything with a UI. Example: A machine has multiple frozen apps and Task Manager is unresponsive — run this to wipe all open windows at once.

32.Close_app_with_open_interface-2. Uses PowerShell to force-kill all processes with a visible window handle, explicitly skipping critical system processes (winlogon, csrss, lsass, dwm, etc.). Safer than script 31. Example: Same scenario as 31 but with protection against accidentally killing core system processes.

A.G__USB

A.G.A__Lock_USB

33.Check_USB_Status. Reads the USBSTOR service Start registry value and reports whether USB storage devices are currently enabled (3) or blocked (4). Example: Before plugging in a USB drive on a corporate machine, check if USB storage has been disabled by policy.

34.Lock_usb. Sets the USBSTOR service Start value to 4, preventing USB storage devices from mounting. Requires admin. Example: Quickly lock USB ports on a machine before handing it to an untrusted user.

35.Unlock_usb. Sets the USBSTOR service Start value back to 3, re-enabling USB storage devices. Requires admin. Example: After a secured session, restore USB access so the client can use their drives again.

A.G.B__USB_Security_Block

36.USB_Security_Block. Full USB hardening: disables USBSTOR (Start=4) and applies Group Policy registry keys to block installation of any new unrecognized USB devices, then forces a policy update. Requires admin. *Example: Lock down a machine before leaving it unattended — no USB drives and no new device installs allowed.*

37.USB_Security_Restore. Reverses script 36: re-enables USBSTOR (Start=3), removes the DenyUnspecified and DenyNewUSBDevices policy keys, and forces a policy update. Requires admin. *Example: After a secure session, undo the full USB block applied by script 36.*

Inside G.USB

38.Disable_USB_storage. Sets USBSTOR Start to 4 via direct registry write, disabling USB storage without touching Group Policy. Lighter version of script 34/36. Requires admin. *Example: Quick one-shot disable of USB storage without modifying device installation policies.*

39.Enable_USB_storage. Sets the USBSTOR service Start value to 3, re-enabling USB storage devices. Direct registry write without spawning a second window. Requires admin. *Example: Counterpart to script 38 — run this after finishing a secured session to restore USB access.*

40.USB_Detection. Downloads usb_monitor.py from the IT-Tool GitHub repository to the Desktop using curl.exe, then launches it immediately with Python. *Example: Deploy the USB monitor companion tool on a client machine without manually copying files.*

A.H__System_Logs

41.-MaxEvents_20. Uses Get-WinEvent to retrieve and display the last 20 entries from the Windows System event log. *Example: Quick check of recent system events after a crash or unexpected behavior.*

42.-Newest_20. Uses Get-EventLog to retrieve and display the last 20 entries from the System log. Older API than script 41 but outputs a different format — more readable for quick review. *Example: Same use as 41 but with a classic table-style output that's easier to scan at a glance.*

43.-Newest_50_Desktop_File_Download. Exports the last 50 System log entries to SystemLog.txt on the Desktop using Get-EventLog, with confirmation of the saved file path. *Example: Save a log snapshot before a risky operation, or send the file to a remote tech for review.*

44.EntryType_Error_-Newest_10. Retrieves and displays the 10 most recent Error-level entries from the Windows System event log, formatted as a table. *Example: A technician investigating an unstable workstation quickly pulls the last 10 system errors to identify hardware or driver faults.*

45.Service_control_Manager_-Newest_5. Retrieves the 5 most recent System event log entries from the Service Control Manager source, showing service start/stop and failure events. *Example: After a service crash report, a technician checks the last SCM entries to confirm which service failed and when.*

A.I__Toggle_VMwareservices

46.Toggle-VMwareservices_Download_PS1. Downloads the Toggle-VMwareServices script from the SalgadoTech GitHub repository to the user's Desktop, then launches it in a new PowerShell window. *Example: A technician on a VM host needs to quickly enable or disable VMware services without manually locating the script — this fetches and launches it in one step.*

A.L__Check_and_Logout_Active_Users

47.Check_Active_Users Types and executes the query user command in the active terminal to display all currently logged-in user sessions on the machine, including session name, state, and idle time. *Example: Before performing maintenance on a shared workstation, run this to confirm whether other users are still actively logged in.*

48.Check_Active_Users_and_Logout. Lists all active user sessions on the machine using query user, then prompts the technician to enter a Session ID and logs off that session. *Example: On a shared workstation with a ghost session blocking a profile, the technician identifies the stuck session ID and forces it off immediately.*

A.M__Telemetry

49.Check_Telemetry. Reads Windows telemetry registry keys (DataCollection, CloudContent), queries the status of DiagTrack and dmwappushservice, and lists Customer Experience-related scheduled tasks. *Example: Before handing over a client's PC, a technician audits telemetry settings to confirm data collection is disabled per company policy.*

50.Telemetry_Change. Applies or removes Windows telemetry and privacy restrictions across registry policies, services (DiagTrack, dmwappushservice), and scheduled CEIP/diagnostic tasks via an interactive menu. *Example: Before returning a client's PC, a*

technician selects option 1 to minimize data collection and then option 2 on a corporate machine that requires standard telemetry for compliance.

Inside A.Admin_And_Security

51.Apps Sends a Win+R keystroke and launches ms-settings:appsfeatures to open the Apps & Features page in Windows Settings directly. *Example: Quickly navigate to the installed applications list to uninstall or modify a program without manually opening Settings and browsing through menus.*

52.BIOS. Reboots the system immediately into BIOS/UEFI firmware settings or the Windows Recovery Environment via an interactive one-option menu. *Example: A technician needs to enable virtualization in BIOS without manually timing the key press on boot — runs this script and the system lands directly in firmware.*

53.Bit_Locker Opens Control Panel via Win+R and navigates to the BitLocker Drive Encryption section. *Example: Access BitLocker settings on a machine that lacks a touchscreen or where direct mouse navigation is not practical.*

54.Calculator Sends a Win+R keystroke and launches calc to open the Windows Calculator. *Example: Quickly pull up the calculator during a network subnetting session without leaving the current workflow.*

55.Check_ram. Queries total, used, and free physical RAM via WMI, then lists the top 20 processes sorted by working set memory with RAM, private memory, and CPU columns. *Example: A technician investigating a slow workstation runs this to instantly identify which process is consuming abnormal memory without opening Task Manager.*

56.Control_Panel Sends a Win+R keystroke and launches control to open the Windows Control Panel directly. *Example: Access legacy system settings that are not available in the modern Windows Settings app.*

57.Control_printers. Opens the Windows Printers & Scanners Control Panel applet for direct printer management. *Example: A technician needs to remove a ghost printer or set a default without navigating through Settings — launches the panel in one step.*

58.Data_Source_Administrator_64-bit Sends a Win+R keystroke and launches odbcad32 to open the ODBC Data Source Administrator (64-bit). *Example: Configure or troubleshoot a database connection on a client machine without searching for the tool through Administrative Tools.*

59.Device_Manager Sends a Win+R keystroke and launches devmgmt.msc to open Device Manager directly. *Example: Quickly check for driver errors or unknown devices on a client PC during a hardware troubleshooting session.*

60.DirectX_Diagnostic Sends a Win+R keystroke and launches dxdiag to open the DirectX Diagnostic Tool. *Example: Quickly pull up GPU, audio, and DirectX version details on a client machine during a display or performance troubleshooting session.*

61.Display Sends a Win+R keystroke and launches desk.cpl to open the Display Settings Control Panel applet directly. *Example: Access screen resolution and multi-monitor settings on a machine without navigating through the Settings app.*

62.Local_Users_and_Groups Sends a Win+R keystroke and launches lusrmgr.msc to open the Local Users and Groups management console. *Example: Quickly add, disable, or inspect local user accounts and group memberships on a workstation.*

63.Mouse_Properties Sends a Win+R keystroke and launches main.cpl to open the Mouse Properties Control Panel applet. *Example: Adjust pointer speed, button configuration, or double-click sensitivity on a client machine during a setup visit.*

64.Notepad Sends a Win+R keystroke and launches notepad to open the Windows Notepad text editor. *Example: Quickly open a blank notepad to paste and inspect a config snippet or log output during a troubleshooting session.*

66.Registry_Editor Sends a Win+R keystroke, launches regedit, and automatically confirms the UAC prompt with Alt+Y to open the Registry Editor immediately. *Example: Jump directly into the registry during a troubleshooting session without having to click through the UAC confirmation dialog.*

67.ResetPowershell. Clears all Console registry color overrides, removes Windows Terminal settings files, backs up and clears all PowerShell profiles, and resets the current session's foreground/background colors to defaults. *Example: After a botched color customization left PowerShell unreadable on a client's machine, the technician runs this to restore a clean console state without reinstalling.*

68.Restart_PC Sends a Win+R keystroke and executes shutdown /r /t 0 to immediately restart the machine with zero delay. *Example: Apply a pending driver or system update that requires a reboot without touching the Start menu.*

69.Restore_Service_Key. Recreates all registry values for the WudfSvc (Windows Driver Foundation) service key and its Parameters subkey using reg add, restoring the service to

its default configuration. *Example: After a malware removal or manual registry cleanup left WudfSvc broken and USB devices failing, a technician runs this to restore the service without reinstalling Windows.*

70.Shutdown_PC Sends a Win+R keystroke and executes shutdown -s -t 0 to immediately power off the machine with zero delay. *Example: Shut down a client workstation instantly at the end of a service visit without navigating the Start menu.*

71.Sound_Panel Sends a Win+R keystroke and launches mmsys.cpl to open the classic Sound Control Panel applet. *Example: Quickly access playback devices, recording devices, and audio levels on a client machine without going through Settings.*

72.System_Configuration Sends a Win+R keystroke and launches msconfig to open the System Configuration utility. *Example: Quickly access startup options, boot settings, or disable startup services during a performance troubleshooting session.*

73.System_ImageWindows_Repair. Runs sfc /scannow followed by DISM /Online /Cleanup-Image /RestoreHealth sequentially to scan and repair corrupted Windows system files and the component store. *Example: A client reports random crashes and app failures — the technician runs this to repair the OS image in one step before escalating to a reinstall.*

74.System_properties. Opens the Windows System Properties dialog (sysdm.cpl) for quick access to computer name, domain, hardware, and advanced system settings. *Example: A technician needs to rename a workstation or check the domain membership without navigating through the Settings app.*

76.Taskkill. Lists all running processes sorted alphabetically with an index, then kills the process selected by the technician by number using Stop-Process -Force. *Example: A frozen application isn't showing in Task Manager's GUI — the technician uses this to locate and force-kill it by index in seconds.*

B__Networks

B.A.FirewallRules_universal_port

B.A.A__Ports1

77.Close_a_port. Finds the process or Windows service listening on a specified TCP/UDP port and stops it — disabling the service if applicable — then confirms whether the port is closed. *Example: A post-incident audit finds an unexpected listener on port 4444 — the technician runs this to identify and kill it immediately without using netstat manually.*

78.Open_a_Port. Finds the process or service associated with a specified port and re-enables it by setting the service startup to automatic and starting it; if no active listener

exists, scans all disabled services and re-enables them. *Example: After running the port-close script on RDP (3389), a technician uses this to restore the service listener without knowing the service name.*

B.A.B__Ports2

79.Close_a_port. Removes any existing Allow firewall rules for a specified port, then creates three inbound Block rules covering TCP, UDP, and Any protocol to ensure the port is fully blocked at the firewall level. *Example: A technician discovers an unexpected open port during a security audit and blocks it immediately via firewall without touching the underlying service.*

80.Open_a_Port. Removes existing Block firewall rules for a specified port and creates inbound Allow rules for TCP and UDP, then displays the resulting firewall rule table for verification. *Example: A client's application stopped working after a security lockdown — the technician opens the required port in seconds and confirms the new Allow rules are active.*

Inside A.FirewallRules_universal_port

81.Check_acssess_to_a_local_port. Runs Test-NetConnection against localhost on a specified port and reports whether the TCP connection succeeds, indicating if the port is actively accessible. *Example: After adjusting firewall rules, a technician quickly confirms that port 443 responds on the local machine before testing from an external client.*

82.Check_if_a_port_has_a_rule. Queries all enabled Windows Firewall rules and lists any that reference the specified port as a local or remote port, showing action, direction, profile, protocol, and port columns. *Example: Before making firewall changes, a technician checks if port 3389 already has conflicting rules that could interfere with a new Allow policy.*

83.Set_a_port_to_listen. Opens a temporary TCP listener on a specified port using TcpListener, waits for a single incoming connection, reports the remote endpoint, then stops the listener and exits cleanly. *Example: A technician tests whether a client machine can reach a specific port on a server by having the server run this script and connecting from the client.*

B.B__Port3389_REMOTE_DESKTOP

B.B.A__NetFirewallRules for 3389

84.Create_the_rule_to_allow_port_3389_(RDP). Creates a Windows Firewall inbound Allow rule named "Allow RDP" permitting TCP traffic on port 3389. *Example: RDP is enabled on a*

machine but the firewall is blocking connections — the technician runs this to add the missing Allow rule without opening the Firewall GUI.

85.Remove_the_rule_to_allow_port_3389_(RDP). Removes the Windows Firewall inbound rule named "Allow RDP" that permits TCP traffic on port 3389. *Example: After finishing a remote support session, a technician removes the custom RDP Allow rule to restore the machine's locked-down firewall posture.*

B.B.B__Open_close_port_3389_Opt1

86.Activate_3389_port. Sets the fDenyTSConnections registry value to 0 in the Terminal Server key, enabling Remote Desktop connections on the machine. *Example: A technician needs to enable RDP on a client PC remotely via a script without navigating through System Properties.*

87.Close_3389_port. Sets the fDenyTSConnections registry value to 1 in the Terminal Server key, disabling Remote Desktop connections on the machine. *Example: After completing remote support, a technician disables RDP via script to prevent unauthorized remote access going forward.*

B.B.C__Open_close_port_3389_Opt2

88.Close_3389_port. Performs a complete RDP lockdown: sets fDenyTSConnections to 1, disables the Remote Desktop firewall group, removes all Allow rules for port 3389, creates TCP/UDP/Any Block rules, and stops TermService. *Example: After a remote support session on a sensitive machine, the technician runs this to fully close RDP at registry, firewall, and service level in one step.*

89.Open_3389_port. Fully enables RDP by setting registry keys, configuring NLA, starting TermService on Automatic, adding the current user to Remote Desktop Users, removing Block rules, enabling the Remote Desktop firewall group, creating Allow rules, and verifying port 3389 responds. *Example: A technician needs to remotely access a client PC that had RDP fully locked down — this restores every layer needed for a successful connection.*

B.C__Bluetooth

90.Bluetooth_Off. Disables all active Bluetooth PnP devices matching the Bluetooth class GUID and stops the Bluetooth Support Service (bthserv). *Example: On a secured workstation where wireless peripherals are not permitted, a technician disables Bluetooth at the hardware and service level without uninstalling drivers.*

91.Bluetooth_On. Re-enables all disabled Bluetooth PnP devices matching the Bluetooth class GUID and starts the Bluetooth Support Service (bthserv). *Example: After a policy*

review allows Bluetooth peripherals again, a technician re-enables Bluetooth hardware and service in one run.

92.Bluetooth_SwiftPair_Permises. Disables Swift Pair via registry, stops and restarts all Bluetooth-related services (bthserv, hidserv, DeviceAssociationService, DeviceInstall, BluetoothUserService), and resets the Bluetooth network adapter with a disable/enable cycle. *Example: A user's PC is showing unsolicited Swift Pair popups from nearby devices — the technician disables the feature and resets the Bluetooth stack to clear the behavior.*

B.D__SSH

B.D.A__PC_Control

93.SSH_Connection Types an SSH command into the active terminal that prompts the technician interactively for a username and an IP address or hostname, then builds and executes the connection string automatically. *Example: SSH into a remote server or network device without remembering the exact syntax — the script asks for credentials and connects in one step.*

B.D.B__Remote_PC

94.A.Enable_SSH_Server. Queries the Windows Optional Features store to report whether the OpenSSH Server capability is installed or only available for installation. *Example: Before attempting to start SSH on a fresh workstation, a technician runs this to confirm the capability is present without opening Settings.*

95.B.Activate_and_start_SSH. Installs the OpenSSH Server Windows capability if not already installed, sets the sshd service to Automatic startup, and starts it immediately. *Example: A technician needs SSH access to a client machine and runs this to install, configure, and start the SSH server in a single step.*

96.C.Change_network__public_to_private_. Displays all current network connection profiles and changes any interface categorized as Public to Private, then shows the updated profile table. *Example: SSH or RDP is failing because the network profile is set to Public — the technician runs this to switch it to Private so the services become reachable.*

97.D.Enable_Ping_rule. Enables the built-in Windows Firewall inbound rule for ICMPv4 Echo Requests, allowing the machine to respond to ping from other hosts. *Example: A technician can't ping a client workstation during troubleshooting — this enables the ICMP rule instantly without opening the Firewall GUI.*

98.E.Check_SSH_is_Listening Types and executes netstat -ano | findstr ":22" in the active terminal to check whether port 22 is open and actively listening on the machine. *Example:*

Verify that an SSH service is running and bound to port 22 before attempting a remote connection to the machine.

Inside B.Networks

99.ARP Types and executes `arp -a` in the active terminal to display the full ARP table, listing all known IP-to-MAC address mappings cached by the machine. *Example: Quickly identify devices on the local network segment or verify that a specific host has been reached recently.*

100.Available_WiFi_Signals Types and executes `netsh wlan show networks mode=bssid interface="Wi-Fi"` in the active terminal to list all visible wireless networks along with their BSSID, signal strength, channel, and authentication type. *Example: Audit the RF environment at a client site to identify nearby networks, check for rogue APs, or troubleshoot Wi-Fi connectivity issues.*

101.BackDoors_Risk. Performs a host-based backdoor sweep covering ARP spoofing detection, suspicious listening ports, outbound connections to known C2 ports, hidden scheduled tasks, script-based autoruns, non-standard auto-start services, and overly permissive firewall rules; exports all findings to JSON and CSV on the Desktop. *Example: After a security incident alert, a technician runs this on a suspect workstation to get a rapid structured report of backdoor indicators before escalating to forensics.*

102.Clear_the_DNS_Cache Types and executes `ipconfig /flushdns` in the active terminal to purge the local DNS resolver cache immediately. *Example: A client is hitting a stale DNS entry after a server migration — flush the cache to force fresh lookups without restarting the machine.*

103.Firewall Sends a Win+R keystroke and launches `control firewall.cpl` to open the Windows Firewall settings through the classic Control Panel applet. *Example: Quickly check or toggle firewall status on a client machine without navigating through the Windows Security app.*

104.Internet_Properties Sends a Win+R keystroke and launches `inetcpl.cpl` to open the Internet Properties dialog. *Example: Access proxy settings, trusted sites, or security zones on a machine during a connectivity troubleshooting session.*

105.IP_Easy_By_SalgadoTech Opens IP-Easy, a web-based IPv4 planning toolkit developed by Salgado Technologies, directly in the default browser. The tool auto-detects the machine's public IP, ISP, and approximate location, and allows the technician to analyze any IPv4 address to obtain class info, binary representation, subnet table (/32 to /0), and a full VLSM Subnet Designer that allocates router-to-router /31 links and sizes

LANs with growth margin. Results can be exported as PDF or copied per row. Example: On a site visit, pull up IP-Easy to plan a multi-LAN network from scratch, assign gateway, modem, and switch addresses following a consistent IP policy, and export the design as a PDF for the client.

106.IP_Identifique Downloads and executes a PowerShell script from the IT-Tool GitHub repository that identifies and displays detailed IP information for the machine. The script is saved to the user's Documents under the ITTOOL folder and launched in a new persistent PowerShell window so output remains visible after execution. *Example: Get a clear, formatted view of all network adapter IPs on a client machine without manually parsing ipconfig output.*

107.IP_Private_And_Public. Lists all non-loopback, non-APIPA IPv4 addresses per network adapter, then queries ipify.org to display the current public IP of the machine. *Example: On a multi-homed workstation, a technician quickly identifies which private IP is on which adapter and confirms the public-facing IP for remote access configuration.*

108.ipconfig Types and executes ipconfig in the active terminal to display the basic IP configuration for all network adapters on the machine. *Example: Quickly check the IP address, subnet mask, and default gateway on a client machine at the start of a network troubleshooting session.*

109.ipconfig_all Types and executes ipconfig /all in the active terminal to display the full network adapter configuration including MAC addresses, DNS servers, DHCP status, and lease information. *Example: Pull a complete network profile from a client machine in one command to diagnose DHCP, DNS, or adapter issues.*

110.IPv4-classic-config. Opens the Windows Network Connections Control Panel (ncpa.cpl) for direct access to classic adapter IPv4 settings. *Example: A technician needs to set a static IP on a client machine and opens the adapter properties directly without navigating through Settings.*

111.IPv4_Manual_Settings Opens the Windows Settings Wi-Fi page and navigates to the IPv4 manual configuration section to allow switching between DHCP and static IP assignment. *Example: Change a laptop from DHCP to a static IP on a client network without manually digging through Settings menus. Note: run only once per boot session to avoid Settings navigation errors.*

112.IPv6_Interfaces Executes netsh interface ipv6 show interfaces to list all network interfaces and their IPv6 configuration details. *Example: Verify which adapters have IPv6 enabled and check their link-local addresses during a network audit.*

113.Listening_Network_Connections_-ab Executes netstat -ab to display all active network connections along with the executable responsible for each one. *Example: Identify which application is holding open a suspicious network connection on a client machine.*

114.Listening_Network_Connections_Ports_ID_Process Executes netstat -ano to list all active connections and listening ports along with the Process ID (PID) associated with each. *Example: Cross-reference a suspicious port with Task Manager to identify the process behind it.*

115.Listening_Network_Connections_Ports Executes netstat -an to display all active connections and listening ports in numerical form without resolving hostnames. *Example: Get a fast, clean view of all open ports on a machine without DNS lookup delays.*

116.MAC_and_Adapters Executes getmac /v /fo list to display each network adapter's MAC address, connection name, and transport type in a readable list format. *Example: Retrieve the MAC address of a specific adapter on a client machine for network registration or troubleshooting purposes.*

117.Network_Connections Opens the classic Network Connections panel via ncpa.cpl for direct access to all network adapters. *Example: Quickly view, enable, disable, or configure any network adapter on the machine.*

118.Network_Band_2.4_or_5GHz Executes netsh wlan show networks mode=bssid to list all visible wireless networks with their BSSID and signal details. *Example: Determine whether nearby access points are broadcasting on 2.4GHz or 5GHz during a wireless troubleshooting or site survey.*

119.Network_Settings Opens the Windows Network & Internet settings page directly via ms-settings:network. *Example: Quickly access Wi-Fi, Ethernet, VPN, and proxy settings on a client machine without navigating through the full Settings menu.*

120.OpenConnections. Collects all established TCP connections, maps each to its process name and primary network adapter, saves the list as NetReport.txt on the Desktop, and opens it in Notepad. *Example: A technician suspects unauthorized connections on a workstation and generates a quick plain-text report of all active sessions by process.*

121.OpenConnections_WithPorts. Same as 120 but includes local and remote port numbers in each connection entry, providing full socket-level visibility into established TCP sessions. *Example: During a security review, a technician needs to see exactly which local ports are communicating with which remote endpoints and the owning process for each.*

122.OpenPort_PublicOrPrivate. Lists all TCP ports currently in Listen state, sorted by port number, showing the local address and the name of the owning process. *Example: A*

technician checks which services are actively listening on a workstation before opening a firewall rule.

123.Ping. Prompts for an IP address or hostname and runs a standard ping test, displaying round-trip times and packet loss. *Example: A technician quickly verifies network reachability to a server or device on-site.*

124.Remote_Desktop_Connections Opens the Windows Remote Desktop Connection client via mstsc. *Example: Quickly launch an RDP session to a remote machine without searching for the app through the Start menu.*

125.Remote_ports_activity. Displays all established TCP connections to remote addresses (excluding loopback), showing local/remote ports, state, PID, and process name. *Example: A technician audits active outbound connections on a workstation to detect unexpected external communication.*

126.Show_WiFi_Driver Executes netsh wlan show drivers to display detailed information about the installed wireless adapter driver, including version, supported bands, and 802.11 protocols. *Example: Verify whether a Wi-Fi adapter supports 5GHz or check the driver version before and after a driver update on a client machine.*

127.Simulated_Listen_Port Prompts the technician for a port number and then binds a TCP listener to that port, keeping it open indefinitely. *Example: Simulate a service listening on a specific port to test firewall rules or verify that a remote machine can reach the port before deploying the actual application.*

128.Tracert. Prompts for an IP address or hostname and runs a traceroute, mapping each hop in the network path to the destination. *Example: A technician diagnoses where a connection is failing or experiencing high latency between a client machine and a remote server.*

129.What_process_use_a_port. Prompts for a TCP port number and identifies the process currently using it, displaying the PID, process name, CPU usage, and start time. *Example: A technician determines which application is occupying port 8080 before deploying a new service.*

130.Wi-Fi_Off. Detects all active Wi-Fi network adapters matching common wireless naming patterns and disables them without confirmation. *Example: A technician isolates a workstation from wireless networks during a security incident or troubleshooting session.*

131.Wi-Fi_On. Detects all disabled Wi-Fi network adapters matching common wireless naming patterns and re-enables them without confirmation. *Example: A technician*

restores wireless connectivity on a workstation after completing a wired-only maintenance task.

132.WiFi_Password Opens the Windows Wi-Fi Settings page and navigates into the properties of the first available network to reach the section where the saved password can be viewed. *Example: Retrieve the saved Wi-Fi password on a client machine without opening PowerShell or Command Prompt. Note: run only once per boot session to avoid Settings navigation errors.*

C_Folder_and_Files

C.A_Robocopy

133.A._SAME_PC_FILES-FIRSTTIME. Prompts for a source and destination folder path on the same machine, then uses Robocopy to perform a full recursive copy including all subfolders. *Example: A technician migrates a user's data folder to a new drive partition before reimaging the original.*

134.B._LOCAL_A_EXTERNO-FIRST-TIME. Prompts for a local source folder and a network share destination, then uses Robocopy to copy all files and subfolders to the remote location. *Example: A technician backs up a workstation's documents folder to a NAS or server share before performing a system restore.*

135.C._EXTERNO_A_LOCAL-FIRST-TIME. Prompts for a network share source and a local destination folder, then uses Robocopy to pull all files and subfolders from the remote location. *Example: A technician restores a user's data from a network backup share onto a freshly imaged workstation.*

136.D._SAME_PC_FILES-E. Prompts for source and destination paths on the same machine and copies all files and subfolders using Robocopy /E, preserving the directory structure and skipping files that already exist at the destination. *Example: A technician copies a user profile folder to a secondary drive without overwriting files already transferred in a previous pass.*

137.E._LOCAL_A_EXTERNO_E. Prompts for a local source path and a network share destination, then copies all files and subfolders using Robocopy /E, skipping files that already exist at the destination. *Example: A technician continues an interrupted backup to a NAS without re-sending files already copied.*

138.F._EXTERNO_A_LOCAL_E. Prompts for a network share source and a local destination path, then copies all files and subfolders using Robocopy /E, skipping files that already exist at the destination. *Example: A technician resumes pulling files from a server share onto a workstation after a network interruption.*

139.G._SAME_PC_FILES-MIR. Prompts for source and destination paths on the same machine and performs a full mirror using Robocopy /MIR, including all subfolders and deleting any files in the destination that no longer exist in the source. *Example: A technician keeps a backup drive in exact sync with the primary drive, removing stale files automatically.*

140.H._LOCAL_A_EXTERNO_MIR. Prompts for a local source path and a network share destination, then performs a full mirror using Robocopy /MIR, deleting files at the destination that no longer exist in the source. *Example: A technician synchronizes a workstation's project folder to a server share, ensuring the remote copy is an exact replica.*

141.I._EXTERNO_A_LOCAL_MIR. Prompts for a network share source and a local destination path, then performs a full mirror using Robocopy /MIR, deleting files at the local destination that no longer exist in the network source. *Example: A technician keeps a local working copy in exact sync with a server share, automatically removing files deleted upstream.*

C.B__Modify attributes of all files in a folder

C.B.A__Files

142.A._Ativate_attributes_from_a_file. Prompts for a file path and sets the Read-Only and Hidden attributes on that file using attrib +R +H. *Example: A technician protects a configuration file from accidental edits and hides it from standard folder views.*

143.B._Remove_attributes_from_a_file. Prompts for a file path and removes the Read-Only and Hidden attributes from that file using attrib -R -H. *Example: A technician restores access to a protected or hidden file before editing or deleting it.*

C.B.B__Folders and subfolders

144.A._Activate_attributes_folder_and_sub_folders. Prompts for a folder path and applies the Read-Only and Hidden attributes to all files in that folder and all subfolders recursively using attrib +R +H /S /D. *Example: A technician locks down an entire directory tree before handing a machine back to a client.*

145.B._Remove_attributes_folder_and_sub_folders_txt. Prompts for a folder path and removes the Read-Only and Hidden attributes from all files in that folder and all subfolders recursively using attrib -R -H /S /D. *Example: A technician clears protective attributes from an entire directory tree to allow bulk editing or deletion.*

146.C._Activate__Read_Only_folder_and_sub_folders. Prompts for a folder path and sets the Read-Only attribute on all files in that folder and all subfolders recursively using attrib

+R /S /D, without affecting the Hidden attribute. *Example: A technician write-protects an entire documentation folder before sharing it with a client.*

147.D._Activate__Hidden_folder_and_sub_folders. Prompts for a folder path and sets the Hidden attribute on all files in that folder and all subfolders recursively using attrib +H /S /D, without affecting the Read-Only attribute. *Example: A technician hides a sensitive folder tree from standard Explorer view without locking file access.*

C.C__Numbering

148.CapitalLettersOnFiles. Prompts for a folder path and a starting letter, then renames all files in that folder by prepending an alphabetical prefix (A., B., C., ... AA., AB., ...), stripping any existing letter prefix first and resolving name collisions automatically. *Example: A technician organizes a set of client documents into a labeled alphabetical sequence starting at a specific letter.*

149.DeleteLettersOnFile. Prompts for a folder path and removes leading letter prefixes (e.g. A. , BC.) from all filenames in that folder, resolving any name collisions automatically. *Example: A technician strips alphabetical labels from a renamed file set to restore clean, undecorated filenames.*

150.DeleteNumbersOnFile. Prompts for a folder path and removes leading numeric prefixes (e.g. 1., 23.) from all filenames in that folder, trimming whitespace and resolving collisions automatically. *Example: A technician cleans up numbered exports from a system that prepends sequence numbers to every filename.*

151.LettersOnFiles. Prompts for a folder path, a starting lowercase letter, and a separator character, then renames all files by prepending a sequential lowercase alphabetical prefix (a., b., ... aa., ab., ...), stripping any existing letter prefix first and resolving collisions automatically. *Example: A technician relabels a set of training documents with lowercase letter sequence using a dash separator instead of a period.*

152.NumbersOnFiles. Prompts for a folder path and a starting number, then renames all files in that folder by prepending a sequential numeric prefix (e.g. 1.filename, 2.filename) sorted alphabetically. *Example: A technician sequences a batch of client report files numerically before importing them into a document management system.*

153.A._ZipFiles_from_a_folder. Prompts for a source and destination folder, then compresses each file in the source into its own individual ZIP file named after the original file, creating the destination folder if it does not exist. *Example: A technician packages each log file from a server into separate ZIPs for individual distribution to different teams.*

C.D__ZIP_Options

153.A._ZipFiles_from_a_folder. Prompts for a source and destination folder, then compresses each file in the source into its own individual ZIP file named after the original file, creating the destination folder if it does not exist. *Example: A technician packages each log file from a server into separate ZIPs for individual distribution to different teams.*

154.B._Zip_all_content_from_and_file_in_one_zip. Prompts for a source folder and an output ZIP path, then compresses all files in the source folder into a single ZIP archive using Compress-Archive. *Example: A technician bundles an entire client folder into one ZIP file before uploading it to a remote support portal.*

155.C._Zip_Files,_folders_and_sub_folders. Prompts for a source and destination folder, then compresses each file and each subfolder in the source into separate ZIP files in the destination, creating the destination folder if needed. *Example: A technician archives both individual files and project subfolders from a workstation into separate ZIPs for organized storage.*

C.E__Share-folders

156_A__Create_a_shared_folder. Creates a network share for a specified local folder and grants full access to a named user via net share. *Example: A technician needs to quickly share a folder on a workstation so a remote colleague can access files over the LAN without setting up a VPN.*

157_B__Delete_a_shared_folder. Removes an active network share by name using net share /delete, leaving the underlying folder intact. *Example: A technician decommissions a temporary file share after a data migration is complete.*

158_C__Create_a_shared_folder-full_access. Creates a network share for a specified local folder and grants full access to the Everyone group, making it accessible to any user on the network. *Example: A technician sets up a quick open drop-zone folder during an on-site data collection session.*

159_D__Zip_Files__folders_and_sub_folders. Compresses a source folder including all files and subfolders into a ZIP archive at a user-specified destination using .NET's ZipFile.CreateFromDirectory. *Example: A technician archives a client's project directory before performing a system migration.*

160_E__Delete_a_shared_folder-full_access. Removes an active network share (previously created with Everyone full access) by name using net share /delete, without deleting the underlying folder. *Example: A technician revokes open network access to a shared folder after a temporary Everyone-accessible share is no longer needed.*

161.F__Create_shared_Folder_Select_User. Creates a network share for a specified folder and grants full access to either an existing domain/local user or a newly created local user, with optional Everyone read access and NTFS Modify permissions applied to the folder. *Example: A technician sets up a shared folder on a client's workstation and creates a dedicated local account for a contractor to access it over the LAN.*

162.G_Map_network_drive. Maps a network UNC path to a specified drive letter persistently using net use, removing any existing mapping or stale registry entry on that letter first, and opens the drive in Explorer on success. *Example: A technician maps a server share to drive Z: on a workstation so it reconnects automatically at every login.*

C.F__NTFS

163.DisableAccessTimeUpd Executes fsutil behavior set disablelastaccess 1 to stop Windows from updating the last access timestamp on files and folders. *Example: Reduce unnecessary disk writes on an SSD or improve file system performance on a busy server by disabling last access time tracking.*

164.EnableAccessTimeUpdate Executes fsutil behavior set disablelastaccess 0 to re-enable Windows last access timestamp updates on files and folders. *Example: Re-enable access time tracking on a machine where audit or compliance requirements depend on accurate file access records.*

165.SystemManagedAccessTime Executes fsutil behavior set disablelastaccess 2 to hand control of last access timestamp updates back to Windows, letting the OS decide based on its own internal policy. *Example: Restore the default OS-managed behavior on a machine after manual access time settings were applied during a previous tuning session.*

C.G_Index_Tree

166.A_Download__PyDocument. Downloads the Folder_tree.py script from the SalgadoTech GitHub repository and saves it to the current user's Desktop. *Example: A technician quickly deploys the folder tree generator to a client PC before running a directory audit.*

167.B_Run_PyDocument. Verifies that Folder_tree.py exists on the Desktop and executes it using Python, with feedback on success or failure. *Example: A technician runs the folder tree generator after downloading it with script 166, generating a structured directory report.*

Inside C_Folder_and_Files

168.Analyze_and_Repair_System_Files_SFC_Scan Executes sfc /scannow to scan all protected Windows system files and automatically repair any corrupted or missing ones.

Example: Run a system file integrity check on a client machine that is experiencing random crashes or unexpected application errors.

169.AppData_Folder Opens the current user's AppData\Roaming folder directly via the %appdata% environment variable. *Example: Quickly access application configuration files or clear a misbehaving app's local data without navigating through hidden folders manually.*

170.Credentials_Manager Executes control.exe keymgr.dll to open the Windows Credential Manager directly. *Example: View, edit, or remove saved network passwords and Windows credentials on a client machine during an authentication troubleshooting session.*

171.Delete_Repeat_Files_And_Folder. Downloads Delete_Repeat_Files_And_Folder.ps1 from the SalgadoTech GitHub repository to the Desktop using curl.exe and executes it directly. *Example: A technician deploys and runs the duplicate file cleaner on a client PC in one step without manual downloads.*

172.Empty_content_any_folder. Clears all files and subfolders from a specified folder without deleting the folder itself, using Remove-Item with a Robocopy mirror fallback for locked or protected items. *Example: A technician empties a Windows temp or cache folder on a client PC that contains locked files that standard deletion can't remove.*

173.Empty_Temp_Folder Executes takeown recursively over the user's TEMP folder to take ownership of all files and force their deletion, bypassing permission restrictions that normally prevent cleanup. *Example: Clear a TEMP folder that is locked by permission errors on a client machine where standard disk cleanup tools failed to remove stubborn temporary files.*

174.Empty_trash. Empties the Windows Recycle Bin silently using Clear-RecycleBin -Force without prompting for confirmation. *Example: A technician clears the Recycle Bin as part of a disk cleanup routine before imaging a workstation.*

175.Encrypt_Decrypt_Files. Encrypts or decrypts a single file using either EFS (Windows Encrypting File System via cipher) or CMS certificate-based encryption (Protect-CmsMessage / Unprotect-CmsMessage), auto-generating a self-signed certificate if none exists. *Example: A technician encrypts a sensitive report file on a shared workstation using CMS before handing it off, so only the certificate holder can decrypt it.*

176.File_encryption. Opens the Windows Certificate Manager (certmgr.msc) so the user can view, export, or manage EFS and encryption certificates. *Example: A technician opens the certificate store to back up or verify the EFS recovery certificate on a user's machine before a system migration.*

177.File_Explorer_Options Opens the File Explorer Options (Folder Options) Control Panel applet via control folders. *Example: Quickly toggle hidden files visibility, disable thumbnail previews, or change how folders open on a client machine without navigating through the View menu.*

178.Hash_Maker. Computes and displays the cryptographic hash of a specified file using a user-selected algorithm (MD5, SHA1, SHA256, SHA384, or SHA512). *Example: A technician verifies the integrity of a downloaded driver or ISO by comparing its SHA256 hash against the vendor's published value.*

179.Hide_hidden_files_and_folders. Sets the Windows Explorer registry value to hide hidden files and folders for the current user (Hidden=2), reverting any previous "show hidden" configuration. *Example: A technician restores the default Explorer visibility setting after finishing a diagnostic session where hidden files were temporarily shown.*

180.Localhost_Folder Opens the local machine's shared resources via the \\localhost UNC path in File Explorer. *Example: Browse all active network shares on the local machine to verify which folders are being shared and check their accessibility during a network audit.*

181.Number_files_with_path. Adds a sequential numeric prefix (1., 2., 3....) to all files in a specified folder, sorted alphabetically before numbering. *Example: A technician organizes a client's unordered photo or document folder by prepending numbers to enforce a stable sort order.*

182.Open_Disk_C Opens the root of the C: drive in File Explorer directly. *Example: Quickly browse the system drive on a client machine without navigating through This PC.*

183.Program_Files_Folder Opens the Program Files folder via the %programfiles% environment variable in File Explorer. *Example: Quickly verify whether a specific application is installed or browse installed software directories on a client machine.*

184.Share_a_Folder Runs a PowerShell script that interactively shares a folder over the network. It asks for the folder path, share name, and whether to assign access to an existing user or create a new local one. It enables the Server service, opens the required SMB firewall rules, creates the SMB share, applies NTFS Modify permissions to the specified account, and optionally grants Everyone read access. The UNC path of the new share is displayed upon completion. *Example: Share a specific folder on a client machine for a remote colleague in minutes, creating a dedicated local user with the correct permissions in a single automated flow.*

185.Shared_Folders Opens the Shared Folders management console via fsmgmt.msc to display all active shares, open sessions, and open files on the machine. *Example: Audit which folders are currently shared on a client machine and close any open sessions before performing maintenance.*

186_Show_hidden_files_and_folders. Sets the Windows Explorer registry value to make hidden files and folders visible for the current user (Hidden=1). *Example: A technician enables hidden file visibility to locate AppData or system configuration files during a troubleshooting session.*

187.Startup_Folder Opens the current user's Startup folder via shell:startup in File Explorer. *Example: Add, remove, or inspect programs that launch automatically when the current user logs into Windows.*

188.Temp_Folder Opens the current user's TEMP folder via the %temp% environment variable in File Explorer. *Example: Manually inspect or clear temporary files on a client machine during a storage cleanup or troubleshooting session.*

189_User_folder. Opens the current user's profile folder (%USERPROFILE%) in Windows Explorer. *Example: A technician quickly navigates to a user's profile directory to inspect or back up personal folders such as Desktop, Documents, and AppData.*

190_Users_folder. Opens the C:\Users folder in Windows Explorer to browse all user profiles present on the machine. *Example: A technician checks which user accounts have active profiles on a workstation before performing a cleanup or account audit.*

D__Storage

D.A__Create_Volume_RAID_0_3_5

D.A.A.__Fast Process

191_CreateVolume. Wipes user-selected disks to RAW, resets them to pool-ready state, then interactively creates a Simple, Spanned, or RAID (0/1/5) volume using diskpart or Windows Storage Spaces. *Example: A technician deploys three new drives in a workstation and uses this script to prep them and set up a RAID 5 volume in one session.*

D.A.B__Step_Process

192_A__Disk-Raw_PoolReady. Clears partitions and data from selected disks (RAW), resets physical disk usage to AutoSelect, and displays CanPool status — preparing them for use with Windows Storage Spaces. *Example: A technician runs this before creating a storage pool to confirm all target disks show CanPool=True.*

193_B_StartStorageSpace. Starts the Windows Storage Spaces service (StorSvc), which must be running before any Storage Pool or virtual disk operations can be performed.

Example: A technician runs this as the first step before executing the pool or RAID creation scripts if StorSvc is stopped.

194_C_SIMPLE_VOLUME. Initializes a single non-system disk as GPT and formats it as a simple NTFS volume with a user-specified drive letter and label using a diskpart script.

Example: A technician quickly formats a new secondary drive on a workstation and assigns it drive letter E: with label DATA.

195_D_SPANNED_VOLUME. Converts two or more disks to dynamic GPT and combines them into a single spanned NTFS volume using a diskpart script, assigning a user-defined drive letter and label. *Example: A technician merges two undersized drives into one logical volume to provide a single large storage space for a client's archive.*

196_E_Raid_0_1_5. Creates a RAID 0, 1, or 5 volume using Windows Storage Spaces with a user-defined storage pool name, virtual disk name, and volume label. *Example: A technician sets up a RAID 5 array on three poolable drives to provide redundant storage on a workstation.*

Inside D.A__Create_Volume_RAID_0_3_5

197_DeleteSimpleAndRAIDVolume. Removes all virtual disks and non-primordial storage pools, clears any Spaces-type disks, then wipes user-specified disks to RAW — skipping System and Boot disks automatically. *Example: A technician tears down a Storage Spaces RAID volume and prepares the drives for a fresh configuration.*

198_DeleteSpannedVolume. Wipes selected dynamic disks back to RAW using a diskpart clean script, removing all spanned volume data and partition structures. *Example: A technician decommissions a spanned volume and reclaims the individual drives for independent use.*

Inside D__Storage

199_Check_free_space__universal_with__drive_. Reports total, free, and available disk space for a specified drive letter using fsutil volume diskfree. *Example: A technician quickly checks remaining capacity on drive D: before copying a large backup to it.*

200.Check_Mount_Points Executes fsutil volume list to display all mounted volumes and their associated drive letters or mount points on the machine. *Example: Verify which volumes are currently mounted and identify any unmapped or orphaned mount points during a disk audit.*

201.Disk_Cleanup Opens the Windows Disk Cleanup utility via cleanmgr. *Example: Quickly launch a guided cleanup of temporary files, system cache, and Recycle Bin contents on a client machine to free up disk space.*

202.Disk_Manager Opens the Windows Disk Management console via diskmgmt.msc. *Example: View, partition, format, or assign drive letters to disks on a client machine without using the command line.*

203.FormatDisk. Displays all connected disks, then interactively formats user-selected disks as GPT NTFS volumes with System/Boot protection, requiring typed confirmation before proceeding, and an additional override phrase for disks containing EFI or Recovery partitions. *Example: A technician formats several secondary drives on a client workstation in one session, with the safety check preventing accidental wipe of the OS disk.*

204_View_drive_info__universal_with__drive_. Displays volume and filesystem details for a specified drive letter using fsutil fsinfo volumeinfo, including filesystem type, serial number, and feature flags. *Example: A technician checks whether a client's D: drive is formatted as NTFS and verifies its volume serial number before a migration.*

205.View_File_System_Type Executes fsutil fsinfo drives to list all drives currently recognized by the system. *Example: Quickly confirm which drive letters are active on a machine before running disk-specific commands during a storage troubleshooting session.*

E__Monitoring

206.About_Windows Opens the Windows version dialog via winver, displaying the exact Windows edition, build number, and update version installed on the machine. *Example: Quickly confirm the Windows build on a client machine before applying a patch or checking compatibility with a software requirement.*

207.Battery_Report Executes powercfg /batteryreport and saves the output as an HTML file directly to the user's Desktop. *Example: Generate a full battery health report on a client laptop to assess capacity degradation and estimated runtime before recommending a battery replacement.*

208_Check_USB_storage_status. Reads the USBSTOR registry key and reports whether USB mass storage is currently enabled (Start=3) or disabled (Start=4) on the system. *Example: A technician confirms USB storage policy status on a workstation before applying a security lockdown.*

209_Check_HID_Dispositives. Lists all present HID keyboard and mouse devices with their Vendor ID (VID) and Product ID (PID) extracted from PnP instance IDs. *Example: A*

technician identifies the VID/PID of an unrecognized input device to look up its driver or verify its origin.

210_Check_VID_PID_Dispositives. Lists all present PnP devices that expose a VID and PID in their instance ID, showing device name, Vendor ID, and Product ID. *Example: A technician audits all connected USB and HID hardware on a workstation to identify unauthorized or unknown devices.*

211_Cpu_usage. Reads the Processor(_Total)\% Processor Time performance counter and displays the current total CPU usage percentage. *Example: A technician does a quick CPU load check on a sluggish workstation before pulling up Task Manager.*

212.Date_Time Executes date /T && time /T to display the current system date and time in the active terminal. *Example: Verify the system clock on a machine during a troubleshooting session where time sync issues may be affecting authentication or logging.*

213_Disks. Lists all filesystem drives visible to PowerShell via Get-PSDrive, showing drive letter, used space, free space, and root path. *Example: A technician quickly checks all mounted drives and available space on a workstation before starting a data transfer.*

214_Domain. Retrieves the computer name and reports whether the machine is joined to a domain or a workgroup using Win32_ComputerSystem. *Example: A technician confirms a workstation's domain membership before attempting a remote group policy push.*

215.Event_Viewer Opens the Windows Event Viewer console via eventvwr.msc. *Example: Quickly inspect system, application, or security logs on a client machine to trace the cause of a crash, service failure, or login anomaly.*

216_Firewall_rule_list_with_Ports_2minuntes_wait. Enumerates all Windows Firewall rules with their associated port filters, displaying direction, action, enabled state, profile, and local port in a table. Warns the user upfront that the operation may take up to 2 minutes. *Example: A technician audits all firewall rules and their ports on a server to verify no unexpected inbound rules are active.*

217.Firewall_Rule_List Executes netsh advfirewall firewall show rule name=all to dump every inbound and outbound firewall rule currently configured on the machine. *Example: Audit all active firewall rules on a client machine to identify overly permissive entries or verify that a specific rule is in place.*

218_Firewall_Active_rules. Lists all currently enabled Windows Firewall rules with display name, direction, action, profile, and description in a readable table. *Example: A technician reviews active firewall rules on a client PC to confirm that only expected inbound ports are allowed.*

219_Get_Local_Users. Lists all local user accounts on the machine with name, enabled status, last logon date, password requirement, and description. *Example: A technician audits local accounts on a workstation to identify any unused, disabled, or unexpected accounts before a security review.*

220_Installed_drivers. Lists all installed signed device drivers with device name, driver version, and manufacturer, sorted alphabetically using Win32_PnPSignedDriver. *Example: A technician audits all drivers on a workstation to identify outdated or third-party drivers before a Windows update.*

221_Installed_apps. Lists all installed applications and their versions by reading both the 64-bit and 32-bit registry uninstall keys, deduplicating and sorting the results alphabetically. *Example: A technician checks which software is installed on a client PC to verify license compliance or identify bloatware.*

222.Net_User Executes net user to list all local user accounts on the machine. *Example: Get a quick overview of every local account on a workstation during a user management or security audit.*

223.Performance_Monitor Opens the Windows Performance Monitor via perfmon. *Example: Access real-time performance counters and data collector sets on a client machine to diagnose CPU, memory, or disk bottlenecks.*

224_Processes_ordered_from_highest_to_lowest_CPU_usage_get_process. Lists all running processes sorted by CPU usage from highest to lowest, showing process name, ID, CPU time, working set, and description. *Example: A technician quickly identifies the top CPU consumer on a sluggish workstation without opening Task Manager.*

225.Programs_and_Features Opens the classic Programs and Features Control Panel applet via appwiz.cpl. *Example: View, uninstall, or repair installed applications on a client machine using the legacy interface instead of the modern Settings app.*

226_ram_info. Displays total, used, and free physical RAM in GB, plus per-slot details (capacity, speed, manufacturer) from Win32_PhysicalMemory. *Example: A technician*

checks how much RAM a PC has installed and which slots are occupied before recommending a memory upgrade.

227.Resource_Monitor Opens the Windows Resource Monitor via resmon. *Example: Get a detailed real-time breakdown of CPU, memory, disk, and network usage by process on a client machine during a performance investigation.*

228.Release_and_Renew_IP Executes ipconfig /release && ipconfig /renew to drop the current DHCP lease and request a fresh IP address from the DHCP server. *Example: Force a client machine to obtain a new IP address after a network change or when the current lease is causing connectivity issues.*

229_services. Lists all currently running Windows services with their name, display name, and startup type, sorted alphabetically by display name. *Example: A technician reviews all active services on a workstation to identify unexpected third-party services running at startup.*

230.Shared_Folders_on_the_Local_Network Executes net share to list all folders and resources currently shared by the local machine over the network, including hidden administrative shares. *Example: Quickly audit what the machine is exposing on the network before handing it back to a client or during a security review.*

232_startup_View_startup_programs. Lists all programs configured to run at startup via Win32_StartupCommand, showing name, command line, registry or folder location, and the user context. *Example: A technician checks startup entries on a slow-booting PC to identify unwanted or suspicious autostart programs.*

233_System_uptime. Displays the last boot time and current system uptime in a human-readable format (days, hours, minutes). *Example: A technician confirms a workstation has been restarted after applying a Windows update by checking its uptime.*

234.Task_List_Open_Process Executes tasklist to display all currently running processes along with their PID, session name, and memory usage. *Example: Get a full snapshot of running processes on a client machine from the terminal without opening Task Manager.*

235_Users_List. Generates a full local user report including all local accounts, Administrators group members with SIDs, and the machine's domain or workgroup membership, with a summary at the end. *Example: A technician audits all user accounts and admin-group membership on a workstation during a security review.*

236.View_Active_RDP_Sessions Executes query session to list all active and disconnected remote desktop sessions on the machine, including session ID, username, and state.

Example: Check whether any RDP sessions are still active on a server before performing maintenance or a restart.

237.View_Group_Policies_gpresult Executes gpresult /R to display a summary of the Group Policy settings currently applied to the machine and the logged-in user. *Example: Verify which GPOs are in effect on a domain-joined workstation when troubleshooting a policy enforcement issue.*

238.VMware_Check. Detects any VMware-related Windows services and displays their name, display name, status, startup type, and executable path. *Example: A technician verifies whether VMware Workstation services are installed and running on a machine before enabling nested virtualization.*

239.Windows_Defender_Fast_Virus_Scanner Executes Windows Defender's command-line scanner with -ScanType 1 to run a quick scan, checking only the most common locations where malware typically resides. *Example: Run a fast malware check on a client machine during a service visit without opening the Windows Security UI.*

240.Windows_Defender_Virus_Complete_Scanner Executes Windows Defender's command-line scanner with -ScanType 2 to run a full system scan across all files and directories on the machine. *Example: Perform a thorough malware sweep on a client machine suspected of infection when a quick scan is not sufficient.*

F__External_links_tools

241.Can_You_Run_It_Game_Test Opens systemrequirementslab.com/cyri in the default browser, a web tool that analyzes the machine's hardware and compares it against the minimum and recommended requirements of any game. *Example: Instantly check whether a client's PC can run a specific game without manually looking up specs.*

242.DNS_Leak_Test Opens dnsleaktest.com in the default browser to verify whether DNS queries are being routed outside the expected path, which could expose browsing activity even when using a VPN. *Example: Confirm that a client's VPN is not leaking DNS requests to their ISP during a privacy audit.*

243.GamePad_Tester Opens hardwaretester.com/gamepad in the default browser, a web-based tool that detects connected controllers and displays real-time input from every button and axis. *Example: Quickly verify that a gamepad is functioning correctly and all inputs are registering without installing any software.*

244. Hybrid_Analysis Opens hybrid-analysis.com in the default browser, a free malware sandbox that allows uploading suspicious files or URLs for deep behavioral analysis. *Example: Submit a questionable executable found on a client machine for automated sandbox detonation and threat reporting.*

245. IP_Void Opens ipvoid.com in the default browser, a multi-engine IP reputation checker that queries blacklists and threat intelligence sources against any IP address. *Example: Check whether an IP address seen in a client's firewall logs is flagged as malicious across known threat databases.*

246. IP_Easy_By_SalgadoTech Opens IP-Easy, a web-based IPv4 planning toolkit developed by Salgado Technologies, directly in the default browser. The tool auto-detects the machine's public IP, ISP, and approximate location, and allows the technician to analyze any IPv4 address to obtain class info, binary representation, subnet table (/32 to /0), and a full VLSM Subnet Designer that allocates router-to-router /31 links and sizes LANs with growth margin. Results can be exported as PDF or copied per row. *Example: On a site visit, pull up IP-Easy to plan a multi-LAN network from scratch, assign gateway, modem, and switch addresses following a consistent IP policy, and export the design as a PDF for the client.*

247. Jotti's_Malware_Scan Opens virusscan.jotti.org in the default browser, a free multi-engine online malware scanner that checks uploaded files against several antivirus engines simultaneously. *Example: Get a second opinion on a suspicious file found on a client machine by scanning it across multiple AV engines without installing anything locally.*

248. KeyBoard_Tester Opens keyboardtester.com in the default browser, a web-based tool that visually highlights each key as it is pressed to verify that every key on the keyboard is registering correctly. *Example: Quickly diagnose a keyboard with unresponsive or stuck keys on a client machine without installing any software.*

249. MyIP_Address Opens whatismyipaddress.com in the default browser to display the machine's current public IP address along with ISP and geolocation information. *Example: Confirm the public IP of a client machine during a network configuration session or verify that a VPN is correctly masking the original address.*

250. Pwned_Email_Security Opens haveibeenpwned.com in the default browser, a service that checks whether an email address has appeared in any known data breaches. *Example: Check a client's email account against published breach databases during a security review to determine if credentials may have been compromised.*

251. RustDesk_Web Opens the RustDesk web client at rustdesk.com/web in the default browser, allowing browser-based remote desktop access without installing the full client.

Example: Remotely assist a client machine from a browser when the RustDesk desktop app is not available on the technician's end.

252.Speed_Test Opens speedtest.net in the default browser to measure the current internet connection's download speed, upload speed, and latency. *Example: Run a quick bandwidth test on a client site to verify whether the connection meets the expected service tier before troubleshooting further.*

253.Virus_Total_Scan Opens virustotal.com in the default browser, a multi-engine online scanner that checks files, URLs, domains, and IP addresses against over 70 antivirus engines and threat intelligence sources. *Example: Submit a suspicious file or URL found on a client machine for instant multi-engine analysis without installing any local antivirus tool.*

G__Nmap

G.A__Install_NmapOnPowershell

254.A.Install_Nmap Executes winget install -e --id Insecure.Nmap to silently download and install Nmap from the official Winget repository. *Example: Deploy Nmap on a client machine in a single command during a network assessment session without manually downloading the installer.*

255_B_LocateNmap. Searches all local drives for nmap.exe using recursive directory scanning and displays the full path of any match found. *Example: A technician installs Nmap manually and needs to find where the executable landed before adding it to PATH.*

256_C_Execute_nmap_using_the_path. Prompts the user for the full path to nmap.exe and executes it with the --version flag to confirm it runs correctly from that location. *Example: A technician uses the path found by script 255 to verify Nmap is functional before scripting a scan.*

257_D_Reload_and_confirmNmap_version. Reloads both Machine and User PATH environment variables in the current session, then locates nmap.exe and displays its installed version. *Example: A technician just installed Nmap and needs to confirm it is accessible in PATH without reopening the terminal.*

258_E_ScanNmap. Runs an Nmap network scan against a user-supplied IP address and subnet prefix (e.g. 192.168.1.0/24). *Example: A technician scans a client subnet to enumerate active hosts and open ports during a network audit.*

Inside G__Nmap

259_A_nmap_-F. Runs an Nmap fast scan (-F) against a single user-supplied IP address, checking only the 100 most common ports. *Example: A technician needs a quick port overview of a specific device without waiting for a full scan.*

260_B_Check_critics_Ports_RDP-HTTP-HTTPS-SSH. Scans a target IP for the four most critical service ports: SSH (22), HTTP (80), HTTPS (443), and RDP (3389) using Nmap. *Example: A technician quickly checks which remote access and web services are exposed on a client workstation before applying a firewall policy.*

261_C_Fast_Scanning_nmap_-T4_-A_-v. Runs an aggressive Nmap scan (-T4 -A -v) against a target IP, enabling fast timing, OS detection, service version identification, script scanning, and traceroute. *Example: A technician needs a detailed fingerprint of an unknown device on the network during an audit.*

262_D_Full_TCP_port_range_Slower. Runs a full TCP port range Nmap scan covering all 65535 ports on a target IP — slower but exhaustive, revealing non-standard services that a default scan would miss. *Example: A technician suspects a hidden service is running on a non-standard port and needs a complete port inventory.*

263_E_Lighter_scan_Detection. Runs Nmap service version detection (-sV) against a target IP with user-controlled probe intensity from 0 (light, low noise) to 9 (aggressive, maximum detail). *Example: A technician scans a sensitive production server at low intensity to identify running services without triggering IDS alerts.*

264.F.Local_Host Executes `nmap -p 1-65535 localhost` to scan all 65535 TCP ports on the local machine and report which ones are open. *Example: Get a full picture of every listening port on the machine during a local security audit or before exposing a service to the network.*

265_G_Nmap_Scan_against_IP_or_host. Runs a standard Nmap scan against a user-supplied IP address or hostname, returning open ports and basic service information. *Example: A technician runs a quick baseline scan on a new device added to the network to confirm what services it is exposing.*

266_H_Nmap_Scan_LAN_ReportOnDesktop. Runs an nmap service version scan (-sV) against a user-specified subnet and saves the full report as a text file on the Desktop. *Example: A technician scans the 192.168.1.0/24 network and saves the results to review device fingerprints offline.*

267_I_Ports_detailed_debugging. Runs a verbose TCP connect scan (`nmap -sT -v -v --reason`) against a target IP to show detailed port state reasoning for debugging. *Example: A technician investigates why a specific port appears filtered or closed on a remote machine.*

268_J_Review_RDP_3389_on_all_equipment. Scans port 3389 (RDP) across all hosts in a user-specified subnet to identify which machines have Remote Desktop exposed. *Example: A technician audits a client network to confirm which PCs are accessible via RDP before a remote support session.*

269_K_Nmap_-Pn_-T4_-sT. Runs a fast TCP connect scan on a target IP, skipping host discovery (`-Pn`) and using aggressive timing (`-T4`), useful for hosts that block ping. *Example: A technician scans a firewall-protected machine that does not respond to ICMP to enumerate its open ports.*

270_L_Nmap_-sS_-T4. Runs a SYN stealth scan (`-sS`) with aggressive timing (`-T4`) on a target IP; requires administrator privileges on Windows. *Example: A technician performs a stealthy port scan on a client device without completing the TCP handshake to avoid detection.*

271_M_Nmap_-sU_-p_Ports. Runs a UDP scan (`-sU`) on user-specified ports against a target IP; requires administrator privileges for raw socket access. *Example: A technician checks whether UDP ports 53, 67, and 161 (DNS, DHCP, SNMP) are open on a network device.*

272_N_Show_packets_sent_and_received. Runs a TCP connect scan with `--packet-trace` to display every packet sent and received, useful for low-level connection debugging. *Example: A technician diagnoses why a port appears filtered by inspecting the exact packet exchange during the scan.*

273_O_Nmap_-sV_Traceroute. Combines service version detection (`-sV`) with traceroute to enumerate open ports and map the network path to the target in a single scan. *Example: A technician audits a remote server's services while simultaneously tracing the routing path to identify bottlenecks.*

274_P_Top_port_Detection. Scans the top N most commonly used ports with service version detection (`-sV`) against a target IP, with the port count chosen by the user. *Example: A technician quickly identifies running services on a new client machine by scanning the top 100 ports.*

275_Q_What_hosts_are_alive_on_a_LAN. Performs a ping scan (-sn) on a user-specified subnet or IP range to discover which hosts are currently alive on the network. *Example: A technician scans 192.168.1.0/24 to get a quick count of active devices before starting a full audit.*

H__App_Downloader

H.A__NmapPortatil

276_A_Nmap_Download. Downloads the Nmap Portable installer from the IT-Tool GitHub repository to the Desktop and launches it with elevated privileges. *Example: A technician installs Nmap Portable on a client machine directly from the IT-Tool toolkit without browsing the web.*

277_B_OpenNMapPortable. Launches NmapPortable.exe from the user's Desktop folder, with a clear error message if the tool has not been installed yet. *Example: A technician opens the Nmap GUI interface quickly without navigating to the folder manually.*

H.B__Python_on_Powershell

278.Check_Python_Version Executes python --version in the active terminal to display the currently installed Python version. *Example: Verify whether Python is installed and confirm the version before running a script or installing a package on a client machine.*

279.Install_Python_on_PowerShell Executes a winget command to silently download and install Python 3.13 from the official Microsoft package source, automatically accepting all agreements. *Example: Deploy Python on a client machine in a single command without manually downloading the installer from python.org.*

280_Python_remove. Downloads the Python_remove script from the IT-Tool GitHub repository to the Desktop and executes it immediately. *Example: A technician runs the Python uninstaller helper on a client machine that has a broken Python installation.*

Inside H__App_Downloader

281_Advanced_IP_Scanner. Downloads the Advanced IP Scanner installer from the IT-Tool GitHub repository to a temp folder and launches it. *Example: A technician deploys Advanced IP Scanner on a client machine to quickly inventory all devices on the local network.*

282_AutoRun. Downloads Autoruns from the IT-Tool GitHub repository, silently accepts the EULA via registry, and launches the tool. *Example: A technician opens Autoruns on a client machine to inspect and clean up startup entries without a manual EULA dialog.*

283_BitTorrent. Downloads the BitTorrent web installer from the IT-Tool GitHub repository and launches it. *Example: A technician installs BitTorrent on a client machine directly from the IT-Tool toolkit.*

284_BizHawk_Emu. Downloads the BizHawk 2.10 multi-system emulator ZIP from GitHub and extracts it to a Desktop folder, ready to run. *Example: A technician sets up BizHawk on a client machine for multi-platform retro game testing without a formal installer.*

285_BorderLessGaming. Downloads the Borderless Gaming installer from the IT-Tool GitHub repository and launches it. *Example: A technician installs Borderless Gaming on a client PC to allow windowed-fullscreen mode for games that lack that option.*

286_CPU-ZPortable. Downloads and silently installs CPU-Z Portable to a temp folder, then automatically launches the executable. *Example: A technician runs CPU-Z Portable on a client machine to quickly identify the CPU model, speed, and memory configuration.*

287_CPUID_HWMonitor. Downloads HWMonitor 1.63 from the IT-Tool GitHub repository to the Desktop and launches it. *Example: A technician opens HWMonitor on a client machine to check real-time CPU, GPU, and drive temperatures during a diagnostic.*

288_DDU_Display_Driver_Uninstaller. Downloads the DDU (Display Driver Uninstaller) ZIP from GitHub, extracts it to the Desktop, and removes the temp file automatically. *Example: A technician prepares DDU on a client machine to perform a clean GPU driver removal before installing new drivers.*

289_DirectTx. Downloads the DirectX June 2010 redistributable ZIP, extracts it, and runs the silent installer with elevated privileges. *Example: A technician reinstalls legacy DirectX components on a client machine that fails to launch older games or applications.*

290_DiskGenius. Downloads the DiskGenius installer from GitHub and launches it with elevated privileges. *Example: A technician opens DiskGenius on a client machine to recover lost partitions or repair a damaged disk structure.*

291_Download_7zip. Downloads the 7-Zip 25.01 x64 installer from GitHub to the Desktop and launches it. *Example: A technician installs 7-Zip on a client machine that needs to extract compressed archives during a file migration.*

292_Fan_Control. Downloads the FanControl ZIP from GitHub, extracts it to the Desktop, and launches FanControl.exe with elevated privileges. *Example: A technician deploys FanControl on a client machine to diagnose and adjust fan curves during an overheating investigation.*

293_LightshotCopyScreen. Downloads the Lightshot installer from the IT-Tool GitHub repository and launches it. *Example: A technician installs Lightshot on a client machine to enable quick annotated screenshot capture during remote support.*

294_MemTest. Downloads MemTest64 from GitHub and launches it for RAM stress testing. *Example: A technician runs MemTest64 on a client machine reporting random crashes to check for faulty memory modules.*

295_N2nCopy. Downloads the N2nCopy ZIP from GitHub, extracts it to the Desktop, and launches n2ncopy.exe. *Example: A technician deploys N2nCopy on a client machine to perform high-speed file transfers between two local directories.*

296_Notedpad++. Downloads and silently installs Notepad++ Portable to a temp folder, then automatically launches it. *Example: A technician opens Notepad++ Portable on a client machine to inspect and edit configuration files without a full installation.*

297_OpenHardwareMonitor. Downloads and silently installs HWMonitor Portable to the Desktop, then automatically launches it. *Example: A technician opens HWMonitor Portable on a client machine to monitor CPU, GPU, and drive temperatures in real time during a diagnostic.*

298_Privoxy. Downloads the Privoxy 4.0.0 installer from the IT-Tool GitHub repository and launches it. *Example: A technician installs Privoxy on a client machine to set up a local HTTP proxy for traffic filtering or anonymization.*

299_Process_Explorer. Downloads Process Explorer from GitHub, accepts the EULA silently via registry, and launches it with elevated privileges. *Example: A technician opens Process Explorer on a client machine to investigate suspicious processes and their DLL dependencies.*

300_Python3_13_5. Downloads the Python 3.13.5 x64 installer from the IT-Tool GitHub repository and launches it. *Example: A technician installs Python on a client machine before deploying IT-Tool companion scripts that require a Python runtime.*

301_RevoUninstaller. Downloads the Revo Uninstaller installer from the IT-Tool GitHub repository and launches it. *Example: A technician uses Revo Uninstaller on a client machine to completely remove a stubborn application including leftover registry entries.*

302_Rufus_portable. Downloads and silently installs Rufus Portable to a temp folder, then automatically launches it. *Example: A technician opens Rufus Portable on a client machine to create a bootable USB drive for OS installation or recovery.*

303_RustDesk. Downloads the RustDesk 1.4.3 x64 installer from GitHub to the Desktop and launches it. *Example: A technician installs RustDesk on a client machine to enable open-source remote desktop access without relying on TeamViewer.*

304_Speccy. Downloads the Speccy installer from the IT-Tool GitHub repository and launches it. *Example: A technician runs Speccy on a client machine to quickly get a full hardware summary including CPU, RAM, motherboard, and temperatures.*

305_SpeedTest. Downloads the Speedtest by Ookla MSI installer from GitHub and launches it via msixexec. *Example: A technician installs the official Speedtest CLI/app on a client machine to run a reproducible bandwidth test during an ISP complaint.*

306_TestDisk. Downloads the TestDisk 7.3 ZIP from GitHub, extracts it to the Desktop, and launches testdisk_win.exe. *Example: A technician runs TestDisk on a client machine to recover deleted partitions or repair a corrupted boot sector.*

307_Tor_Portatil. Downloads the Tor Browser Portable ZIP from GitHub to the Desktop and extracts it, ready to run without installation. *Example: A technician deploys Tor Browser Portable on a client machine for anonymous browsing without leaving a system installation.*

308_UserBenchmark. Downloads the UserBenchmark installer from the IT-Tool GitHub repository and launches it. *Example: A technician runs UserBenchmark on a client machine to get a quick performance score across CPU, GPU, RAM, and storage.*

309_VisualC__Runtimes-All-in-One. Downloads and silently installs the Visual C++ 2015-2022 x64 redistributable with elevated privileges, handling restart and version conflict exit codes. *Example: A technician runs this on a client machine that fails to launch applications due to missing Visual C++ runtime dependencies.*

310_Win32_Disk_Imager. Downloads the Win32 Disk Imager installer from GitHub to the Desktop and launches it with elevated privileges. *Example: A technician uses Win32 Disk Imager on a client machine to write a recovery image to an SD card or USB drive.*

311_WinMediaCreatorTool. Downloads the Windows Media Creation Tool from the IT-Tool GitHub repository and launches it. *Example: A technician uses the Media Creation Tool on a client machine to create a bootable Windows 11 USB drive for a clean reinstall.*

312_WinRAR_Compress. Downloads the WinRAR 7.13 installer from the IT-Tool GitHub repository to the Desktop and launches it. *Example: A technician installs WinRAR on a client machine that needs to open or create RAR archives during a file recovery task.*

313.WinUtil Downloads and executes a hosted copy of Chris Titus Tech's WinUtil directly from the IT-Tool GitHub repository. WinUtil is a comprehensive Windows utility that

provides a GUI for installing and uninstalling applications, applying system tweaks, configuring Windows settings, running repairs, and debloating the OS. *Example: Launch a full Windows optimization and software management session on a client machine in a single command, without manually downloading or installing anything.*

314_Wireshark_Install. Installs Wireshark silently via winget, verifies the installation path, and launches it automatically; requires administrator privileges. *Example: A technician installs Wireshark on a client machine to capture and analyze network traffic during a connectivity investigation.*

315_Wireshark_Npcap. Downloads the latest Wireshark x64 installer directly from wireshark.org to the Desktop and launches it with elevated privileges. *Example: A technician downloads the latest Wireshark build on a client machine when winget is unavailable or the repo version is outdated.*

316_WizTree. Downloads the WizTree Portable ZIP from GitHub, extracts it to the Desktop, and cleans up the temp file. *Example: A technician deploys WizTree Portable on a client machine to quickly visualize which folders are consuming the most disk space.*