

Frontend <-> Backend Discrepancy Report

CLSynergy MVP | Integration Branch | July 2026

1. What Was Wired

POST /inquiries/inquiries-new-new -- Create Inquiry

apiCreateInquiry() transforms the flat frontend payload into the backend nested structure { client, contact, inquiry, commodities[], containers[] } and calls the correct URL. Each ContainerLine maps to one CommodityNew + one ContainerNew, linked by commodity_index. ContainerLine.isFcl maps to ContainerNew.is_fully_loaded per backend convention.

Frontend Field	-> Backend Field
customer_name	client.name
contact_person	contact.name
contact_channel_id (channel = Email)	contact.email
contact_channel_id (channel = WhatsApp)	contact.whatsapp
sbu, origin, priority, remark	inquiry.* (same field names)
delivery_type 'port-to-port'	inquiry.service_mode = PORT_TO_PORT
delivery_type 'door-to-door'	inquiry.service_mode = DOOR_TO_DOOR
preferred_liners: string[]	inquiry.preferred_liners (joined as comma string)
ContainerLine (each item)	commodities[i] + containers[i] with commodity_index: i
ContainerLine.isFcl	containers[i].is_fully_loaded

Response { inq_id, cli_id, cpid, com_ids, cont_ids } replaces the optimistic entry in-place. Frontend id is set to String(inq_id); all five backend IDs are stored on the Inquiry object.

GET /inquiries/inquiries/{inq_id} -- Fetch Single Inquiry

apiFetchInquiry(inq_id: number) returns InquiryRow[] -- one row per commodity-container join. InquiryRow typed in api.ts covers: inq_id, emp_id, sbu, origin, incoterm, priority, service_mode, cargo_ready_date, preferred_liners, preferred_rate, com_id, commodity_name, commodity_type, hs_code, commodity_weight, cont_id, container_type, temperature, qty, destination, zip_code, address, is_fully_loaded, free_time.

PATCH /inquiries/inquiries/{inq_id} -- Patch Inquiry Fields

apiPatchInquiry(inq_id, data) accepts: sbu, remark, origin, incoterm, cargo_ready_date, priority, preferred_liners, preferred_rate, service_mode. Only fields present in the payload are updated (exclude_unset on the backend).

PATCH ../commodities/{com_id} and ../containers/{cont_id}

apiPatchCommodity(inq_id, com_id, data) and apiPatchContainer(inq_id, cont_id, data) cover the two remaining PATCH routes in the inquiry router.

mockData.ts Additions

- Inquiry -- new optional backend fields (populated after create / fetch):
 inq_id: number
 cli_id: number
 cpid: number
 com_ids: number[]
 cont_ids: number[]

- ContainerLine -- new optional backend fields:
 - temperature: number // reefer set-point in deg C
 - address: string // door-delivery address (distinct from zip code)

2. Discrepancies -- Frontend Has, Backend Lacks (backend not modified)

Frontend Field / Concept	Issue
inquiry_text / request	No column in the inquiry table. Free-text description is not persisted to the backend.
destination (inquiry-level)	Backend stores destination per container only, not at inquiry level.
channel ('WhatsApp' 'Email' 'Phone')	No inquiry-table column. Channel value (contact_channel_id) is routed to contact.email or contact.whatsapp; the channel label itself is lost.
status ('pending' 'completed')	Not a backend field. Managed entirely in frontend state.
workflow_stage	Not a backend field. The entire workflow state machine lives only in the frontend.
is_fcl (Inquiry) / isFcl (ContainerLine)	Mapped to is_fully_loaded per backend convention. Semantically different: FCL/LCL vs whether the container is physically fully loaded.
ContainerLine.doorAgents[]	No backend equivalent. Silently dropped on create. this is only relevant for CS's view
ContainerLine.freeTime: number	Backend free_time is a string. Sent as String(freeTime); semantic differences possible.
employee_id in create payload	Backend derives emp_id from the auth session. This field is silently ignored. obsolete once authn authz flow is created
contact_channel_id when channel = 'Phone'	Contact table has email and whatsapp but no phone field. Phone-channel inquiries have nowhere to store the contact number.
recorded_by	Not in any backend payload or response. ← emp-id
completed_at / followup_note	Not in any backend model.

3. Discrepancies -- Backend Has / Lacks, Frontend App Flow Lacks / Has

Item	Detail
No 'fetch all inquiries' endpoint	Router only has GET /inquiries/inquiries/{inq_id} (single record). The Inquiry List page cannot be populated until a list/paginate endpoint is added.
No DELETE endpoint	No DELETE route in the inquiry router. Delete is frontend-only state.
apiAdvanceWorkflow -- no backend route	Kept in api.ts so App.tsx compiles, but every call returns 404 until /workflow-stage is added to the router.
incoterm, cargo_ready_date, preferred_rate	Backend stores these in the inquiry table. No UI controls in the New Inquiry form yet to capture them at creation time.
hs_code (commodity)	Returned by GET /inquiries/inquiries/{inq_id}. No form field to enter or display it on the frontend.
Existing client / existing contact paths	POST /inquiries/inquiries-old-new and ...-old-old are not wired. All creates go through the new-client path -- duplicate clients will be created for returning customers. Requires cli_id lookup; no client-search endpoint available in the inquiry module.
temperature (ContainerLine)	Backend ContainerNew has temperature: int for reefer containers. Added to ContainerLine type in mockData.ts but no UI input field exists yet.
address (ContainerLine)	Backend ContainerNew has address: str for door-delivery. Added to ContainerLine type but no UI input field exists yet.

4. Full Field Mapping Reference -- ContainerLine -> Backend

ContainerLine Field	Backend Table	Backend Column	Notes
containerType	container	container_type	Direct string
quantity	container	qty	Direct int
weight	commodity	weight	Float; " becomes None
commodityType	commodity	com_type	Direct string
commodityName	commodity	name	Direct string
destination	container	destination	Required; falls back to inquiry-level destination
isFcl	container	is_fully_loaded	bool; mapped per backend convention
zipCode	container	zip_code	" becomes None
freeTime	container	free_time	number -> String(n); " becomes None
temperature	container	temperature	New field; no UI input yet
address	container	address	New field; no UI input yet
doorAgents[]	--	--	NO BACKEND EQUIVALENT - dropped

5. Inquiry Endpoint Status at a Glance

Method	Path	Frontend Function	Status
POST	/inquiries/inquiries-new-new	apiCreateInquiry()	WIRED
POST	/inquiries/inquiries-old-new	--	NOT WIRED
POST	/inquiries/inquiries-old-old	--	NOT WIRED
GET	/inquiries/inquiries/{inq_id}	apiFetchInquiry()	WIRED
PATCH	/inquiries/inquiries/{inq_id}	apiPatchInquiry()	WIRED
PATCH	/inquiries/inquiries/{inq_id}/commodities/{com_id}	apiPatchCommodity()	WIRED
PATCH	/inquiries/inquiries/{inq_id}/containers/{cont_id}	apiPatchContainer()	WIRED
GET	/inquiries/inquiries (list / paginate)	--	MISSING IN BE
DELETE	/inquiries/inquiries/{inq_id}	--	MISSING IN BE
PATCH	/inquiries/{id}/workflow-stage	apiAdvanceWorkflow()	MISSING IN BE

Note: 'NOT WIRED' means the backend endpoint exists but the frontend does not call it yet. 'MISSING IN BE' means the frontend expects the endpoint but it has not been implemented in the backend router. All changes described here are frontend-only; the backend repository (FreightOS) was not modified for these discrepancy resolutions.