



# SLIIT

*Discover Your Future*

# IT1010 – Introduction to Programming

## Lecture 5 – Repetition statements in C



## Objectives

---

- At the end of the Lecture students should be able to
  - use the **while** repetition statement to execute statements in a program repeatedly.
  - use the **for** repetition statement to execute statements in a program repeatedly.
  - use the **do...while** repetition statement to execute statements in a program repeatedly.
  - Use **break** and **continue** statements to alter the flow of control.

## Counter-Controlled Repetition

---

- Number of repetitions is known before the loop begins execution.
- A control variable is used to count the number of repetitions.
- The control variable is incremented (usually by 1) each time the group of instructions is performed.
- The repetition terminates when the counter exceeds number of repetitions.

## Counter Controlled Repetition cont...

---

- Counter-controlled repetition requires:
  - The name of a control variable.
  - The initial value of the control variable
  - The increment ( or decrement) by which the control variable is modified each time through the loop.
  - The condition that tests for the final value of the control variable.

## Counter-Controlled Repetition with the while statement

```
//Counter-controlled repetition
# include <stdio.h>
int main(void)
{
    int counter = 1; // initialization
    while (counter <= 10) { //repetition condition
        printf("%d ", counter); // display counter
        ++ counter; // increment
    } // end while
} //end function main
```

Output

1 2 3 4 5 6 7 8 9 10

## General Format of a while Statement

---

```
while (condition) {  
    statements  
}
```

- The while statement body may contain single or a compound statement.

## Example 02 - while statement

```
// class average program with counter-controlled repetition
#include <stdio.h>
//function main begins program execution
int main(void)
{
    int counter, grade, total;
    float average;
    total = 0;
    counter = 1;
    while(counter <= 10){ //loop ten times
        printf("Enter grade :");
        scanf("%d", &grade); // read grade from user
        total = total + grade;
        counter = counter + 1; // increment counter
    } //end while
    average = (float)total / 10;
    printf("Class average is %.2f\n", average);
} //end function main
```

### output

```
Enter grade : 98
Enter grade : 76
Enter grade : 71
Enter grade : 87
Enter grade : 83
Enter grade : 90
Enter grade : 57
Enter grade : 79
Enter grade : 82
Enter grade : 94
Class average is 81
```

## Quiz

---

- What does the following program print?

```
#include <stdio.h>
int main(void)
{
    int x = 1, y;
    while ( x <= 5) {
        y = x * x;
        printf("%d\n", y);
        ++ x;
    } // end while
} //end function main
```



## Exercise 01

---

- Write a program that print all the even integers from 0 to 20.

## Sentinel-Controlled Repetition

---

- When no indication is given of how many times the loop should execute, a sentinel value is used to terminate the loop.
- E.g : type -1 to terminate entering of marks
- A loop should have a statement to obtain data each time the loop is performed.
- sentinel value must chosen so that it cannot be confused with an acceptable input value.

## Sentinel-Controlled Repetition

```
// class average program with sentinel-controlled repetition
#include <stdio.h>
int main(void)
{
    int grade, total, counter;
    float average;

    total = 0;
    counter = 0;

    //get first input from the user
    printf("Enter grade, -1 to end :");
    scanf("%d",&grade);

    while(grade != -1){
        total = total + grade;
        counter = counter + 1;
        // get next grade from user
        printf("Enter grade, -1 to end :");
        scanf("%d",&grade);
    } //end while
    average = (float)total / counter;
    printf("Class average is %.2f\n", average);
} //end function main
```

### Output

```
Enter grade, -1 to end : 75
Enter grade, -1 to end : 94
Enter grade, -1 to end : 97
Enter grade, -1 to end : 88
Enter grade, -1 to end : 70
Enter grade, -1 to end : 64
Enter grade, -1 to end : 83
Enter grade, -1 to end : 89
Enter grade, -1 to end : -1
Class average is 82.50
```

## Exercise 02

---

- Write a program that calculates and prints the average of several integers. Assume the last value read with scanf is the sentinel 9999.

## Counter-Controlled Repetition with the for statement

---


```
# include <stdio.h>
int main(void)
{
    int counter; // define counter

    for( counter = 1; counter <= 10; ++counter ){
        printf("%d\n", counter);
    }
}
```

Output

1 2 3 4 5 6 7 8 9 10

## for Statement Header Components



## General Format of a for Statement

---

```
for ( expression1; expression2; expression3){  
    statement  
    {
```

- Expressions in the for statement's header are optional
- Increment Expression acts like a standalone statement

## Quiz

---

- What does the following program print?

```
#include <stdio.h>
int main(void)
{
    int x;
    for( x = 3; x <= 15; x +=3 ){
        printf("%d\n", x);
    }
}
```



## Exercise 03

---

- Write a program that will print the following sequence of values . (Hint : use a for loop)

3, 8, 13, 18, 23

## do...while Repetition Statement

---

- Loop continuation condition is checked after the loop body is performed.
- Therefore the loop body will be executed at least once.

```
do{  
    statement  
}while (condition);
```

## Counter-Controlled Repetition with the do...while statement

```
# include <stdio.h>
int main(void)
{
    int counter = 1;

    do{
        printf("%d ", counter);
    } while (++counter <= 10);

}
```

Output

1 2 3 4 5 6 7 8 9 10

## break statement

---

- The break statement, when executed in a while, for, do...while statement causes immediate exit from that statement.
- Program execution continues with the next statement.
- Common uses of the break statement are to escape early from a loop.

## break statement example

```
//Using a break statement in a while statement
# include <stdio.h>
int main(void)
{
    int x = 1;
    while ( x <= 10) {
        if ( x == 5) {
            break;
        }
        printf("%d ", x);
        ++ x;
    } // end while
} //end function main
```

Output

1 2 3 4

## continue statement

---

- The continue statement, when executed in a while, for and do...while statement, skips the remaining statements in the body of that control statement and perform the next iteration of the loop.
- In while and do...while , loop continuation test is evaluated immediately after the continue statement is executed.
- In the for statement, the increment expression is executed.

## continue statement example

```
//Using the continue statement in a while statement
#include <stdio.h>
int main(void)
{
    int x = 1;
    while ( x <= 10) {
        if ( x == 5) {
            ++x;
            continue;
        }
        printf("%d ", x);
        ++ x;
    } // end while
} //end function main
```

### Output

1 2 3 4 6 7 8 9 10

## Nested iteration

```
# include <stdio.h>
int main(void)
{
    int i, j;
    for ( i = ; i <= 5 ; ++i){
        for ( j = 1; j <= i; ++j){
            printf(" *" );
        }
        printf("\n");
    }
}
```

## Output

```
*
* *
* * *
* * * *
* * * * *
```



## Exercise 04

---

- Write a program that will print the following output.

```
1
1 2
1 2 3
1 2 3 4
1 2 3 4 5
```