



BSc (Hons) in **Information Technology**
Specialized in AI

IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing

Practical 01

Objective & Lecture Mapping: Recall that an intelligent agent acts within a continuous loop: Sensors generate percept sequences, and Actuators execute actions to maximize a Performance measure. Use this sheet to execute practical modifications and incrementally evaluate your design against Lecture 01 and 02 theory (from basic recall to analytical classification).

Part 1: Code Analysis & PEAS Evaluation

Task 0 : Setting up and getting the starter Code

1. Go to the [Git Hub Repo](#). Create a Fork of this Git Repo to your Personal Github Profile. Open it using your favourite IDE and follow the below instruction to complete the practical. The base code is in the "master" brach of the repo.

Task 1.1: The Environment State (__init__)

1. (Remember) List the four components of the PEAS framework discussed in Lecture 01.

P – Performance Measure
E – Environment
A – Actuators
S – Sensors

2. (Understand) Look at the `VisualGridHuntGame.__init__` method. Which

specific variables in this code represent the physical "Environment (E)" state?

```
self.grid_width  
self.grid_height  
self.walls  
self.food  
self.agent_pos  
self.opponents
```

3. (Analyze) Based on the variables initialized (specifically `self.opponents`), classify this baseline environment as "Single-Agent" or "Multi-Agent". Briefly justify your choice.

Multi-Agent
Because the game has opponents (`self.opponents`). So, more than one agent is in the environment.

Task 1.2: The Perception Subsystem (`get_percept`)

4. (Remember) Define what a "percept sequence" is according to Lecture 01.

A percept sequence is all the information the agent receives from its sensors over time

5. (Understand) Which component of the PEAS framework does the `get_percept()` method represent in our code?

Sensors (S)
Because it collects information from the environment.

6. (Evaluate) Based on the exact dictionary returned by `get_percept()` , is this environment "Fully Observable" or "Partially Observable"? Explain why based on what the agent can and cannot see.

Partially Observable
Because the agent can only see the information given by `get_percept()`. It cannot see the whole environment.

Task 1.3: Action Execution (execute_action)

7. (Understand) When `execute_action()` deducts points for hitting a wall, which PEAS component is being actively updated?

Performance Measure (P)
Because the score changes based on the agent's action.

8. (Evaluate) Why is it structurally important that this metric evaluates changes in the external environment state (hitting a wall) rather than the agent's internal processing effort?

The performance measure should check the result of the action, not how the agent thinks. This helps measure whether the agent reaches its goal.

Part 2: Guided Modification & Deep Theory Mapping

Follow the implementation instructions to inject a new hazard, then answer the questions to map your code changes back to the theoretical nature of the environment.

Step 2.1: Extending the Environment Initialization (`__init__`)

1. **Implementation Instructions:** Declare a new trap collection attribute (e.g., `self.toxic_traps = set()`) inside `__init__`. Populate it with coordinate tuples safely avoiding position `(0, 0)`, walls, and food.

9. (Understand) If you successfully add `self.toxic_traps` to the environment but intentionally **hide** this data from the agent's sensors, how does this specifically alter the environment's "Observability" classification?

The environment becomes Partially Observable because the agent cannot see the trap locations.

Step 2.2: Updating the Perception Subsystem (get_percept)

1. **Implementation Instructions:** Locate `get_percept(self)` and add a new boolean sensor key (e.g., `'smells_toxin': tuple(self.agent_pos)` in `self.toxic_traps`) to the dictionary returned to the agent loop.

10. (Analyze) By adding `'smells_toxin'` , you expand the agent's percept sequence. Explain how this specific sensor helps the agent act with "Rationality" (maximizing expected utility).

The `smells_toxin` sensor warns the agent about toxic traps. This helps the agent avoid danger, make better decisions, and get a higher score.

Step 2.3: Modifying Action Execution & Visual Rendering (execute_action & draw_grid)

1. **Implementation Instructions:** In `execute_action` , check if the updated `self.agent_pos` intersects with `self.toxic_traps` to decrement `self.score` by 15 points. In `draw_grid` , iterate through traps to render custom purple shapes on the canvas.

11. (Remember) You programmed a severe score penalty for stepping on a trap to avoid metric exploitation. What was the classic "Vacuum World Exploit" example discussed in Lecture 01 that illustrated the danger of faulty metrics?

The vacuum agent keeps cleaning an already clean place to get more points instead of cleaning the whole environment. This shows that a bad performance measure can cause wrong behavior.

Finalize and Lock Lab 01 Analytical Evaluation

Lab 01 code analysis and theoretical evaluation complete and verified!



FACULTY OF COMPUTING