



BSc (Hons) in **Computer Science**
SE3062 : Intelligent Systems
Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing



Practical 02

Objective & Lecture Mapping: In Lecture 03, we learned that a mathematically perfect "Table-Driven Agent" is impossible to build due to combinatorial explosion. Instead, we must write Agent Programs. Today, you will implement a **Simple Reflex Agent** using Condition-Action rules, observe its fatal flaws in a partially observable environment, and then upgrade it to a **Model-Based Agent** that maintains an internal memory state.

Part 1: Practical Implementation — Coding the Architectures

Step 1.1: Setting the Trap (Partial Observability)

To see why Simple Reflex agents fail, we must handicap your agent's sensors. We are moving from a Fully Observable world to a Partially Observable one.

1. Open your `visual_grid_game.py` from Lab 01.
2. Locate the `get_percept(self)` method.
3. Modify it so it **no longer returns** the exact global coordinates (`agent_pos`). Instead, it should only return local booleans, e.g., `{'wall_ahead': True/False, 'food_here': True/False}` based on checking the adjacent cell in its current facing direction.

Step 1.2: The Simple Reflex Agent (Implementation & Failure)

1. Create a new class called `SimpleReflexAgent`.
2. Implement a `sense_and_act(self, percept)` method that uses strictly IF-THEN logic (Condition-Action rules). *Do not use an `__init__` method to store history.*

Example Logic: IF food_here THEN suck; IF wall_ahead THEN turn_left; ELSE move_forward

3. Run the simulation. **Observe:** Watch the agent get trapped in a corner or a U-shaped wall, infinitely repeating a cycle (e.g., turn left, step forward, hit wall, turn left...).

Step 1.3: The Model-Based Agent (Memory & State)

1. Create a new class called `ModelBasedAgent`.
2. Implement an `__init__(self)` method to initialize an internal memory state (e.g., `self.visited_cells = set()` or a relative movement tracker).
3. In `sense_and_act(self, percept)`, first **update the state** (Transition & Sensor Model) by recording the current percept and the last action taken.
4. Update your IF-THEN rules to query the memory.
Example Logic: IF wall_ahead AND left_is_visited THEN turn_right
5. Run the simulation. **Observe:** The agent should now remember where it has been, realize it is in a loop, and choose an alternate path to escape.

Part 2: Theoretical Evaluation & Lecture Mapping

Based on your practical observations above, answer the following questions to map your code directly to the architectural theories covered in Lecture 02.

1. (Remember) According to Lecture 02, why is it impossible to program a mathematically perfect "Table-Driven Agent" for complex environments like Chess? What happens as the agent's lifetime increases?

A Table-Driven Agent is not practical for Chess because there are too many possible situations and moves to store in a table.
As the agent's lifetime increases, the number of possible situations grows extremely, so the table becomes too large to create or store.

2. (Understand) Look at the code you wrote for your `SimpleReflexAgent` . Identify and explain the specific lines of code that represent the "Condition-Action Rules" discussed in the lecture.

The Condition-Action Rules are implemented using if-elif-else statements in `sense_and_act()`. The agent checks its current percept and chooses an action. If `food_here` is true, it returns "Suck". If `wall_ahead` is true, it returns "Left". Otherwise, it returns "Forward". These rules make the agent a Simple Reflex Agent because it makes decisions only from the current percept and does not use memory.

3. (Analyze) Your `SimpleReflexAgent` likely got stuck in an infinite loop during Step 1.2. Based on the lecture, analyze exactly why this happened. How did the combination of "Partial Observability" and a lack of "Percept History" cause this failure?

It could only see what was directly around it. It could not remember where it had been (No memory). When it saw the same situation again, it made the same decision again. So it repeated the same movements and got stuck in a loop.

4. (Evaluate) In Step 1.3, you added an internal state to your `ModelBasedAgent` . Evaluate how your specific code handles the "Transition Model" (how the world evolves) and the "Sensor Model" (how the agent's actions affect the world).

Sensor Model is handled by `get_percept()`, which gives the agent information such as `wall_ahead` and `food_here`. The Transition Model is handled by the agent's memory, such as `visited_cells`, `last_percept`, and `last_action`. This allows the agent to remember previous situations and choose a different action instead of repeating the same action.

Finalize and Lock Lab 02 Documentation

