



BSc (Hons) in **Computer Science**
SE3062 : Intelligent Systems

Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing

Practical 02

Objective & Lecture Mapping: In Lecture 03, we learned that a mathematically perfect "Table-Driven Agent" is impossible to build due to combinatorial explosion. Instead, we must write Agent Programs. Today, you will implement a **Simple Reflex Agent** using Condition-Action rules, observe its fatal flaws in a partially observable environment, and then upgrade it to a **Model-Based Agent** that maintains an internal memory state.

Part 1: Practical Implementation — Coding the Architectures

Step 1.1: Setting the Trap (Partial Observability)

To see why Simple Reflex agents fail, we must handicap your agent's sensors. We are moving from a Fully Observable world to a Partially Observable one.

1. Open your `visual_grid_game.py` from Lab 01.
2. Locate the `get_percept(self)` method.
3. Modify it so it **no longer returns** the exact global coordinates (`agent_pos`). Instead, it should only return local booleans, e.g., `{'wall_ahead': True/False, 'food_here': True/False}` based on checking the adjacent cell in its current facing direction.

Step 1.2: The Simple Reflex Agent (Implementation & Failure)

1. Create a new class called `SimpleReflexAgent` .
2. Implement a `sense_and_act(self, percept)` method that uses strictly IF-THEN logic (Condition-Action rules). *Do not use an `__init__` method to store history.*
Example Logic: IF `food_here` THEN `suck`; IF `wall_ahead` THEN `turn_left`; ELSE `move_forward`
3. Run the simulation. **Observe:** Watch the agent get trapped in a corner or a U-shaped wall, infinitely repeating a cycle (e.g., turn left, step forward, hit wall, turn left...).

Step 1.3: The Model-Based Agent (Memory & State)

1. Create a new class called `ModelBasedAgent` .
2. Implement an `__init__(self)` method to initialize an internal memory state (e.g., `self.visited_cells = set()` or a relative movement tracker).
3. In `sense_and_act(self, percept)` , first **update the state** (Transition & Sensor Model) by recording the current percept and the last action taken.
4. Update your IF-THEN rules to query the memory.
Example Logic: IF `wall_ahead` AND `left_is_visited` THEN `turn_right`
5. Run the simulation. **Observe:** The agent should now remember where it has been, realize it is in a loop, and choose an alternate path to escape.

Part 2: Theoretical Evaluation & Lecture Mapping

Based on your practical observations above, answer the following questions to map your code directly to the architectural theories covered in Lecture 02.

1. (Remember) According to Lecture 02, why is it impossible to program a mathematically perfect "Table-Driven Agent" for complex environments like Chess? What happens as the agent's lifetime increases?

A Table-Driven Agent stores an action for every possible percept sequence. In a complex game like Chess, the number of possible percept sequences becomes extremely large (combinatorial explosion) as the agent's lifetime increases. Therefore, it is impossible to store all possible actions in a lookup table, so we use an Agent Program instead.

2. (Understand) Look at the code you wrote for your `SimpleReflexAgent` . Identify and explain the specific lines of code that represent the "Condition-Action Rules" discussed in the lecture.

The condition-action rules in my `SimpleReflexAgent` are represented by the if, elif, and else statements.

```
if percept["food_here"]: return "Suck"
```

Rule: If food is detected, then suck it up.

```
elif ...: return "TurnLeft"
```

Rule: If there is a wall in front, then turn left.

```
else: return "MoveForward"
```

Rule: If neither of the above conditions is true, then move forward.

These rules allow the agent to select an action based directly on its current percept, which is the main idea of Condition-Action Rules in a simple reflex agent

3. (Analyze) Your `SimpleReflexAgent` likely got stuck in an infinite loop during Step 1.2. Based on the lecture, analyze exactly why this happened. How did the combination of "Partial Observability" and a lack of "Percept History" cause this failure?

The agent got stuck because it could only see what was immediately around it, such as whether there was a wall or food. Since it did not store any information about where it had already been or what actions it had taken, it could not recognize that it was repeating the same situation. As a result, the same percept produced the same action repeatedly, causing the agent to move in a loop.

4. (Evaluate) In Step 1.3, you added an internal state to your `ModelBasedAgent` . Evaluate how your specific code handles the "Transition Model" (how the world evolves) and the "Sensor Model" (how the agent's actions affect the world).

The `ModelBasedAgent` uses an internal state to keep track of how the environment changes. The Transition Model updates information such as the agent's position, direction, visited locations, and previous action as it moves. The Sensor Model combines the current percept with this stored information to decide what to do next. This memory helps the agent recognize repeated paths and avoid loops, making it more reliable than the Simple Reflex Agent.

Finalize and Lock Lab 02 Documentation



FACULTY OF COMPUTING