



BSc (Hons) in **Computer Science**
SE3062 : Intelligent Systems
 Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing

Practical 02

Objective & Lecture Mapping: In Lecture 03, we learned that a mathematically perfect "Table-Driven Agent" is impossible to build due to combinatorial explosion. Instead, we must write Agent Programs. Today, you will implement a **Simple Reflex Agent** using Condition-Action rules, observe its fatal flaws in a partially observable environment, and then upgrade it to a **Model-Based Agent** that maintains an internal memory state.

Part 1: Practical Implementation — Coding the Architectures

Step 1.1: Setting the Trap (Partial Observability)

To see why Simple Reflex agents fail, we must handicap your agent's sensors. We are moving from a Fully Observable world to a Partially Observable one.

1. Open your `visual_grid_game.py` from Lab 01.
2. Locate the `get_percept(self)` method.
3. Modify it so it **no longer returns** the exact global coordinates (`agent_pos`). Instead, it should only return local booleans, e.g., `{'wall_ahead': True/False, 'food_here': True/False}` based on checking the adjacent cell in its current facing direction.

Step 1.2: The Simple Reflex Agent (Implementation & Failure)

1. Create a new class called `SimpleReflexAgent` .
2. Implement a `sense_and_act(self, percept)` method that uses strictly IF-THEN logic (Condition-Action rules). *Do not use an `__init__` method to store history.*
 Example Logic: IF `food_here` THEN `suck`; IF `wall_ahead` THEN `turn_left`; ELSE `move_forward`
3. Run the simulation. **Observe:** Watch the agent get trapped in a corner or a U-shaped wall, infinitely repeating a cycle (e.g., turn left, step forward, hit wall, turn left...).

Step 1.3: The Model-Based Agent (Memory & State)

1. Create a new class called `ModelBasedAgent` .
2. Implement an `__init__(self)` method to initialize an internal memory state (e.g., `self.visited_cells = set()` or a relative movement tracker).
3. In `sense_and_act(self, percept)` , first **update the state** (Transition & Sensor Model) by recording the current percept and the last action taken.
4. Update your IF-THEN rules to query the memory.
 Example Logic: IF `wall_ahead` AND `left_is_visited` THEN `turn_right`

5. Run the simulation. **Observe:** The agent should now remember where it has been, realize it is in a loop, and choose an alternate path to escape.

Part 2: Theoretical Evaluation & Lecture Mapping

Based on your practical observations above, answer the following questions to map your code directly to the architectural theories covered in Lecture 02.

1. (Remember) According to Lecture 02, why is it impossible to program a mathematically perfect "Table-Driven Agent" for complex environments like Chess? What happens as the agent's lifetime increases?

The agent function maps every possible percept sequence to an action. to build a table driven agent of this, it needs a new row for every possible percept sequence. For a game like chess, the possible percept sequences are very large. it can be even infinite. it is impossible to store infinite lookup table in real.

2. (Understand) Look at the code you wrote for your `SimpleReflexAgent`. Identify and explain the specific lines of code that represent the "Condition-Action Rules" discussed in the lecture.

this lines takes only one single percept: not a percept sequence
The if, elif, else structure enforces a fixxed rule odering. food_ here is checked before the wall_ahead. Only one rule fires per decision cycle.

3. (Analyze) Your `SimpleReflexAgent` likely got stuck in an infinite loop during Step 1.2. Based on the lecture, analyze exactly why this happened. How did the combination of "Partial Observability" and a lack of "Percept History" cause this failure?

The agent has no memory. This agent only uses the single current percept. Since it has no memory of the history, if it hits a wall it will take the exact same decision it took before. like that whenever it faces a wall it will take the same decision over and over again because the situation look identical to the agent's sensors.

4. (Evaluate) In Step 1.3, you added an internal state to your `ModelBasedAgent`. Evaluate how your specific code handles the "Transition Model" (how the world evolves) and the "Sensor Model" (how the agent's actions affect the world).

Apply the effect of the previous action to update the belief abput position. it uses self.last_wall_ahead rather than the current percept, since a move forward only acts right when there was no wall ahead then.

Finalize and Lock Lab 02 Documentation

Incomplete: 0/11 questions answered. Please provide detailed responses for all questions.



FACULTY OF COMPUTING