



BSc (Hons) in **Computer Science**
SE3062 : Intelligent Systems
Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing

Practical 02

Objective & Lecture Mapping: In Lecture 03, we learned that a mathematically perfect "Table-Driven Agent" is impossible to build due to combinatorial explosion. Instead, we must write Agent Programs. Today, you will implement a **Simple Reflex Agent** using Condition-Action rules, observe its fatal flaws in a partially observable environment, and then upgrade it to a **Model-Based Agent** that maintains an internal memory state.

Part 1: Practical Implementation — Coding the Architectures

Step 1.1: Setting the Trap (Partial Observability)

To see why Simple Reflex agents fail, we must handicap your agent's sensors. We are moving from a Fully Observable world to a Partially Observable one.

1. Open your `visual_grid_game.py` from Lab 01.
2. Locate the `get_percept(self)` method.

3. Modify it so it **no longer returns** the exact global coordinates (`agent_pos`). Instead, it should only return local booleans, e.g., `{'wall_ahead': True/False, 'food_here': True/False}` based on checking the adjacent cell in its current facing direction.

Step 1.2: The Simple Reflex Agent (Implementation & Failure)

1. Create a new class called `SimpleReflexAgent` .
2. Implement a `sense_and_act(self, percept)` method that uses strictly IF-THEN logic (Condition-Action rules). *Do not use an `__init__` method to store history.*
Example Logic: IF `food_here` THEN `suck`; IF `wall_ahead` THEN `turn_left`; ELSE `move_forward`
3. Run the simulation. **Observe:** Watch the agent get trapped in a corner or a U-shaped wall, infinitely repeating a cycle (e.g., turn left, step forward, hit wall, turn left...).

Step 1.3: The Model-Based Agent (Memory & State)

1. Create a new class called `ModelBasedAgent` .
2. Implement an `__init__(self)` method to initialize an internal memory state (e.g., `self.visited_cells = set()` or a relative movement tracker).
3. In `sense_and_act(self, percept)` , first **update the state** (Transition & Sensor Model) by recording the current percept and the last action taken.
4. Update your IF-THEN rules to query the memory.
Example Logic: IF `wall_ahead` AND `left_is_visited` THEN `turn_right`

5. Run the simulation. **Observe:** The agent should now remember where it has been, realize it is in a loop, and choose an alternate path to escape.

Part 2: Theoretical Evaluation & Lecture Mapping

Based on your practical observations above, answer the following questions to map your code directly to the architectural theories covered in Lecture 02.

1. (Remember) According to Lecture 02, why is it impossible to program a mathematically perfect "Table-Driven Agent" for complex environments like Chess? What happens as the agent's lifetime increases?

A Table-Driven Agent is not practical for complex environments like Chess because it would need to store an action for every possible percept sequence. As the agent's lifetime increases, the number of possible percept histories grows exponentially (combinatorial explosion), making the table far too large to store or use efficiently.

2. (Understand) Look at the code you wrote for your `SimpleReflexAgent`. Identify and explain the specific lines of code that represent the "Condition-Action Rules" discussed in the lecture.

In my `SimpleReflexAgent`, the IF-THEN statements represent the condition-action rules. For example, if `percept["food_here"]` then the agent performs "Eat", elif `percept["wall_ahead"]` then it performs "Left", otherwise it moves "Up". The agent chooses an action based only on its current percept without using any memory.

3. (Analyze) Your `SimpleReflexAgent` likely got stuck in an infinite loop during Step 1.2. Based on the lecture, analyze exactly why this happened. How did the combination of "Partial Observability" and a lack of "Percept History" cause this failure?

The SimpleReflexAgent got stuck because it could only observe its current surroundings and had no memory of previous actions or visited locations. Due to partial observability and the lack of percept history, it repeatedly made the same decision in the same situation, causing it to loop instead of finding a new path.

4. (Evaluate) In Step 1.3, you added an internal state to your `ModelBasedAgent` . Evaluate how your specific code handles the "Transition Model" (how the world evolves) and the "Sensor Model" (how the agent's actions affect the world).

The ModelBasedAgent uses an internal memory to store visited cells, its estimated position, and the previous action. The transition model updates the agent's internal state after each action, while the sensor model uses the current percept to determine whether there is food or a wall ahead. This allows the agent to make better decisions and avoid repeating the same mistakes.

Finalize and Lock Lab 02 Documentation

