BSc (Hons) in **Information Technology Specialized in AI**

Faculty of Computing

IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Practical 03

> **Objective & Lecture Mapping:** In previous labs, we built a Simple Reflex Agent that moved randomly or reacted only to immediate adjacent cells. Today, we transition to a **Goal-Based/Planning Agent**. You will expose the environment's state space to the agent, allowing it to use **Breadth-First Search (BFS)**, **Depth-First Search (DFS)**, and **Uniform-Cost Search (UCS)** to simulate and find paths to the food before taking a physical action.

Part 1: Practical Implementation — Building the Search Agent

Step 1.1: Exposing the World Model

> Classical search algorithms require an abstract model of the environment to simulate future states. Currently, your agent is "blind" to the overall map.

1. Create a new Branch called Week_03 in your Forked Github Repo and work on the below Questions.
2. Open `visual_grid_game.py` .
3. Locate the `get_percept(self)` method.
4. Add three new keys to the dictionary to pass the global state to the agent:

```
'grid_size': (self.width, self.height)
'walls': list(self.walls)
'all_food': list(self.food_positions)
```

Step 1.2: Implementing BFS, DFS, and UCS

> You will implement three distinct uninformed search strategies. The core node expansion structure is identical; only the data structure for the **Frontier** changes!

1. Open `agent.py` and create a new class called `SearchAgent`.
2. Import required structures: `from collections import deque` and `import heapq`.
3. **BFS:** Create `def bfs_search(...)`. Use a FIFO queue (`deque.popleft()`). This explores the shallowest nodes first.
4. **DFS:** Create `def dfs_search(...)`. Use a LIFO stack (`list.pop()`). This explores the deepest nodes first.
5. **UCS:** Create `def ucs_search(...)`. Use a Priority Queue (`heapq.heappop()`) ordered by the total path cost $g(n)$.
6. For all three algorithms, you must maintain a `reached` set (or visited array) to track explored states. This converts your algorithm from a *Tree Search* to a *Graph Search*, preventing infinite loops.

Step 1.3: Executing and Comparing Offline Plans

> The agent must now form a complete plan and execute it step-by-step.

1. In your `SearchAgent.__init__`, add an empty list: `self.plan = []` and a config string `self.active_algo = 'BFS'`.
2. In `sense_and_act(self, percept)`, check if `self.plan` is empty.
3. If empty, find the closest food pellet from `percept['all_food']`, execute the search method matching `self.active_algo`, and store the resulting sequence of actions in `self.plan`.
4. Return the first action from the plan using `return self.plan.pop(0)`.
5. **Observation Task:** Change `self.active_algo` between 'BFS', 'DFS', and 'UCS' and run the simulation. Watch how DFS takes erratic, winding paths, while BFS and UCS take direct, optimal paths!

Part 2: Theoretical Evaluation

> Based on your implementation and Lecture 04, complete the following analytical questions.

1. (Remember) You built your search logic based on the environment coordinates. What is the fundamental difference between the "State Space" and the "Search Tree"?

State Space - It represents the physical layout of the grid environment. Every unique (x, y) coordinates that the agent can physically occupy is a single state. Search Tree - It is the logical data structure that the agent builds in its memory while simulating future moves. In the search tree, a single physical coordinate can appear multiple times as different nodes if the agent discovers multiple different routes to reach that same spot.

2. (Understand) In Step 1.2, you were instructed to use a `reached` set. In graph search theory, what specific problem does this set solve, and what would happen to your DFS agent without it?

reached set is implemented to solve the problem of redundant paths and cycles. If we did not include this set, then the DFS agent fall into an infinite loop. The agent could take a step forward and take a step backward then repeat that cycle forever because it remember that it had already visited those exact same squares.

3. (Analyze) Compare the visual paths generated by BFS and DFS in your simulation. Why is BFS guaranteed to be optimal in this specific grid, whereas DFS produces winding, suboptimal routes?

BFS is guaranteed to be optimal in this specific grid game because every movement has an equal step cost of 1. Because BFS explores the environment level by level. It is mathematically guaranteed to be the shortest possible path.

DFS, here plunges as deep as possible down a single path until it hits a dead end or stumbles upon the goal. It accepts the very first path which it finds which is why the visual simulation shows it taking long, erratic and suboptimal routes rather than a direct line.

4. (Evaluate) If we scaled `visual_grid_game.py` up to a massive 1000x1000 grid, BFS and UCS might crash before finding food. According to the time and space complexity formulas from the lecture, contrast the memory bottlenecks of BFS versus DFS.

here, BFS runs out of memory and crash. Its space complexity is O(b^d) (where b is the branching factor and d is depth) - it has to remember every possible

move on the expanding edge of its search all at once. This eats up computer RAM extremely fast.

DFS is much more memory friendly with a space complexity of O(bm) (where m is max depth). It only has to remember the single path it is currently walking down so it avoids the memory crash entirely and even though it takes longer to find the answer.

Once Completed Get a PDF of the completed File and Push into the Week 03 brach in the Github Project

Finalize and Lock Lab 03 Documentation

Incomplete: 0/11 questions answered. Please provide detailed responses for all questions.



FACULTY OF COMPUTING