



BSc (Hons) in **Information Technology**
Specialized in AI

IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing

Practical 03

Objective & Lecture Mapping: In previous labs, we built a Simple Reflex Agent that moved randomly or reacted only to immediate adjacent cells. Today, we transition to a **Goal-Based/Planning Agent**. You will expose the environment's state space to the agent, allowing it to use **Breadth-First Search (BFS)**, **Depth-First Search (DFS)**, and **Uniform-Cost Search (UCS)** to simulate and find paths to the food before taking a physical action.

Part 1: Practical Implementation — Building the Search Agent

Step 1.1: Exposing the World Model

Classical search algorithms require an abstract model of the environment to simulate future states. Currently, your agent is "blind" to the overall map.

1. Create a new Branch called Week_03 in your Forked Github Repo and work on the below Questions.
2. Open `visual_grid_game.py` .
3. Locate the `get_percept(self)` method.
4. Add three new keys to the dictionary to pass the global state to the agent:

```
'grid_size': (self.width, self.height)
'walls': list(self.walls)
'all_food': list(self.food_positions)
```

Step 1.2: Implementing BFS, DFS, and UCS

You will implement three distinct uninformed search strategies. The core node expansion structure is identical; only the data structure for the **Frontier** changes!

1. Open `agent.py` and create a new class called `SearchAgent` .

2. Import required structures: `from collections import deque` and `import heapq` .
3. **BFS:** Create `def bfs_search(...)` . Use a FIFO queue (`deque.popleft()`). This explores the shallowest nodes first.
4. **DFS:** Create `def dfs_search(...)` . Use a LIFO stack (`list.pop()`). This explores the deepest nodes first.
5. **UCS:** Create `def ucs_search(...)` . Use a Priority Queue (`heapq.heappop()`) ordered by the total path cost $g(n)$.
6. For all three algorithms, you must maintain a `reached` set (or visited array) to track explored states. This converts your algorithm from a *Tree Search* to a *Graph Search*, preventing infinite loops.

Step 1.3: Executing and Comparing Offline Plans

The agent must now form a complete plan and execute it step-by-step.

1. In your `SearchAgent.__init__` , add an empty list: `self.plan = []` and a config string `self.active_algo = 'BFS'` .
2. In `sense_and_act(self, percept)` , check if `self.plan` is empty.
3. If empty, find the closest food pellet from `percept['all_food']` , execute the search method matching `self.active_algo` , and store the resulting sequence of actions in `self.plan` .
4. Return the first action from the plan using `return self.plan.pop(0)` .
5. **Observation Task:** Change `self.active_algo` between 'BFS', 'DFS', and 'UCS' and run the simulation. Watch how DFS takes erratic, winding paths, while BFS and UCS take direct, optimal paths!

Part 2: Theoretical Evaluation

Based on your implementation and Lecture 04, complete the following analytical questions.

1. (Remember) You built your search logic based on the environment coordinates. What is the fundamental difference between the "State Space" and the "Search Tree"?

The state space is the set of all possible states of the problem, while the Search Tree is the tree of states generated and explored by a search algorithm starting from the initial state

2. (Understand) In Step 1.2, you were instructed to use a `reached` set. In graph search theory, what specific problem does this set solve, and what would happen to your DFS agent without it?

The reached set prevents the search algorithm from visiting the same state multiple times. It prevents cycles and unnecessary repeated exploration. Without it, DFS could get stuck in loops and repeatedly explore the same states instead of reaching the goal.

3. (Analyze) Compare the visual paths generated by BFS and DFS in your simulation. Why is BFS guaranteed to be optimal in this specific grid, whereas DFS produces winding, suboptimal routes?

BFS is guaranteed to be optimal because it explores states level by level. Since every movement in the grid has the same cost, the first solution found by BFS has the minimum number of steps. DFS explores deeply along one branch before backtracking, so it can find longer and winding paths and does not guarantee an optimal solution.

4. (Evaluate) If we scaled `visual\_grid\_game.py` up to a massive 1000x1000 grid, BFS and UCS might crash before finding food. According to the time and space complexity formulas from the lecture, contrast the memory bottlenecks of BFS versus DFS.

BFS has a major memory bottleneck because its space complexity is $O(b^d)$, meaning it stores many nodes in the frontier and memory grows exponentially. DFS uses much less memory, with space complexity $O(bm)$, because it mainly stores the current search path and alternatives. Therefore, on a massive 1000x1000 grid, BFS is more likely to run out of memory, while DFS can handle larger spaces but may take longer to find the food.

Once Completed Get a PDF of the completed File and Push into the Week 03 brach in the Github Project

Finalize and Lock Lab 03 Documentation

Incomplete: 0/11 questions answered. Please provide detailed responses for all questions.



FACULTY OF COMPUTING