



Objective & Lecture Mapping: In previous labs, we built a Simple Reflex Agent that moved randomly or reacted only to immediate adjacent cells. Today, we transition to a **Goal-Based/Planning Agent**. You will expose the environment's state space to the agent, allowing it to use **Breadth-First Search (BFS)**, **Depth-First Search (DFS)**, and **Uniform-Cost Search (UCS)** to simulate and find paths to the food before taking a physical action.

Part 1: Practical Implementation — Building the Search Agent

Step 1.1: Exposing the World Model

Classical search algorithms require an abstract model of the environment to simulate future states. Currently, your agent is "blind" to the overall map.

1. Create a new Branch called Week_03 in your Forked Github Repo and work on the below Questions.
2. Open `visual_grid_game.py` .
3. Locate the `get_percept(self)` method.
4. Add three new keys to the dictionary to pass the global state to the agent:

```
'grid_size': (self.width, self.height)
'walls': list(self.walls)
'all_food': list(self.food_positions)
```

Step 1.2: Implementing BFS, DFS, and UCS

You will implement three distinct uninformed search strategies. The core node expansion structure is identical; only the data structure for the **Frontier** changes!

1. Open `agent.py` and create a new class called `SearchAgent` .

2. Import required structures: `from collections import deque` and `import heapq` .
3. **BFS:** Create `def bfs_search(...)` . Use a FIFO queue (`deque.popleft()`). This explores the shallowest nodes first.
4. **DFS:** Create `def dfs_search(...)` . Use a LIFO stack (`list.pop()`). This explores the deepest nodes first.
5. **UCS:** Create `def ucs_search(...)` . Use a Priority Queue (`heapq.heappop()`) ordered by the total path cost $g(n)$.
6. For all three algorithms, you must maintain a `reached` set (or visited array) to track explored states. This converts your algorithm from a *Tree Search* to a *Graph Search*, preventing infinite loops.

Step 1.3: Executing and Comparing Offline Plans

The agent must now form a complete plan and execute it step-by-step.

1. In your `SearchAgent.__init__` , add an empty list: `self.plan = []` and a config string `self.active_algo = 'BFS'` .
2. In `sense_and_act(self, percept)` , check if `self.plan` is empty.
3. If empty, find the closest food pellet from `percept['all_food']` , execute the search method matching `self.active_algo` , and store the resulting sequence of actions in `self.plan` .
4. Return the first action from the plan using `return self.plan.pop(0)` .
5. **Observation Task:** Change `self.active_algo` between 'BFS', 'DFS', and 'UCS' and run the simulation. Watch how DFS takes erratic, winding paths, while BFS and UCS take direct, optimal paths!

Part 2: Theoretical Evaluation

Based on your implementation and Lecture 04, complete the following analytical questions.

1. (Remember) You built your search logic based on the environment coordinates. What is the fundamental difference between the "State Space" and the "Search Tree"?

The state space is the complete set of all possible states in the environment, such as every valid grid coordinate the agent can occupy. The search tree is the structure created by the search algorithm while exploring those states from the initial state. The same state can appear more than once in a search tree if it can be reached through different paths.

2. (Understand) In Step 1.2, you were instructed to use a `reached` set. In graph search theory, what specific problem does this set solve, and what would happen to your DFS agent without it?

The reached set stores the states that have already been visited. It prevents the search algorithm from exploring the same states repeatedly and converts the process from tree search into graph search. Without it, DFS could repeatedly move through cycles, waste time, and may fail to reach the goal efficiently.

3. (Analyze) Compare the visual paths generated by BFS and DFS in your simulation. Why is BFS guaranteed to be optimal in this specific grid, whereas DFS produces winding, suboptimal routes?

BFS explores nodes level by level, so it checks all shorter paths before longer ones. Since every movement in this grid has the same cost, the first path found by BFS is a shortest path. DFS explores one branch as deeply as possible before backtracking, so it can reach the goal through a longer and more winding route even when a shorter path exists.

4. (Evaluate) If we scaled `visual\_grid\_game.py` up to a massive 1000x1000 grid, BFS and UCS might crash before finding food. According to the time and space complexity formulas from the lecture, contrast the memory bottlenecks of BFS versus DFS.

BFS uses more memory because it must store many nodes from the current and next search levels at the same time. Its space complexity is approximately $O(b^d)$, where b is the branching factor and d is the depth of the shallowest solution. DFS is more memory efficient because it mainly stores the current path and some unexplored branches, with space complexity approximately $O(bm)$, where m is the maximum search depth. Therefore, on a very large grid, BFS is more likely to run out of memory than DFS.

Once Completed Get a PDF of the completed File and Push into the Week 03 brach in the Github Project

Finalize and Lock Lab 03 Documentation



FACULTY OF COMPUTING