Kularatne R.A.D | IT24103431

BSc (Hons) in **Computer Science**

SE3062 : Intelligent Systems

Year 3 · Semester 1 · 2026

Faculty of Computing

Practical 07

Module Objective: In previous weeks, your Drow Ranger agent used A* Search to find a physical path to the goal. However, it blindly assumed every non-wall tile was safe. Today, we implement a **Knowledge Base (KB)** and a **Forward Chaining Inference Engine**. Your agent must now mathematically prove a cell is logically *Feasible* before taking a step, using real-time rules about map vision and enemy threats.

Before you start: This lab continues the project from Labs 1–4. Open the same project and check that `SearchAgent.astar_search()` in `agent.py` works.

- Parts 1, 2 & 4: new files (`logic_engine.py` , `test_logic.py`) in the project folder.
- Part 3: edit your existing `agent.py` .
- **Create a separate branch `lab-07`** and start your work there. When finished, **commit your code and push the branch**, as you did in Labs 1–4.
- **Upload this worksheet's answered PDF to the submission portal.**

Part 1: The Logic Engine Architecture

Step 1.1: Building the Knowledge Base (KB)

> Instead of hardcoding hundreds of nested `if-else` statements in our agent's movement logic, we will build a declarative Knowledge Base. You need to design a Python class that stores **Facts** (current percepts) and **Rules** (Horn Clauses).

1. Create a new file named `logic_engine.py` .
2. Implement a `KnowledgeBase` class based on the following structural requirements:

```
CLASS KnowledgeBase:
    // Attributes
    DECLARE facts AS Set                  // To store unique string fact
    DECLARE rules AS List                 // To store rules as Tuples: (

    // Methods
    FUNCTION tell_fact(fact_string):
        ADD fact_string TO facts

    FUNCTION tell_rule(premise_list, conclusion_string):
        APPEND Tuple(premise_list, conclusion_string) TO rules

    FUNCTION clear_facts():
        EMPTY the facts Set
```

Part 2: Implementing Forward Chaining

Step 2.1: The Inference Algorithm

> The agent needs an Inference Engine to deduce new information from its raw sensors. Translate the following Data-Driven **Forward Chaining** algorithm into a Python method inside your `KnowledgeBase` class.

1. Write the `forward_chain()` method.
2. Ensure you use a `while` loop that continues to iterate over the rules until a full pass results in absolutely no new facts being deduced.

```
FUNCTION forward_chain():
    DECLARE new_facts_added = TRUE

    WHILE new_facts_added == TRUE:
        new_facts_added = FALSE

        FOR EACH (premises, conclusion) IN rules:
            IF conclusion IS NOT IN facts:
```

```
                // Modus Ponens Check
                IF ALL premises ARE IN facts:
                    ADD conclusion TO facts
                    new_facts_added = TRUE
```

Part 3: Hooking Logic into the Grid Game

Step 3.1: Defining the Game Constraints

> Now we translate the game's safety constraints into our logic engine using Propositional Logic.

1. In `agent.py`, add `from logic_engine import KnowledgeBase`, then create the KB in `SearchAgent.__init__`: `self.kb = KnowledgeBase()`.
2. Use your `tell_rule` method to define the following safety rules:
   Rule 1: `TargetVisible` ∧ `HasDust` ⇒ `SafeToEngage`
   Rule 2: `SafeToEngage` ∧ `BloodseekerMissing` ⇒ `Retreat`

The game does not produce these facts, so you supply them per tile as a dictionary: `{(x, y): [facts]}`. A tile where `Retreat` is deduced is unsafe to enter.

Step 3.2: Validating Feasibility in A*

> Modify your existing A* pathfinding algorithm to consult the Knowledge Base before expanding a node.

1. Add a parameter `tile_facts=None` to `astar_search()` (treat `None` as `{}`).
2. Locate the neighbor-generation loop in your A* code (where you normally check for physical walls).
3. Before adding a neighbor to the `open_list`, clear the KB facts.
4. Feed that tile's facts into the KB: `for fact in tile_facts.get(successor, []): self.kb.tell_fact(fact)`.
5. Run `self.kb.forward_chain()`.
6. If `'Retreat'` is deduced and exists in `self.kb.facts`, mark the tile as **Infeasible**. Skip it (do not add it to the open list), even if it is physically reachable.

Step 3.3: Run It in the Grid

1. In `sense_and_act()`, define sample facts and pass them to A*:

```
 tile_facts = {
    (1, 0): ['TargetVisible', 'HasDust', 'BloodseekerMissing'],  # dedu
    (0, 1): ['TargetVisible', 'HasDust'],                        # Safe
}
self.plan = self.astar_search(position, nearest_food, walls, grid_size,
```

2. Run `visual_grid_game.py`. The agent should never step onto `(1, 0)`.

Part 4: Self-Evaluation Test Cases

4.1 Automated Validation

Create a file named `test_logic.py`. Copy and run the following Python assert statements to verify your Forward Chaining engine works correctly mathematically before you attempt to integrate it into the visual grid.

```
 from logic_engine import KnowledgeBase

def test_forward_chaining():
    kb = KnowledgeBase()

    # Add Domain Rules
    kb.tell_rule(['TargetVisible', 'HasDust'], 'SafeToEngage')
    kb.tell_rule(['SafeToEngage', 'BloodseekerMissing'], 'Retreat')

    # Test Case 1: Safe Engagement
    kb.clear_facts()
    kb.tell_fact('TargetVisible')
    kb.tell_fact('HasDust')
    kb.forward_chain()
    assert 'SafeToEngage' in kb.facts, "Test 1 Failed: Should deduce Sa
    assert 'Retreat' not in kb.facts, "Test 1 Failed: Should NOT deduce

    # Test Case 2: Unsafe Engagement (Bloodseeker Missing)
    kb.clear_facts()
    kb.tell_fact('TargetVisible')
    kb.tell_fact('HasDust')
    kb.tell_fact('BloodseekerMissing')
    kb.forward_chain()
    assert 'Retreat' in kb.facts, "Test 2 Failed: Should deduce Retreat

    print("✅ All Logic Engine Test Cases Passed!")

if __name__ == "__main__":
    test_forward_chaining()
```

Part 5: Theory-to-Implementation Mapping

> Based on the code you just wrote and the lecture on Logical Reasoning, complete the following analytical questions to explain *how* your code implements the theory.

1. Reachability vs. Feasibility (Apply)

In Step 3.2, you modified the A* algorithm's neighbor-generation loop. How does your new code differentiate between checking if a node is "Reachable" (like a wall collision) versus checking if it is "Feasible"? Explain how the Knowledge Base enforces feasibility.

Reachability is the physical check: the successor must lie inside the grid and must not be a wall. Feasibility is a rule-based safety check performed after that. For each candidate tile, A* clears the KB's old facts, adds that tile's facts, and runs forward chaining. If the rules derive Retreat, A* skips the tile, even though the tile is reachable. The (1, 0) example is therefore blocked; (0, 1) remains available.

2. Declarative vs. Procedural Paradigms (Analyze)

Why did we build a `KnowledgeBase` class with a `forward_chain()` loop instead of simply writing `if 'TargetVisible' in percepts and 'HasDust' in percepts:` directly inside the agent's movement code? What happens to the agent's code complexity if we add 50 new game rules?

The KnowledgeBase stores rules separately from the movement algorithm. A* only asks whether Retreat was inferred, while forward_chain applies the same process to every rule and can use one conclusion as another rule's premise. With 50 new rules, we add entries to the rule list instead of adding 50 condition blocks to movement code. The inference work still grows with the rules, but the agent's control flow stays shorter and easier to change.

3. Modus Ponens & Horn Clauses (Understand)

The rule `['TargetVisible', 'HasDust'] ⇒ 'SafeToEngage'` is formally known as a Horn Clause. Briefly explain how your Python implementation of the `forward_chain()` `while` loop acts as a mathematical execution of the *Modus Ponens* inference rule.

The Horn clause says that TargetVisible and HasDust together imply SafeToEngage. The all() check tests whether both premises are already facts; when they are, forward_chain adds the conclusion. This is Modus Ponens applied by code. The while loop repeats complete passes until nothing new is added, allowing SafeToEngage to support the later BloodseekerMissing rule and derive Retreat.

Finalize and Lock Lab 07 Implementation



FACULTY OF COMPUTING