BSc (Hons) in **Information Technology Specialized in AI**

Faculty of Computing

IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Practical 04

Objective & Lecture Mapping: In previous labs, you explored Uninformed Search strategies like BFS and UCS inside `agent.py` [cite: 1]. Today, we transition to **Informed Search**. You will enhance your agent by implementing the **A* Search** algorithm, using **Heuristics** to drastically reduce the number of explored nodes in the `visual_grid_game.py` environment[cite: 4]. You will start with basic heuristic functions and connect them to your search logic.

Part 1: Practical Implementation — Building the A* Agent

Step 1.1: Implementing the Heuristic Functions

> Informed search algorithms require a heuristic function, h(n), which estimates the cheapest path from the current node to the goal. You will calculate distance metrics on a 2D grid.

1. Create a new Branch called Week_04 in your Forked Github Repo.
2. Open `agent.py` and locate your `SearchAgent` class[cite: 1].
3. Add a new method named `def manhattan_distance(self, pos, goal):` that calculates the distance using the formula h(n) = |x_1 - x_2| + |y_1 - y_2| and returns the integer value.
4. Add a second method named `def euclidean_distance(self, pos, goal):` that calculates the straight-line distance using the formula h(n) = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2}. You will need to `import math` for this.
5. *Testing Checkpoint:* Print the outputs of both functions for a mock start position (0, 0) and goal (3, 4) to verify that Manhattan returns 7 and Euclidean returns 5.0.

Step 1.2: Implementing A* Search

> A* evaluates nodes by combining the path cost so far, g(n), and the estimated cost to the goal, h(n). The evaluation function is f(n) = g(n) + h(n).

1. Inside `SearchAgent`, create a new method: `def astar_search(self, start_pos, goal_pos, walls, grid_size, heuristic_type='manhattan')`.
2. Initialize an empty priority queue using `heapq` and an empty set for `reached_states`.
3. Push the initial state into the priority queue. Unlike UCS which only uses g(n), your A* tuple must be formatted as: `(f_cost, g_cost, current_pos, path_taken)`. For the starting node, g(n) = 0. Calculate h(n) using your chosen heuristic method, and set f(n) = g(n) + h(n).
4. Create your standard `while` loop to process the queue. Pop the node with the lowest `f_cost`. If `current_pos == goal_pos`, return the `path_taken`. Otherwise, add `current_pos` to `reached_states`.
5. For node expansion, check the four adjacent cells (Up, Down, Left, Right). For each valid neighbor (not a wall, within bounds, and not reached): Calculate g_{new} = g_{current} + 1, h_{new} using your heuristic, and f_{new} = g_{new} + h_{new}. Push the new tuple to the priority queue.

Step 1.3: Integrating A* into the Agent's Decision Loop

> Finally, you need to connect your new search algorithm to the agent's perception and action loop so it can run in the visual environment.

1. Navigate to the `sense_and_act(self, percept)` method in your `SearchAgent`.
2. Add an `elif self.active_algo == 'AStar':` block to handle the new algorithm alongside your existing BFS/DFS/UCS.
3. Extract the necessary global state from the percept dictionary (e.g., `percept['remaining_food']`).
4. Find the closest food item to act as the `goal_pos`. Call your `astar_search` method and store the returned list of actions in `self.plan`.
5. Open `visual_grid_game.py` and modify the `GridGameGUI` initialization to inject your `SearchAgent()` instead of the `ModelBasedAgent()`. Run the simulation and observe the optimized pathfinding!

Part 2: Theoretical Evaluation

> Based on your implementation and Lecture 05, complete the following analytical questions.

1. (Understand) What is the key difference between how Uniform-Cost Search (UCS) and A* Search prioritize which node to explore next?

UCS only looks at g(n), the cost so far, so it expands outward in all directions equally like ripples in a pond. A* uses f(n) = g(n) + h(n), so the heuristic pulls it to prioritize nodes that seem closer to the goal, letting it skip large chunks of the map UCS would have wasted time exploring.

2. (Analyze) In Step 1.1, you used Manhattan Distance. Why is Manhattan Distance considered an "admissible" heuristic for this specific 4-way movement grid, and what would happen to your A* algorithm if the heuristic was NOT admissible?

Manhattan distance is admissible here because on a 4-way grid, every single step can only reduce the straight x or y distance by at most 1, so it can never overestimate the true number of steps needed. If the heuristic were not admissible (it overestimated at some point), A* could skip over the actual optimal path in favor of a worse one that just looked cheaper, so it would no longer be guaranteed to find the shortest path.

3. (Evaluate) If we modified `visual_grid_game.py` to allow the agent to move diagonally (8-way movement), would Manhattan distance still be an admissible heuristic? Why or why not? Which metric should you switch to?

No, Manhattan distance would no longer be admissible with 8-way movement, because a diagonal move covers both an x and y step in a single move, so Manhattan distance would overestimate the true cost by counting those as two separate steps. I would switch to Euclidean distance, or better, Chebyshev distance, since diagonal movement matches straight-line movement more closely.

4. (Create) When targeting multiple food items simultaneously, calculating the distance to just the single closest food item is a weak heuristic. Propose (in text) a stronger heuristic for navigating the grid to eat ALL remaining food efficiently.

A stronger heuristic would be the maximum Manhattan distance to any remaining food pellet, rather than just the closest one, since the agent still has to eventually reach the farthest pellet no matter what order it visits them in, so that distance is a hard lower bound on the total remaining cost. An even stronger version would estimate a rough minimum spanning tree distance connecting all remaining food pellets, since that better reflects the actual cost of visiting all of them rather than just the single farthest one.

Once Completed Get a PDF of the completed File and Push into the Week 04 branch in the Github Project

Finalize and Lock Lab 04 Documentation

Incomplete: {filledCount}/{fields.length} questions answered. Please provide detailed responses for all questions.



FACULTY OF COMPUTING