BSc (Hons) in **Computer Science**

SE3062 : Intelligent Systems

Year 3 · Semester 1 · 2026

Faculty of Computing

Practical 07

> **Module Objective:** In previous weeks, your Drow Ranger agent used A* Search to find a physical path to the goal. However, it blindly assumed every non-wall tile was safe. Today, we implement a **Knowledge Base (KB)** and a **Forward Chaining Inference Engine**. Your agent must now mathematically prove a cell is logically *Feasible* before taking a step, using real-time rules about map vision and enemy threats.

> **Before you start:** This lab continues the project from Labs 1–4. Open the same project and check that `SearchAgent.astar_search()` in `agent.py` works.
>
> - Parts 1, 2 & 4: new files (`logic_engine.py` , `test_logic.py`) in the project folder.
> - Part 3: edit your existing `agent.py` .
> - **Create a separate branch `lab-07`** and start your work there. When finished, **commit your code and push the branch**, as you did in Labs 1–4.
> - **Upload this worksheet's answered PDF to the submission portal.**

Part 1: The Logic Engine Architecture

Step 1.1: Building the Knowledge Base (KB)

> Instead of hardcoding hundreds of nested `if-else` statements in our agent's movement logic, we will build a declarative Knowledge Base. You need to design a Python class that stores **Facts** (current percepts) and **Rules** (Horn Clauses).

1. Create a new file named `logic_engine.py` .
2. Implement a `KnowledgeBase` class based on the following structural requirements:

```
CLASS KnowledgeBase:
   // Attributes
```

```
DECLARE facts AS Set                    // To store unique string fact
DECLARE rules AS List                   // To store rules as Tuples: (

// Methods
FUNCTION tell_fact(fact_string):
    ADD fact_string TO facts

FUNCTION tell_rule(premise_list, conclusion_string):
    APPEND Tuple(premise_list, conclusion_string) TO rules

FUNCTION clear_facts():
    EMPTY the facts Set
```

Part 2: Implementing Forward Chaining

Step 2.1: The Inference Algorithm

> The agent needs an Inference Engine to deduce new information from its raw sensors. Translate the following Data-Driven **Forward Chaining** algorithm into a Python method inside your `KnowledgeBase` class.

1. Write the `forward_chain()` method.
2. Ensure you use a `while` loop that continues to iterate over the rules until a full pass results in absolutely no new facts being deduced.

```
FUNCTION forward_chain():
   DECLARE new_facts_added = TRUE

   WHILE new_facts_added == TRUE:
       new_facts_added = FALSE

       FOR EACH (premises, conclusion) IN rules:
           IF conclusion IS NOT IN facts:

               // Modus Ponens Check
               IF ALL premises ARE IN facts:
```

```
            ADD conclusion TO facts
            new_facts_added = TRUE
```

Part 3: Hooking Logic into the Grid Game

Step 3.1: Defining the Game Constraints

> Now we translate the game's safety constraints into our logic engine using Propositional Logic.

1. In `agent.py`, add `from logic_engine import KnowledgeBase`, then create the KB in `SearchAgent.__init__`: `self.kb = KnowledgeBase()`.
2. Use your `tell_rule` method to define the following safety rules:
   Rule 1: `TargetVisible ∧ HasDust ⇒ SafeToEngage`
   Rule 2: `SafeToEngage ∧ BloodseekerMissing ⇒ Retreat`

The game does not produce these facts, so you supply them per tile as a dictionary: `{(x, y): [facts]}`. A tile where `Retreat` is deduced is unsafe to enter.

Step 3.2: Validating Feasibility in A*

> Modify your existing A* pathfinding algorithm to consult the Knowledge Base before expanding a node.

1. Add a parameter `tile_facts=None` to `astar_search()` (treat `None` as `{}`).
2. Locate the neighbor-generation loop in your A* code (where you normally check for physical walls).
3. Before adding a neighbor to the `open_list`, clear the KB facts.
4. Feed that tile's facts into the KB: `for fact in tile_facts.get(successor, []): self.kb.tell_fact(fact)`.
5. Run `self.kb.forward_chain()`.
6. If `'Retreat'` is deduced and exists in `self.kb.facts`, mark the tile as **Infeasible**. Skip it (do not add it to the open list), even if it is physically reachable.

Step 3.3: Run It in the Grid

1. In `sense_and_act()`, define sample facts and pass them to A*:

```
tile_facts = {
    (1, 0): ['TargetVisible', 'HasDust', 'BloodseekerMissing'],  # dedu
    (0, 1): ['TargetVisible', 'HasDust'],                        # Safe
}
self.plan = self.astar_search(position, nearest_food, walls, grid_size,
```

2. Run `visual_grid_game.py`. The agent should never step onto `(1, 0)`.

Part 4: Self-Evaluation Test Cases

4.1 Automated Validation

Create a file named `test_logic.py`. Copy and run the following Python assert statements to verify your Forward Chaining engine works correctly mathematically before you attempt to integrate it into the visual grid.

```
from logic_engine import KnowledgeBase

def test_forward_chaining():
    kb = KnowledgeBase()

    # Add Domain Rules
    kb.tell_rule(['TargetVisible', 'HasDust'], 'SafeToEngage')
    kb.tell_rule(['SafeToEngage', 'BloodseekerMissing'], 'Retreat')

    # Test Case 1: Safe Engagement
    kb.clear_facts()
    kb.tell_fact('TargetVisible')
    kb.tell_fact('HasDust')
    kb.forward_chain()
    assert 'SafeToEngage' in kb.facts, "Test 1 Failed: Should deduce Sa
    assert 'Retreat' not in kb.facts, "Test 1 Failed: Should NOT deduce

    # Test Case 2: Unsafe Engagement (Bloodseeker Missing)
    kb.clear_facts()
```

```
    kb.tell_fact('TargetVisible')
    kb.tell_fact('HasDust')
    kb.tell_fact('BloodseekerMissing')
    kb.forward_chain()
    assert 'Retreat' in kb.facts, "Test 2 Failed: Should deduce Retreat

    print("✅ All Logic Engine Test Cases Passed!")

if __name__ == "__main__":
    test_forward_chaining()
```

Part 5: Theory-to-Implementation Mapping

> Based on the code you just wrote and the lecture on Logical Reasoning, complete the following analytical questions to explain *how* your code implements the theory.

1. Reachability vs. Feasibility (Apply)

In Step 3.2, you modified the A* algorithm's neighbor-generation loop. How does your new code differentiate between checking if a node is "Reachable" (like a wall collision) versus checking if it is "Feasible"? Explain how the Knowledge Base enforces feasibility.

There are two checks within my A* neighbor loop; reachability and feasibility. Reachability is the physical check performed using the grid boundary condition and the if new_pos in walls: continue which checks whether the agent can physically enter the tile. Feasibility is the logical check which follows the physical check. I use kb.clear_facts() to clear the knowledge base and feed the facts of the particular tile by using the tile_facts function followed by kb.forward_chain(). If the result of 'Retreat' is derived from this function and if it exists within kb.facts then I continue the loop and therefore never add the tile into the open list even though it is physically reachable. The knowledge base performs feasibility check using the rules of (TargetVisible ∧ HasDust -> SafeToEngage) and (SafeToEngage ∧ BloodseekerMissing -> Retreat).

2. Declarative vs. Procedural Paradigms (Analyze)

Why did we build a `KnowledgeBase` class with a `forward_chain()` loop instead of simply writing `if 'TargetVisible' in percepts and 'HasDust' in`

`percepts:` directly inside the agent's movement code? What happens to the agent's code complexity if we add 50 new game rules?

The separation between Knowledge Base is done between the knowledge of the agent (knowledge of facts and rules) and how it thinks (the generic forward_chain()). In the hardcoded version if 'TargetVisible' in percepts and 'HasDust' in percepts: the rules will be embedded within the movement code. For chaining rules like SafeToEngage -> Retreat, we have to do nested if-else statements in the correct order. Adding a new rule means that we will have to modify and test the agent again. If we added 50 new rules, then our procedural agent will become big, complicated, and prone to errors. In our KB version, we just added 50 tell_rule(...)'s and forward_chain() remains unchanged because it loops until no more new facts are generated.

3. Modus Ponens & Horn Clauses (Understand)

The rule `['TargetVisible', 'HasDust'] ⇒ 'SafeToEngage'` is formally known as a Horn Clause. Briefly explain how your Python implementation of the `forward_chain()` `while` loop acts as a mathematical execution of the *Modus Ponens* inference rule.

According to Modus Ponens, if P is true and P -> Q is true, then Q is true. A rule such as ['TargetVisible', 'HasDust'] -> 'SafeToEngage' is an example of a Horn clause where a number of premises are conjoined and there is only one conclusion. The line of code all(p in self.facts for p in premises) in forward_chain() checks whether each premise is a fact. If yes, the rule is triggered and self.facts.add(conclusion) makes the conclusion a new fact and that is exactly one application of Modus Ponens. This is done repeatedly inside the outer while loop till no new facts are added during a full iteration (fixed point). This allows a conclusion like SafeToEngage to be used as a premise in another rule to get Retreat.

Git repo Link- https://github.com/IT24103469/IT3012---Practical-Base/tree/IT24103469Lab7

Finalize and Lock Lab 07 Implementation

✅ **Lab 05 Theory-to-Implementation Mapping completed!**



FACULTY OF COMPUTING