

BSc (Hons) in **Computer Science****SE3062 : Intelligent Systems**

Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing**Practical 01**

Objective & Lecture Mapping: Recall that an intelligent agent acts within a continuous loop: Sensors generate percept sequences, and Actuators execute actions to maximize a Performance measure. Use this sheet to execute practical modifications and incrementally evaluate your design against Lecture 01 and 02 theory (from basic recall to analytical classification).

Part 1: Code Analysis & PEAS Evaluation**Task 0 : Setting up and getting the starter Code**

1. Go to the [Git Hub Repo](#). Create a Fork of this Git Repo to your Personal Github Profile. Open it using your favourite IDE and follow the below instruction to complete the practical. The base code is in the "master" brach of the repo.

Task 1.1: The Environment State (__init__)

1. (Remember) List the four components of the PEAS framework discussed in Lecture 01.

Performance Measure, Environment, Actuators, Sensors

2. (Understand) Look at the `VisualGridHuntGame.__init__` method. Which specific variables in this code represent the physical "Environment (E)" state?

`self.width, self.height, self.agent_pos, self.walls, self.food_positions, self.opponents, self.score, self.steps, self.collison`

3. (Analyze) Based on the variables initialized (specifically `self.opponents`), classify this baseline environment as "Single-Agent" or "Multi-Agent". Briefly justify your choice.

Because `self.opponents = []` is a list. It creates other agents in the environment. These opponents move independently and affect the main agent through collisions.

Task 1.2: The Perception Subsystem (`get_percept`)

4. (Remember) Define what a "percept sequence" is according to Lecture 01.

A percept sequence is the complete history of all observations received by an agent through its sensors over time.

5. (Understand) Which component of the PEAS framework does the `get_percept()` method represent in our code?

Sensors
Because `def get_percept(self)` returns information the agent receives from the environment.

6. (Evaluate) Based on the exact dictionary returned by `get_percept()` , is this environment "Fully Observable" or "Partially Observable"? Explain why based on what the agent can and cannot see.

Partially Observable
Because it doesn't know the details about the complete environment. It can only observe current details only.

Task 1.3: Action Execution (`execute_action`)

7. (Understand) When `execute_action()` deducts points for hitting a wall, which PEAS component is being actively updated?

Performance Measure

Because it measure the score continuously to calculate the performance

8. (Evaluate) Why is it structurally important that this metric evaluates changes in the external environment state (hitting a wall) rather than the agent's internal processing effort?

Intelligent agents should be evaluated based on their success in changing the external environment. The goal is to achieve the best result.

Part 2: Guided Modification & Deep Theory Mapping

Follow the implementation instructions to inject a new hazard, then answer the questions to map your code changes back to the theoretical nature of the environment.

Step 2.1: Extending the Environment Initialization (`__init__`)

1. **Implementation Instructions:** Declare a new trap collection attribute (e.g., `self.toxic_traps = set()`) inside `__init__`. Populate it with coordinate tuples safely avoiding position `(0, 0)`, walls, and food.

9. (Understand) If you successfully add `self.toxic_traps` to the environment but intentionally **hide** this data from the agent's sensors, how does this specifically alter the environment's "Observability" classification?

it may happens because the environment becomes partially observable. Because the agent cannot access all important information needed for decision making.

Step 2.2: Updating the Perception Subsystem (`get_percept`)

1. **Implementation Instructions:** Locate `get_percept(self)` and add a new boolean sensor key (e.g., `'smells_toxin': tuple(self.agent_pos) in self.toxic_traps`) to the dictionary returned to the agent loop.

10. (Analyze) By adding `'smells_toxin'`, you expand the agent's percept sequence. Explain how this specific sensor helps the agent act with "Rationality" (maximizing expected utility).

The toxin sensor gives the agent additional environmental information. This allows the agent to get some idea about dangerous cells and select actions that maximize expected utility.

Step 2.3: Modifying Action Execution & Visual Rendering (`execute_action` & `draw_grid`)

1. **Implementation Instructions:** In `execute_action`, check if the updated `self.agent_pos` intersects with `self.toxic_traps` to decrement `self.score` by 15 points. In `draw_grid`, iterate through traps to render custom purple shapes on the canvas.

11. (Remember) You programmed a severe score penalty for stepping on a trap to avoid metric exploitation. What was the classic "Vacuum World Exploit" example discussed in Lecture 01 that illustrated the danger of faulty metrics?

The vacuum world exploit was that an agent could repeatedly clean the same location to increase its score without actually improving the environment. So, the agent start to update the metrics by staying in the same trap and it creates a loop. This showed that badly designed performance measures can encourage incorrect

Finalize and Lock Lab 01 Analytical Evaluation



FACULTY OF COMPUTING