



BSc (Hons) in **Information Technology**
Specialized in AI

IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing

Practical 01

Objective & Lecture Mapping: Recall that an intelligent agent acts within a continuous loop: Sensors generate percept sequences, and Actuators execute actions to maximize a Performance measure. Use this sheet to execute practical modifications and incrementally evaluate your design against Lecture 01 and 02 theory (from basic recall to analytical classification).

Part 1: Code Analysis & PEAS Evaluation

Task 0 : Setting up and getting the starter Code

1. Go to the [Git Hub Repo](#). Create a Fork of this Git Repo to your Personal Github Profile. Open it using your favourite IDE and follow the below instruction to complete the practical. The base code is in the "master" branch of the repo.

Task 1.1: The Environment State (`_init_`)

1. (Remember) List the four components of the PEAS framework discussed in Lecture 01.

P - performance measure
E - environment
A - actuators
S - sensors

2. (Understand) Look at the `VisualGridHuntGame.__init__` method. Which specific variables in this code represent the physical "Environment (E)" state?

`self.width, self.height, self.agent_pos, self.walls, self.food_positions, self.opponents, self.collison`

3. (Analyze) Based on the variables initialized (specifically `self.opponents`), classify this baseline environment as "Single-Agent" or "Multi-Agent". Briefly justify your choice.

Multi-Agent
Environment has the `self.opponents` variable. That variable stores one or more opponents that move independently of the main agent.

Task 1.2: The Perception Subsystem (`get_percept`)

4. (Remember) Define what a "percept sequence" is according to Lecture 01.

The absolute, cumulative historical log of every single percept the agent has received from its initialization up to the current moment

5. (Understand) Which component of the PEAS framework does the `get_percept()` method represent in our code?

Sensors

6. (Evaluate) Based on the exact dictionary returned by `get_percept()` , is this environment "Fully Observable" or "Partially Observable"? Explain why based on what the agent can and cannot see.

Fully Observable
The `get_percept()` method provides the agent with all important information about the environment.

Task 1.3: Action Execution (`execute_action`)

7. (Understand) When `execute_action()` deducts points for hitting a wall, which PEAS component is being actively updated?

Performance measure

8. (Evaluate) Why is it structurally important that this metric evaluates changes in the external environment state (hitting a wall) rather than the agent's internal processing effort?

The performance measure should evaluate the results of the agent's actions in the environment, not how much computation the agent performs internally. This is important because internal processing time or algorithm complexity does not necessarily indicate successful behavior.

Part 2: Guided Modification & Deep Theory Mapping

Follow the implementation instructions to inject a new hazard, then answer the questions to map your code changes back to the theoretical nature of the environment.

Step 2.1: Extending the Environment Initialization (`__init__`)

1. **Implementation Instructions:** Declare a new trap collection attribute (e.g., `self.toxic_traps = set()`) inside `__init__`. Populate it with coordinate tuples safely avoiding position `(0, 0)`, walls, and food.

9. (Understand) If you successfully add `self.toxic_traps` to the environment but intentionally **hide** this data from the agent's sensors, how does this specifically alter the environment's "Observability" classification?

The environment becomes Partially Observable.

If toxic traps exist in the environment but are not included in the agent's percepts, the agent cannot directly observe them before stepping on them.

As a result:

Part of the environment state is hidden.

The agent must make decisions without complete information.

Therefore, the environment changes from fully observable to partially observable.

Step 2.2: Updating the Perception Subsystem (get_percept)

1. **Implementation Instructions:** Locate `get_percept(self)` and add a new boolean sensor key (e.g., `'smells_toxin': tuple(self.agent_pos)` in `self.toxic_traps`) to the dictionary returned to the agent loop.

10. (Analyze) By adding `'smells_toxin'` , you expand the agent's percept sequence. Explain how this specific sensor helps the agent act with "Rationality" (maximizing expected utility).

It gives the agent additional information about nearby hazards. This helps the agent to detect dangerous locations, avoid stepping on toxic traps, reduce score penalties, choose safer actions.

Step 2.3: Modifying Action Execution & Visual Rendering (execute_action & draw_grid)

1. **Implementation Instructions:** In `execute_action` , check if the updated `self.agent_pos` intersects with `self.toxic_traps` to decrement `self.score` by 15 points. In `draw_grid` , iterate through traps to render custom purple shapes on the canvas.

11. (Remember) You programmed a severe score penalty for stepping on a trap to avoid metric exploitation. What was the classic "Vacuum World Exploit" example discussed in Lecture 01 that illustrated the danger of faulty metrics?

The Vacuum World Exploit is when the vacuum agent keeps making the floor dirty and then cleaning it again to earn more points. It shows that if the performance measure is poorly designed, the agent may find ways to increase its score without actually achieving the real goal. That's why your trap penalty helps encourage the correct behavior avoiding dangerous traps instead of exploiting the scoring system.

Finalize and Lock Lab 01 Analytical Evaluation



FACULTY OF COMPUTING