



BSc (Hons) in **Information Technology**
Specialized in AI

IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing

Practical 01

Objective & Lecture Mapping: Recall that an intelligent agent acts within a continuous loop: Sensors generate percept sequences, and Actuators execute actions to maximize a Performance measure. Use this sheet to execute practical modifications and incrementally evaluate your design against Lecture 01 and 02 theory (from basic recall to analytical classification).

Part 1: Code Analysis & PEAS Evaluation

Task 0 : Setting up and getting the starter Code

1. Go to the [Git Hub Repo](#). Create a Fork of this Git Repo to your Personal Github Profile. Open it using your favourite IDE and follow the below instruction to complete the practical. The base code is in the "master" branch of the repo.

Task 1.1: The Environment State (`__init__`)

1. (Remember) List the four components of the PEAS framework discussed in Lecture 01.

P – Performance Measure
E – Environment
A – Actuators

2. (Understand) Look at the `VisualGridHuntGame.__init__` method. Which specific variables in this code represent the physical "Environment (E)" state?

```
self.walls  
self.food_positions  
self.opponents
```

3. (Analyze) Based on the variables initialized (specifically `self.opponents`), classify this baseline environment as "Single-Agent" or "Multi-Agent". Briefly justify your choice.

This is multi - agent environment because self-opponents stores other agents (opponents) in the environment in addition to the main player agent.

Task 1.2: The Perception Subsystem (`get_percept`)

4. (Remember) Define what a "percept sequence" is according to Lecture 01.

A percept sequence is the complete history of everything an agent has perceived through it's sensors up to a given point in the time.

5. (Understand) Which component of the PEAS framework does the `get_percept()` method represent in our code?

Sensors

6. (Evaluate) Based on the exact dictionary returned by `get_percept()` , is this environment "Fully Observable" or "Partially Observable"? Explain why based on what the agent can and cannot see.

The environment is partially observable because the agent can only see food and walls at it's current position.
The agent cannot see where food or walls are located anywhere else on the grid

Task 1.3: Action Execution (`execute_action`)

7. (Understand) When `execute_action()` deducts points for hitting a wall, which PEAS component is being actively updated?

Performance

8. (Evaluate) Why is it structurally important that this metric evaluates changes in the external environment state (hitting a wall) rather than the agent's internal processing effort?

Because the agents goal is to maximize score by interacting with the external world, not by performing computations.

Part 2: Guided Modification & Deep Theory Mapping

Follow the implementation instructions to inject a new hazard, then answer the questions to map your code changes back to the theoretical nature of the environment.

Step 2.1: Extending the Environment Initialization (`__init__`)

1. **Implementation Instructions:** Declare a new trap collection attribute (e.g., `self.toxic_traps = set()`) inside `__init__`. Populate it with coordinate tuples safely avoiding position `(0, 0)`, walls, and food.

9. (Understand) If you successfully add `self.toxic_traps` to the environment but intentionally **hide** this data from the agent's sensors, how does this specifically alter the environment's "Observability" classification?

It makes the environment partially observable.

Why: the full state includes trap locations, but the agent's percepts don't include

Step 2.2: Updating the Perception Subsystem (`get_percept`)

1. **Implementation Instructions:** Locate `get_percept(self)` and add a new boolean sensor key (e.g., `'smells_toxin': tuple(self.agent_pos) in self.toxic_traps`) to the dictionary returned to the agent loop.

10. (Analyze) By adding `'smells_toxin'`, you expand the agent's percept sequence. Explain how this specific sensor helps the agent act with "Rationality" (maximizing expected utility).

Adding smells_toxin helps rationality because the agent now gets useful warning information about danger.
So instead of moving blindly, it can avoid trap cells, reduce heavy penalties, survive longer, and collect more food overall.

Step 2.3: Modifying Action Execution & Visual Rendering (`execute_action` & `draw_grid`)

1. **Implementation Instructions:** In `execute_action`, check if the updated `self.agent_pos` intersects with `self.toxic_traps` to decrement `self.score` by 15 points. In `draw_grid`, iterate through traps to render custom purple shapes on the canvas.

11. (Remember) You programmed a severe score penalty for stepping on a trap to avoid metric exploitation. What was the classic "Vacuum World Exploit" example discussed in Lecture 01 that illustrated the danger of faulty metrics?

The classic exploit was an agent that keeps dropping dirt and re-cleaning it to keep increasing its performance score, instead of actually maintaining a clean environment efficiently.

Finalize and Lock Lab 01 Analytical Evaluation

Incomplete: 10/11 questions answered. Please provide detailed responses for all questions.

