

BSc (Hons) in **Computer Science****SE3062 : Intelligent Systems**

Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing**Practical 01**

Objective & Lecture Mapping: Recall that an intelligent agent acts within a continuous loop: Sensors generate percept sequences, and Actuators execute actions to maximize a Performance measure. Use this sheet to execute practical modifications and incrementally evaluate your design against Lecture 01 and 02 theory (from basic recall to analytical classification).

Part 1: Code Analysis & PEAS Evaluation**Task 0 : Setting up and getting the starter Code**

1. Go to the [Git Hub Repo](#). Create a Fork of this Git Repo to your Personal Github Profile. Open it using your favourite IDE and follow the below instruction to complete the practical. The base code is in the "master" brach of the repo.

Task 1.1: The Environment State (`_init_`)

1. (Remember) List the four components of the PEAS framework discussed in Lecture 01.

- 1.Performance measure
- 2.Environment
- 3.Actuators
- 4.Sensors

2. (Understand) Look at the `VisualGridHuntGame.__init__` method. Which specific variables in this code represent the physical "Environment (E)" state?

```
self.width  
self.height  
self.agent_pos  
self.food_positions  
self.walls  
self.opponents
```

3. (Analyze) Based on the variables initialized (specifically `self.opponents`), classify this baseline environment as "Single-Agent" or "Multi-Agent". Briefly justify your choice.

Multi-Agent
Because opponents variable tracks multiple entities within same shared environment.

Task 1.2: The Perception Subsystem (`get_percept`)

4. (Remember) Define what a "percept sequence" is according to Lecture 01.

Percept sequence is a historical log of every percept that agent has received from the beginning to the current moment.

5. (Understand) Which component of the PEAS framework does the `get_percept()` method represent in our code?

Sensors component

6. (Evaluate) Based on the exact dictionary returned by `get_percept()`, is this environment "Fully Observable" or "Partially Observable"? Explain why based on what the agent can and cannot see.

Partially Observable

Agent can see available food source but cannot see the exact food agent have to find it ,agent only knows where it is.

Task 1.3: Action Execution (execute_action)

7. (Understand) When `execute_action()` deducts points for hitting a wall, which PEAS component is being actively updated?

Performance Measure

8. (Evaluate) Why is it structurally important that this metric evaluates changes in the external environment state (hitting a wall) rather than the agent's internal processing effort?

Deducting points updates the performance measure, which must evaluate external environment changes rather than internal processing effort because an agent's rationality is judged by real-world task success rather than its internal computational costs.

Part 2: Guided Modification & Deep Theory Mapping

Follow the implementation instructions to inject a new hazard, then answer the questions to map your code changes back to the theoretical nature of the environment.

Step 2.1: Extending the Environment Initialization (`__init__`)

1. **Implementation Instructions:** Declare a new trap collection attribute (e.g., `self.toxic_traps = set()`) inside `__init__` . Populate it with coordinate tuples

safely avoiding position $(0, 0)$, walls, and food.

9. (Understand) If you successfully add `self.toxic_traps` to the environment but intentionally **hide** this data from the agent's sensors, how does this specifically alter the environment's "Observability" classification?

Partially Observable.

Agent can't perceive where traps are located until it interacts with them. Because sensors are hidden from the sensors.

Step 2.2: Updating the Perception Subsystem (`get_percept`)

1. **Implementation Instructions:** Locate `get_percept(self)` and add a new boolean sensor key (e.g., `'smells_toxin': tuple(self.agent_pos) in self.toxic_traps`) to the dictionary returned to the agent loop.

10. (Analyze) By adding `'smells_toxin'`, you expand the agent's percept sequence. Explain how this specific sensor helps the agent act with "Rationality" (maximizing expected utility).

Adding the `smells_toxin` sensor expands the agent's percept sequence enabling it to detect hidden hazards and act rationally by choosing actions that avoid penalties and maximize its expected performance score.

Step 2.3: Modifying Action Execution & Visual Rendering (`execute_action` & `draw_grid`)

1. **Implementation Instructions:** In `execute_action`, check if the updated `self.agent_pos` intersects with `self.toxic_traps` to decrement `self.score` by 15 points. In `draw_grid`, iterate through traps to render custom purple shapes on the canvas.

11. (Remember) You programmed a severe score penalty for stepping on a trap to avoid metric exploitation. What was the classic "Vacuum World Exploit" example discussed in Lecture 01 that illustrated the danger of faulty metrics?

The vacuum world exploit was that an agent could repeatedly clean the same locations to increase its score without actually improving the environment. Because of that, the agent starts to update the metrics by staying the same location and it creates a loop. This shows that badly designed performance measures can encourage incorrect behavior.

Finalize and Lock Lab 01 Analytical Evaluation



FACULTY OF COMPUTING