



Objective & Lecture Mapping: In previous labs, we built a Simple Reflex Agent that moved randomly or reacted only to immediate adjacent cells. Today, we transition to a **Goal-Based/Planning Agent**. You will expose the environment's state space to the agent, allowing it to use **Breadth-First Search (BFS)**, **Depth-First Search (DFS)**, and **Uniform-Cost Search (UCS)** to simulate and find paths to the food before taking a physical action.

Part 1: Practical Implementation — Building the Search Agent

Step 1.1: Exposing the World Model

Classical search algorithms require an abstract model of the environment to simulate future states. Currently, your agent is "blind" to the overall map.

1. Create a new Branch called Week_03 in your Forked Github Repo and work on the below Questions.
2. Open `visual_grid_game.py` .
3. Locate the `get_percept(self)` method.
4. Add three new keys to the dictionary to pass the global state to the agent:

```
'grid_size': (self.width, self.height)
'walls': list(self.walls)
'all_food': list(self.food_positions)
```

Step 1.2: Implementing BFS, DFS, and UCS

You will implement three distinct uninformed search strategies. The core node expansion structure is identical; only the data structure for the **Frontier** changes!

1. Open `agent.py` and create a new class called `SearchAgent` .
2. Import required structures: `from collections import deque` and `import heapq` .
3. **BFS:** Create `def bfs_search(...)` . Use a FIFO queue (`deque.popleft()`). This explores the shallowest nodes first.
4. **DFS:** Create `def dfs_search(...)` . Use a LIFO stack (`list.pop()`). This explores the deepest nodes first.
5. **UCS:** Create `def ucs_search(...)` . Use a Priority Queue (`heapq.heappop()`) ordered by the total path cost $g(n)$.
6. For all three algorithms, you must maintain a `reached` set (or visited array) to track explored states. This converts your algorithm from a *Tree Search* to a *Graph Search*, preventing infinite loops.

Step 1.3: Executing and Comparing Offline Plans

The agent must now form a complete plan and execute it step-by-step.

1. In your `SearchAgent.__init__` , add an empty list: `self.plan = []` and a config string `self.active_algo = 'BFS'` .
2. In `sense_and_act(self, percept)` , check if `self.plan` is empty.
3. If empty, find the closest food pellet from `percept['all_food']` , execute the search method matching `self.active_algo` , and store the resulting sequence of actions in `self.plan` .
4. Return the first action from the plan using `return self.plan.pop(0)` .
5. **Observation Task:** Change `self.active_algo` between 'BFS', 'DFS', and 'UCS' and run the simulation. Watch how DFS takes erratic, winding paths, while BFS and UCS take direct, optimal paths!

Part 2: Theoretical Evaluation

Based on your implementation and Lecture 04, complete the following analytical questions.

1. (Remember) You built your search logic based on the environment coordinates. What is the fundamental difference between the "State Space" and the "Search Tree"?

- **State Space:** The physical set of all distinct configurations in the environment.
- **Search Tree:** The tree graph of possible pathways constructed during exploration starting from the root node. Multiple nodes in a search tree can correspond to the exact same state in the state space if reached via different paths

2. (Understand) In Step 1.2, you were instructed to use a `reached` set. In graph search theory, what specific problem does this set solve, and what would happen to your DFS agent without it?

- **Purpose:** Converts a tree search into a graph search by recording visited states, preventing infinite loops.
- **Effect on DFS without it:** DFS would get trapped in an infinite loop moving back and forth endlessly between adjacent cells (ex: UP--> Down --> UP--> Down

3. (Analyze) Compare the visual paths generated by BFS and DFS in your simulation. Why is BFS guaranteed to be optimal in this specific grid, whereas DFS produces winding, suboptimal routes?

- BFS: Expands frontier nodes level-by-level in order of path length, guaranteeing that the first time a goal is reached, the path has the fewest possible steps.
- DFS: Blindly expands down a single search branch as deeply as possible before backtracking, causing it to take erratic, long winding paths around obstacles.

4. (Evaluate) If we scaled `visual\_grid\_game.py` up to a massive 1000x1000 grid, BFS and UCS might crash before finding food. According to the time and space complexity formulas from the lecture, contrast the memory bottlenecks of BFS versus DFS.

- **BFS Memory Bottleneck:** Stores all generated frontier nodes at depth **d**, leading to an exponential space complexity of $O(b^d)$ (where **b** is branching factor and **d** is depth). On large grids, memory exhausts rapidly, causing system crashes.

- DFS Memory Efficiency: Only stores nodes along the current search path, requiring linear space complexity of $O(m)$ (where m is maximum depth). DFS consumes drastically less RAM despite finding suboptimal routes.

Once Completed Get a PDF of the completed File and Push into the Week 03 brach in the Github Project

Finalize and Lock Lab 03 Documentation

Incomplete: 0/11 questions answered. Please provide detailed responses for all questions.



FACULTY OF COMPUTING