BSc (Hons) in **Information Technology Specialized in AI**

Faculty of Computing

IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Practical 03

> **Objective & Lecture Mapping:** In previous labs, we built a Simple Reflex Agent that moved randomly or reacted only to immediate adjacent cells. Today, we transition to a **Goal-Based/Planning Agent**. You will expose the environment's state space to the agent, allowing it to use **Breadth-First Search (BFS)**, **Depth-First Search (DFS)**, and **Uniform-Cost Search (UCS)** to simulate and find paths to the food before taking a physical action.

Part 1: Practical Implementation — Building the Search Agent

Step 1.1: Exposing the World Model

> Classical search algorithms require an abstract model of the environment to simulate future states. Currently, your agent is "blind" to the overall map.

1. Create a new Branch called Week_03 in your Forked Github Repo and work on the below Questions.
2. Open `visual_grid_game.py` .
3. Locate the `get_percept(self)` method.
4. Add three new keys to the dictionary to pass the global state to the agent:

```
'grid_size': (self.width, self.height)
'walls': list(self.walls)
'all_food': list(self.food_positions)
```

Step 1.2: Implementing BFS, DFS, and UCS

> You will implement three distinct uninformed search strategies. The core node expansion structure is identical; only the data structure for the **Frontier** changes!

1. Open `agent.py` and create a new class called `SearchAgent`.
2. Import required structures: `from collections import deque` and `import heapq`.
3. **BFS:** Create `def bfs_search(...)`. Use a FIFO queue (`deque.popleft()`). This explores the shallowest nodes first.
4. **DFS:** Create `def dfs_search(...)`. Use a LIFO stack (`list.pop()`). This explores the deepest nodes first.
5. **UCS:** Create `def ucs_search(...)`. Use a Priority Queue (`heapq.heappop()`) ordered by the total path cost $g(n)$.
6. For all three algorithms, you must maintain a `reached` set (or visited array) to track explored states. This converts your algorithm from a *Tree Search* to a *Graph Search*, preventing infinite loops.

Step 1.3: Executing and Comparing Offline Plans

> The agent must now form a complete plan and execute it step-by-step.

1. In your `SearchAgent.__init__`, add an empty list: `self.plan = []` and a config string `self.active_algo = 'BFS'`.
2. In `sense_and_act(self, percept)`, check if `self.plan` is empty.
3. If empty, find the closest food pellet from `percept['all_food']`, execute the search method matching `self.active_algo`, and store the resulting sequence of actions in `self.plan`.
4. Return the first action from the plan using `return self.plan.pop(0)`.
5. **Observation Task:** Change `self.active_algo` between 'BFS', 'DFS', and 'UCS' and run the simulation. Watch how DFS takes erratic, winding paths, while BFS and UCS take direct, optimal paths!

Part 2: Theoretical Evaluation

> Based on your implementation and Lecture 04, complete the following analytical questions.

1. (Remember) You built your search logic based on the environment coordinates. What is the fundamental difference between the "State Space" and the "Search Tree"?

The State Space represents the physical layout of the grid it is the finite collection of all unique, possible positions the agent could occupy. The Search Tree is the logical mapping constructed by the algorithm during execution; a single physical coordinate in the state space can appear as multiple separate nodes in the search tree if there are multiple different paths leading to it.

2. (Understand) In Step 1.2, you were instructed to use a `reached` set. In graph search theory, what specific problem does this set solve, and what would happen to your DFS agent without it?

The `reached` set converts the algorithm from a *Tree Search* to a *Graph Search* by maintaining a memory of historically visited states. If you removed it, your agent would instantly encounter infinite loops (e.g., infinitely stepping `Left`, then `Right`, then `Left` again) because the grid environment contains cyclic, reversible actions.

3. (Analyze) Compare the visual paths generated by BFS and DFS in your simulation. Why is BFS guaranteed to be optimal in this specific grid, whereas DFS produces winding, suboptimal routes?

BFS is guaranteed optimal on this grid because step costs are uniform (+1 per move). Because BFS checks all paths of length d before looking at paths of length $d+1$, the very first path that strikes the food is logically guaranteed to be the shortest physical distance. DFS, however, ignores distance and plunges blindly down one path until it hits a wall/boundary before unwinding, which produces excessively long, indirect routes.

4. (Evaluate) If we scaled `visual_grid_game.py` up to a massive 1000x1000 grid, BFS and UCS might crash before finding food. According to the time and space complexity formulas from the lecture, contrast the memory bottlenecks of BFS versus DFS.

If scaled massively, BFS would crash. BFS holds every unexplored node at the current depth boundary in RAM, giving it an exponential space complexity of $O(b^d)$ (where *b* is branching factor). In contrast, DFS shines regarding memory constraint; because it only holds a single active path and its direct siblings in the stack, its space complexity is merely linear $O(bm)$ making it computationally capable of surviving a massive grid, even if the resulting route is terrible.

Once Completed Get a PDF of the completed File and Push into the Week 03 brach in the Github Project

Finalize and Lock Lab 03 Documentation

Incomplete: 0/11 questions answered. Please provide detailed responses for all questions.