



BSc (Hons) in **Information Technology**
Specialized in AI

IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing

Practical 03

Objective & Lecture Mapping: In previous labs, we built a Simple Reflex Agent that moved randomly or reacted only to immediate adjacent cells. Today, we transition to a **Goal-Based/Planning Agent**. You will expose the environment's state space to the agent, allowing it to use **Breadth-First Search (BFS)**, **Depth-First Search (DFS)**, and **Uniform-Cost Search (UCS)** to simulate and find paths to the food before taking a physical action.

Part 1: Practical Implementation — Building the Search Agent

Step 1.1: Exposing the World Model

Classical search algorithms require an abstract model of the environment to simulate future states. Currently, your agent is "blind" to the overall map.

1. Create a new Branch called Week_03 in your Forked Github Repo and work on the below Questions.
2. Open `visual_grid_game.py` .
3. Locate the `get_percept(self)` method.
4. Add three new keys to the dictionary to pass the global state to the agent:

```
'grid_size': (self.width, self.height)
'walls': list(self.walls)
'all_food': list(self.food_positions)
```

Step 1.2: Implementing BFS, DFS, and UCS

You will implement three distinct uninformed search strategies. The core node expansion structure is identical; only the data structure for the **Frontier** changes!

1. Open `agent.py` and create a new class called `SearchAgent`.
2. Import required structures: `from collections import deque` and `import heapq`.
3. **BFS:** Create `def bfs_search(...)`. Use a FIFO queue (`deque.popleft()`). This explores the shallowest nodes first.
4. **DFS:** Create `def dfs_search(...)`. Use a LIFO stack (`list.pop()`). This explores the deepest nodes first.
5. **UCS:** Create `def ucs_search(...)`. Use a Priority Queue (`heapq.heappop()`) ordered by the total path cost $g(n)$.
6. For all three algorithms, you must maintain a `reached` set (or visited array) to track explored states. This converts your algorithm from a *Tree Search* to a *Graph Search*, preventing infinite loops.

Step 1.3: Executing and Comparing Offline Plans

The agent must now form a complete plan and execute it step-by-step.

1. In your `SearchAgent.__init__`, add an empty list: `self.plan = []` and a config string `self.active_algo = 'BFS'`.
2. In `sense_and_act(self, percept)`, check if `self.plan` is empty.
3. If empty, find the closest food pellet from `percept['all_food']`, execute the search method matching `self.active_algo`, and store the resulting sequence of actions in `self.plan`.
4. Return the first action from the plan using `return self.plan.pop(0)`.
5. **Observation Task:** Change `self.active_algo` between 'BFS', 'DFS', and 'UCS' and run the simulation. Watch how DFS takes erratic, winding paths, while BFS and UCS take direct, optimal paths!

Part 2: Theoretical Evaluation

Based on your implementation and Lecture 04, complete the following analytical questions.

1. (Remember) You built your search logic based on the environment coordinates. What is the fundamental difference between the "State Space" and the "Search Tree"?

The State Space is the set of all possible states that can be reached from the initial state by applying actions.

The Search Tree is the structure created by the search algorithm while exploring the state space. Its nodes represent states, and its branches represent actions.

In simple words:

State Space → All possible states in the problem.

Search Tree → The states and paths explored by the search algorithm.

The state space as all states reachable from the initial state and explains that tree search generates successors while exploring the state space.

2. (Understand) In Step 1.2, you were instructed to use a `reached` set. In graph search theory, what specific problem does this set solve, and what would happen to your DFS agent without it?

The reached set keeps track of states that have already been explored. It prevents the search algorithm from visiting the same state repeatedly.

Without the reached set, DFS could enter a loop by repeatedly visiting the same states.

For example:

$A \rightarrow B \rightarrow A \rightarrow B \rightarrow A \rightarrow B \dots$

The DFS agent could continue exploring the same path and may never reach the food.

Therefore, the reached set helps prevent repeated states and infinite loops.

This is especially important for DFS because the lecture explains that DFS can get stuck going deep in the wrong path

3. (Analyze) Compare the visual paths generated by BFS and DFS in your simulation. Why is BFS guaranteed to be optimal in this specific grid, whereas DFS produces

winding, suboptimal routes?

BFS expands the shallowest unexpanded node first. Therefore, it explores the grid level by level.

In this grid, every movement has the same cost (one step). Therefore, when BFS finds the food, it has found the path with the minimum number of steps.

So, BFS is optimal in this grid.

DFS, on the other hand, expands the deepest unexpanded node first. It follows one path deeply before exploring other possible paths. Therefore, it can take a long or winding path even when a shorter path exists.

So:

BFS → shortest path when every step has equal cost

DFS → may find a longer path

BFS → optimal

DFS → non-optimal

BFS is optimal when the cost is 1 per step, while DFS is non-optimal.

4. (Evaluate) If we scaled `visual\_grid\_game.py` up to a massive 1000x1000 grid, BFS and UCS might crash before finding food. According to the time and space complexity formulas from the lecture, contrast the memory bottlenecks of BFS versus DFS.

BFS: Requires more memory because it stores many nodes at the same time. Space complexity: $O(b^{(d+1)})$

b = branching factor

d = depth of the shallowest solution

DFS: Uses less memory because it mainly stores the current path and frontier.

Space complexity: $O(bm)$

m = maximum depth of the search

Conclusion:

BFS: High memory usage.

DFS: Lower memory usage but may explore very deep wrong paths.

Once Completed Get a PDF of the completed File and Push into the Week 03 brach in the Github Project

Finalize and Lock Lab 03 Documentation

Incomplete: 0/11 questions answered. Please provide detailed responses for all questions.



FACULTY OF COMPUTING