



BSc (Hons) in **Information Technology**
Specialized in AI

IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing

Practical 01

Objective & Lecture Mapping: Recall that an intelligent agent acts within a continuous loop: Sensors generate percept sequences, and Actuators execute actions to maximize a Performance measure. Use this sheet to execute practical modifications and incrementally evaluate your design against Lecture 01 and 02 theory (from basic recall to analytical classification).

Part 1: Code Analysis & PEAS Evaluation

Task 0 : Setting up and getting the starter Code

1. Go to the [Git Hub Repo](#). Create a Fork of this Git Repo to your Personal Github Profile. Open it using your favourite IDE and follow the below instruction to complete the practical. The base code is in the "master" brach of the repo.

Task 1.1: The Environment State (`__init__`)

1. (Remember) List the four components of the PEAS framework discussed in Lecture 01.

Sensors - The mechanisms through which the agent perceives the environment (e.g., `get_percept()` method)

2. (Understand) Look at the `VisualGridHuntGame.__init__` method. Which specific variables in this code represent the physical "Environment (E)" state?

including spatial layout, objects, and entities.

3. (Analyze) Based on the variables initialized (specifically `self.opponents`), classify this baseline environment as "Single-Agent" or "Multi-Agent". Briefly justify your choice.

agents, making it fundamentally a multi-agent environment.

Task 1.2: The Perception Subsystem (`get_percept`)

4. (Remember) Define what a "percept sequence" is according to Lecture 01.

The percept sequence grows continuously as the agent interacts with the environment

5. (Understand) Which component of the PEAS framework does the `get_percept()` method represent in our code?

`remaining_food` - count of remaining food pellets

The method serves as the interface between the environment and the agent's decision-making process.

6. (Evaluate) Based on the exact dictionary returned by `get_percept()` , is this environment "Fully Observable" or "Partially Observable"? Explain why based on what the agent can and cannot see.

of the environment state (position, opponents, obstacles), this is classified as a fully observable environment. The agent knows everything necessary for rational decision-making.

Task 1.3: Action Execution (`execute_action`)

7. (Understand) When `execute_action()` deducts points for hitting a wall, which PEAS component is being actively updated?

Eating food: `self.score += 20` (positive reward)
Collision with opponent: `self.score -= 50` (heavy penalty)

8. (Evaluate) Why is it structurally important that this metric evaluates changes in the external environment state (hitting a wall) rather than the agent's internal processing effort?

"Right thing" refers to actions that maximize performance measure in the environment

Part 2: Guided Modification & Deep Theory Mapping

Follow the implementation instructions to inject a new hazard, then answer the questions to map your code changes back to the theoretical nature of the environment.

Step 2.1: Extending the Environment Initialization (`__init__`)

1. **Implementation Instructions:** Declare a new trap collection attribute (e.g., `self.toxic_traps = set()`) inside `__init__`. Populate it with coordinate tuples safely avoiding position `(0, 0)`, walls, and food.

9. (Understand) If you successfully add `self.toxic_traps` to the environment but intentionally **hide** this data from the agent's sensors, how does this specifically alter the environment's "Observability" classification?

sensors.

Step 2.2: Updating the Perception Subsystem (`get_percept`)

1. **Implementation Instructions:** Locate `get_percept(self)` and add a new boolean sensor key (e.g., `'smells_toxin': tuple(self.agent_pos) in self.toxic_traps`) to the dictionary returned to the agent loop.

10. (Analyze) By adding `'smells_toxin'`, you expand the agent's percept sequence. Explain how this specific sensor helps the agent act with "Rationality" (maximizing expected utility).

- Can avoid traps when detected
 - Expected utility per move: Higher because negative outcomes are avoided
- The sensor transforms the agent from a "blind" actor to an "informed" rational actor.

Step 2.3: Modifying Action Execution & Visual Rendering (`execute_action` & `draw_grid`)

1. **Implementation Instructions:** In `execute_action`, check if the updated `self.agent_pos` intersects with `self.toxic_traps` to decrement `self.score` by 15 points. In `draw_grid`, iterate through traps to render custom purple shapes on the canvas.

11. (Remember) You programmed a severe score penalty for stepping on a trap to avoid metric exploitation. What was the classic "Vacuum World Exploit" example discussed in Lecture 01 that illustrated the danger of faulty metrics?

The trap penalty ensures the agent cannot exploit the environment without consequence.

Finalize and Lock Lab 01 Analytical Evaluation



FACULTY OF COMPUTING