BSc (Hons) in **Computer Science**

Faculty of Computing

SE3062 : Intelligent Systems

Year 3 · Semester 1 · 2026

Practical 07

> **Module Objective:** In previous weeks, your Drow Ranger agent used A* Search to find a physical path to the goal. However, it blindly assumed every non-wall tile was safe. Today, we implement a **Knowledge Base (KB)** and a **Forward Chaining Inference Engine**. Your agent must now mathematically prove a cell is logically *Feasible* before taking a step, using real-time rules about map vision and enemy threats.

> **Before you start:** This lab continues the project from Labs 1–4. Open the same project and check that `SearchAgent.astar_search()` in `agent.py` works.
>
> - Parts 1, 2 & 4: new files (`logic_engine.py` , `test_logic.py`) in the project folder.
> - Part 3: edit your existing `agent.py` .
> - **Create a separate branch `lab-07` and start your work there. When finished, commit your code and push the branch**, as you did in Labs 1–4.
> - **Upload this worksheet's answered PDF to the submission portal.**

Part 1: The Logic Engine Architecture

Step 1.1: Building the Knowledge Base (KB)

> Instead of hardcoding hundreds of nested `if-else` statements in our agent's movement logic, we will build a declarative Knowledge Base. You need to design a Python class that stores **Facts** (current percepts) and **Rules** (Horn Clauses).

1. Create a new file named `logic_engine.py` .
2. Implement a `KnowledgeBase` class based on the following structural requirements:

```
CLASS KnowledgeBase:
   // Attributes
```

```
    DECLARE facts AS Set                    // To store unique string fact
    DECLARE rules AS List                   // To store rules as Tuples: (

    // Methods
    FUNCTION tell_fact(fact_string):
        ADD fact_string TO facts

    FUNCTION tell_rule(premise_list, conclusion_string):
        APPEND Tuple(premise_list, conclusion_string) TO rules

    FUNCTION clear_facts():
        EMPTY the facts Set
```

Part 2: Implementing Forward Chaining

Step 2.1: The Inference Algorithm

> The agent needs an Inference Engine to deduce new information from its raw sensors. Translate the following Data-Driven **Forward Chaining** algorithm into a Python method inside your `KnowledgeBase` class.

1. Write the `forward_chain()` method.
2. Ensure you use a `while` loop that continues to iterate over the rules until a full pass results in absolutely no new facts being deduced.

```
FUNCTION forward_chain():
    DECLARE new_facts_added = TRUE

    WHILE new facts added == TRUE:
        new_facts_added = FALSE

        FOR EACH (premises, conclusion) IN rules:
            IF conclusion IS NOT IN facts:

                // Modus Ponens Check
                IF ALL premises ARE IN facts:
```

```
        ADD conclusion TO facts
        new_facts_added = TRUE
```

Part 3: Hooking Logic into the Grid Game

Step 3.1: Defining the Game Constraints

> Now we translate the game's safety constraints into our logic engine using Propositional Logic.

1. In `agent.py`, add `from logic_engine import KnowledgeBase`, then create the KB in `SearchAgent.__init__`: `self.kb = KnowledgeBase()`.
2. Use your `tell_rule` method to define the following safety rules:
   Rule 1: `TargetVisible ∧ HasDust ⇒ SafeToEngage`
   Rule 2: `SafeToEngage ∧ BloodseekerMissing ⇒ Retreat`

The game does not produce these facts, so you supply them per tile as a dictionary: `{(x, y): [facts]}`. A tile where `Retreat` is deduced is unsafe to enter.

Step 3.2: Validating Feasibility in A*

> Modify your existing A* pathfinding algorithm to consult the Knowledge Base before expanding a node.

1. Add a parameter `tile_facts=None` to `astar_search()` (treat `None` as `{}`).
2. Locate the neighbor-generation loop in your A* code (where you normally check for physical walls).
3. Before adding a neighbor to the `open_list`, clear the KB facts.
4. Feed that tile's facts into the KB: `for fact in tile_facts.get(successor, []): self.kb.tell_fact(fact)`.
5. Run `self.kb.forward_chain()`.
6. If `'Retreat'` is deduced and exists in `self.kb.facts`, mark the tile as **Infeasible**. Skip it (do not add it to the open list), even if it is physically reachable.

Step 3.3: Run It in the Grid

1. In `sense_and_act()`, define sample facts and pass them to A*:

```
tile facts = {
    (1, 0): ['TargetVisible', 'HasDust', 'BloodseekerMissing'],  # dedu
    (0, 1): ['TargetVisible', 'HasDust'],                        # Safe
}
self.plan = self.astar_search(position, nearest_food, walls, grid_size,
```

2. Run `visual_grid_game.py`. The agent should never step onto `(1, 0)`.

Part 4: Self-Evaluation Test Cases

4.1 Automated Validation

Create a file named `test_logic.py`. Copy and run the following Python assert statements to verify your Forward Chaining engine works correctly mathematically before you attempt to integrate it into the visual grid.

```
from logic_engine import KnowledgeBase

def test_forward_chaining():
    kb = KnowledgeBase()

    # Add Domain Rules
    kb.tell_rule(['TargetVisible', 'HasDust'], 'SafeToEngage')
    kb.tell_rule(['SafeToEngage', 'BloodseekerMissing'], 'Retreat')

    # Test Case 1: Safe Engagement
    kb.clear_facts()
    kb.tell_fact('TargetVisible')
    kb.tell_fact('HasDust')
    kb.forward_chain()
    assert 'SafeToEngage' in kb.facts, "Test 1 Failed: Should deduce Sa
    assert 'Retreat' not in kb.facts, "Test 1 Failed: Should NOT deduce

    # Test Case 2: Unsafe Engagement (Bloodseeker Missing)
    kb.clear_facts()
```

```
    kb.tell_fact('TargetVisible')
    kb.tell_fact('HasDust')
    kb.tell fact('BloodseekerMissing')
    kb.forward_chain()
    assert 'Retreat' in kb.facts, "Test 2 Failed: Should deduce Retreat

    print("✅ All Logic Engine Test Cases Passed!")

if __name__ == "__main__":
    test_forward_chaining()
```

Part 5: Theory-to-Implementation Mapping

> Based on the code you just wrote and the lecture on Logical Reasoning, complete the following analytical questions to explain *how* your code implements the theory.

1. Reachability vs. Feasibility (Apply)

In Step 3.2, you modified the A* algorithm's neighbor-generation loop. How does your new code differentiate between checking if a node is "Reachable" (like a wall collision) versus checking if it is "Feasible"? Explain how the Knowledge Base enforces feasibility.

Reachability concerns physical access: the agent must stay inside the grid and cannot move through walls. In my implementation, successors() checks these conditions before yielding a neighbouring tile. Feasibility adds a logical safety check. A tile may be physically accessible but still be rejected because its facts imply that the agent should retreat.

For each candidate neighbour, A* calls clear_facts(), adds that tile's facts, and runs forward_chain(). If Retreat is inferred, the continue statement skips the neighbour before it enters the frontier. For tile (1, 0), TargetVisible and HasDust imply SafeToEngage; together with BloodseekerMissing, this implies Retreat. The integration test therefore finds the alternative path Up, Right, Right, Down. Clearing facts between tiles prevents conclusions from one tile affecting another. Under the worksheet's rule, a tile is allowed when Retreat is not inferred; this is not a proof that an unknown tile is safe.

2. Declarative vs. Procedural Paradigms (Analyze)

Why did we build a `KnowledgeBase` class with a `forward_chain()` loop instead

of simply writing `if 'TargetVisible' in percepts and 'HasDust' in percepts:` directly inside the agent's movement code? What happens to the agent's code complexity if we add 50 new game rules?

The knowledge base separates what the agent knows from how it moves. Facts and rules are stored as data, while one general inference loop applies them. This also supports chains of deductions: SafeToEngage can be derived first and then used to infer Retreat. A direct if statement can handle one condition, but many interacting conditions would make the movement code harder to read, update and test.

If 50 new rules are added, they can be registered through tell_rule() without adding 50 separate conditions to A*. The movement code can keep the same check for Retreat, provided the new rules use that decision convention. This reduces maintenance complexity, but it does not make inference free: the engine must check more rules and may need additional passes. New rules still need testing for their intended interactions.

3. Modus Ponens & Horn Clauses (Understand)

The rule `['TargetVisible', 'HasDust'] ⇒ 'SafeToEngage'` is formally known as a Horn Clause. Briefly explain how your Python implementation of the `forward_chain()` `while` loop acts as a mathematical execution of the *Modus Ponens* inference rule.

Modus Ponens states that if a premise P is true and P implies Q, then Q can be concluded. Here, P is the conjunction TargetVisible AND HasDust, and Q is SafeToEngage. The expression all(premise in self.facts for premise in premises) checks that every required premise is known. When the check succeeds, the engine adds the rule's conclusion to the facts set.

This rule is a definite Horn clause: it has a conjunction of positive premises and one positive conclusion. Newly inferred facts can trigger other rules, so the while loop repeats until a complete pass adds nothing

new. Checking that the conclusion is not already present prevents repeated additions. With the finite facts and rules used here, this reaches a fixed point and terminates. The reversed-rule test confirms that Retreat is still inferred even when its rule is checked before the rule that produces SafeToEngage.

Finalize and Lock Lab 07 Implementation

✅ Lab 05 Theory-to-Implementation Mapping completed!



FACULTY OF COMPUTING