



CSS

Tutorial

- <http://www.w3schools.com/css/default.asp>

What is CSS?

- CSS stands for **Cascading Style Sheets**
- Styles define **how to display** HTML elements
- Styles were added to HTML 4.0 **to solve a problem**
- **External Style Sheets** can save you a lot of work
- Multiple style definitions will **cascade** into one

Examples

- CSS Zen Garden
- <http://www.csszengarden.com/>
- <http://www.mezzoblue.com/zengarden/alldesigns/>

Examples

CSS contents

```
p.right {text-align: right}
```

HTML contents

```
<p class="center">
```

This paragraph will be center-aligned.

```
</p>
```

More exciting ideas

- What is possible to do with CSS?
 - Image gallery
 - Web site with user chosen style
 - ...

CSS inserting strategies

External Style Sheet	<pre><head> <link rel="stylesheet" type="text/css" href="mystyle.css" /> </head></pre>
Internal Style Sheet	<pre><head> <style type="text/css"> hr {color: sienna} p {margin-left: 20px} body {background-image: url("images/back40.gif")} </style> </head></pre>
Inline Styles	<pre><p style="color: sienna; margin-left: 20px"> This is a paragraph </p></pre>

Cascading Order

- Browser default
- External Style Sheet
- Internal Style Sheet (inside the `<head>` tag)
- Inline Style (inside HTML element)

CSS syntax

- The CSS syntax is made up of three parts:
 - selector
 - property
 - value

selector {property: value}

```
body {color: black}
```

```
p {  
  text-align: center;  
  color: black;  
  font-family: arial  
}
```

Grouping & Class

- Grouping

```
h1,h2,h3,h4,h5,h6 { color: green }
```

- Class selector

```
p.right {text-align: right}  
p.center {text-align: center}
```

```
.right {text-align: right}
```

```
<p class="center">  
This paragraph will be center-aligned.  
</p>
```

Grouping & Class (2)

- Multiple Class

```
p.right {text-align: right; color: red;}  
p.green1 {color: green;}
```

```
<p class="green1 right">
```

This paragraph will be center-aligned.

```
</p>
```

Class essence

- Separates information using structure:
 - Title
 - Contents
 - Menu
 - Header, footer
 - ...
- Reuses same styles if structure has a model
 - Example: title-content block

ID & comments

- id selector

```
p#para1 { text-align: center; color: red }
```

```
#right { text-align: right }
```

```
<p id="para1">
```

This paragraph will be center-aligned.

```
</p>
```

- comments

```
/* This is a comment */
```

Pseudo-Class

- It is possible to use pseudo-classes in CSS

selector:pseudo-class {property: value}

```
a:link {color: #FF0000}           /* unvisited link */
a:visited {color: #00FF00}        /* visited link */
a:hover {color: #FF00FF}          /* mouse over link */
a:active {color: #0000FF}         /* selected link */
```

```
a.red:visited {color: #FF0000}
```

```
<a class="red" href="...">CSS Syntax</a>
```

- Pseudo-element

```
p:first-letter { color: #FF0000 }
```

```
p:first-line { color: #00FF00 }
```

Media types

Media Type	Description
all	all media type devices
aural	speech and sound synthesizers
braille	braille tactile feedback devices
embossed	paged braille printers
handheld	small or handheld devices
print	printers
projection	projected presentations, like slides
screen	computer screens
tty	media using a fixed-pitch character grid, like teletypes and terminals
tv	television -type devices

Combining

```
div p { text-indent:25px }
```

```
<div>
```

```
<p>
```

First paragraph in div. This paragraph will be indented.

```
</p>
```

```
<p>
```

Second paragraph in div. This paragraph will not be indented.

```
</p>
```

```
</div>
```

CSS Attribute Selectors

```
[onclick]
```

```
{
```

```
    color: blue;
```

```
}
```

```
<p onclick="...">
```

```
    This paragraph is blue.
```

```
</p>
```

Problems

- Browsers has different default CSS
- Browsers interpret CSS differently

Hints

- Always force refresh if style sheet is in .css file
- CSS Debuggers
 - Firebug (Firefox add-in)
 - IE developer toolbar

Future

- Min-width, min-height
- Outline
- counter-increment ☺
- ...

CSS Box model

```
div.a { color: red; }
```

```
div.b { color: green; }
```

```
<div class="b a"> Tekstas </div>
```

Can be used:

- by blind people
- to help users learning to read
- to help users who have reading problems
- for home entertainment
- in the car
- by print-impaired communities

Klausimai?

- Kokie būtų privalumai ir trūkumai jei neatskirtume duomenų nuo stiliaus?
 - T.y. HTML ir CSS?
 - Duokite pavyzdį iš kitos srities

- CSS stands for **C**ascading **S**tyle **S**heets
 - Kodėl yra žodis “Cascading” ir ką jis reiškia?
- Ar galima pakeisti elemento stilių, pagal tai, kokius atributus jis turi?