

Mô tả dữ liệu

Output crawl Twitter account:

`id: Int64`

The integer representation of the unique identifier for this User. This number is greater than 53 bits and some programming languages may have difficulty/silent defects in interpreting it. Using a signed 64 bit integer for storing this identifier is safe. Use `id_str` to fetch the identifier to be safe. See Twitter IDs for more information. Example:

Example:

`"id": 6253282`

`id_str String`

The string representation of the unique identifier for this User. Implementations should use this rather than the large, possibly un-consumable integer in `id`.

Example:

`"id_str": "6253282"`

`name String`

The name of the user, as they've defined it. Not necessarily a person's name. Typically capped at 50 characters, but subject to change.

Example:

`"name": "Twitter API"`

`screen_name String`

The screen name, handle, or alias that this user identifies themselves with. `screen_names` are unique but subject to change. Use `id_str` as a user identifier whenever possible. Typically a maximum of 15 characters long, but some historical accounts may exist with longer names.

Example:

`"screen_name": "twitterapi"`

`location String`

Nullable . The user-defined location for this account's profile. Not necessarily a location, nor machine-parseable. This field will occasionally be fuzzily interpreted by the Search service.

Example:

`"location": "San Francisco, CA"`

`derived Arrays of Enrichment Objects`

Enterprise APIs only Collection of Enrichment metadata derived for user. Provides the Profile Geo Enrichment metadata. See referenced documentation for more information, including JSON data dictionaries.

Example:
`"derived":{"locations": [{"country":"United States","country_code":"US","locality":"Denver"}]}`

url String
 Nullable . A URL provided by the user in association with their profile.
 Example:
`"url": "https://developer.twitter.com"`

description String
 Nullable . The user-defined UTF-8 string describing their account.
 Example:
`"description": "The Real Twitter API."`

protected Boolean
 When true, indicates that this user has chosen to protect their Tweets. See About Public and Protected Tweets.
 Example:
`"protected": true`

verified Boolean
 When true, indicates that the user has a verified account. See Verified Accounts.
 Example:
`"verified": false`

followers_count Int
 The number of followers this account currently has. Under certain conditions of duress, this field will temporarily indicate "0".
 Example:
`"followers_count": 21`

friends_count Int
 The number of users this account is following (AKA their "followings"). Under certain conditions of duress, this field will temporarily indicate "0".
 Example:
`"friends_count": 32`

listed_count Int
 The number of public lists that this user is a member of.
 Example:
`"listed_count": 9274`

favourites_count Int
 The number of Tweets this user has liked in the account's lifetime. British spelling used in the field name for historical reasons.
 Example:
`"favourites_count": 13`

statuses_count Int
 The number of Tweets (including retweets) issued by the user.
 Example:
`"statuses_count": 42`

created_at String
The UTC datetime that the user account was created on Twitter.
Example:
"created_at": "Mon Nov 29 21:18:15 +0000 2010"

profile_banner_url String
The HTTPS-based URL pointing to the standard web representation of the user's uploaded profile banner. By adding a final path element of the URL, it is possible to obtain different image sizes optimized for specific displays. For size variants, please see User Profile Images and Banners .
Example:
"profile_banner_url": "https://si0.twimg.com/profile_banners/819797/1348102824"

profile_image_url_https String
A HTTPS-based URL pointing to the user's profile image.
Example:
"profile_image_url_https":
"https://abs.twimg.com/sticky/default_profile_images/default_profile_normal.png"

default_profile Boolean
When true, indicates that the user has not altered the theme or background of their user profile.
Example:
"default_profile": false

default_profile_image Boolean
When true, indicates that the user has not uploaded their own profile image and a default image is used instead.
Example:
"default_profile_image": false

withheld_in_countries Array of String
When present, indicates a list of uppercase two-letter country codes this content is withheld from. Twitter supports the following non-country values for this field:
"XX" - Content is withheld in all countries "XY" - Content is withheld due to a DMCA request.
Example:
"withheld_in_countries": ["GR", "HK", "MY"]

withheld_scope String
When present, indicates that the content being withheld is a "user."
Example:
"withheld_scope": "user"

Output crawl tweet:

```
_type: str
cashtags: list[str]
conversationId: int
coordinates: Optional[Coordinates] = None
date: datetime
hashtags: list[str]
id: int
id_str: str
inReplyToTweetId: int | None = None
inReplyToUser: UserRef | None = None
lang: str
likeCount: int
links: list[TextLink]
media: Optional["Media"] = None
mentionedUsers: list[UserRef]
place: Optional[Place] = None
quoteCount: int
quotedTweet: Optional["Tweet"] = None
rawContent: str
replyCount: int
retweetCount: int
retweetedTweet: Optional["Tweet"] = None
source: str | None = None
sourceLabel: str | None = None
sourceUrl: str | None = None
url: str
user: User
viewCount: int | None = None
```